



" විශිෂ්ට රාජ්‍ය සේවාවක් සඳහා ජය කපුවේදී "

ප්‍රධාන ලේකම් කාර්යාලය - බස්නාහිර පළාත
பிரதான செயலாளர் அலுவலகம் - மேல் மாகாணம்
OFFICE OF THE CHIEF SECRETARY - WESTERN PROVINCE



204, ඩෙන්සිල් කොබ්බෑකඩුව මාවත, බත්තරමුල්ල.
 204, டென்சில் கொப்பேகடுவ மாவத்தை, பத்தரமுல்ல.
 204, Denzil Kobbekaduwa Mawatha, Battaramulla.



| | | | | |
|---|---|--|---|--|
| ප්‍රධාන ලේකම් பிரதான செயலாளர் Chief Secretary | } | දුරකථන / தொலைபேசி / Telephone - 011 - 2092599 | } | ජනප්‍රිය දුරකථන பொதுத் தொலைபேசி / General Telephone - 011 - 2093000 |
| | | ෆැක්ස් / பெக்ஸ் / Fax - 011 - 2092601 | | |
| | | ඊ-මේල් / இணைப்புகள் / E-mail - chiefsecretary@wpc.gov.lk | | |

මගේ අංකය
 எனது இலக்கம்
 My No.

CSWP/ENG-CON/5-2/FI/1

ඔබේ අංකය
 உமது இலக்கம்
 Your No.

දිනය
 திகதி
 Date

2020.08.28

පළාත් ගොඩනැගිලි අධ්‍යක්ෂ/ වාරිමාර්ග අධ්‍යක්ෂ/ අධ්‍යක්ෂ (ඉංජිනේරු),
 සාමාන්‍යාධිකාරී, පළාත් බදු මාර්ග සංවර්ධන අධිකාරිය (බ.ප.),
 පළාත් සෞඛ්‍ය සේවා අධ්‍යක්ෂ, ප්‍රාදේශීය සෞඛ්‍ය අධ්‍යක්ෂ (කොළඹ, ගම්පහ, කළුතර)
 පළාත් පාලන කොමසාරිස් සහ සියලුම පළාත් පාලන ආයතන ලේකම්වරුන්,
 බස්නාහිර පළාතේ සියලුම ප්‍රාදේශීය ලේකම්වරුන්,
 ප්‍රාදේශීය ඉංජිනේරුවරුන්,

ගොඩනැගිලි ගාස්තු උපලේඛණය - 2020/2021

බස්නාහිර පළාතේ පළාත් සභාවේ මූල්‍ය රීති සංග්‍රහයේ රීති අංක 425 ප්‍රකාර ගොඩනැගිලි ඉදිකිරීම් වැඩි දියුණු කිරීම් සහ නඩත්තු කටයුතු සඳහා මුළු පිරිවැය ඇස්තමේන්තු පිළියෙල කර ගැනීමට උපයෝගී කරගත යුතු 2020 සැප්තැම්බර් 01 දින සිට වලංගු ගොඩනැගිලි ගාස්තු උපලේඛණය මේ සමඟ ඉදිරිපත් කරමි. තවද මෙම ලේඛණය බස්නාහිර පළාත් සභාවේ පළාත් ඉංජිනේරු කාර්යාංශයේ වෙබ් අඩවියෙන් (chiefsec.wpc.gov.lk/engi) බාගත හැක. මෙම ලේඛණය 2020.09.01 දින සිට නැවත දැනුම් දෙනතුරු වලංගු වේ.

02. මෙම ලේඛණයේ ඇතුළත් රේට් මිල ගණන් සඳහා එකතු කළ අගය මත බදු (VAT), එකතු කර නොමැත.

03. මෙම ගොඩනැගිලි ගාස්තු ලේඛණයේ සඳහන් මිල ගණන් සකසා ඇත්තේ බස්නාහිර පළාතේ දිස්ත්‍රික්ක තුනම ආවරණය වන පරිදිය. කෙසේ වුවද, මෙහි සඳහන් ද්‍රව්‍ය වල මිල හා ඇතැම් බල ප්‍රදේශ තුළ පවතින මිල ගණන් අතර සැලකිය යුතු වෙනස්කම් තිබේනම්, ඒ පිළිබඳව මා වෙත දැන්වීමට පියවර ගන්න. එවැනි විශේෂ අවස්ථාවකදී යම් බල ප්‍රදේශයකට පමණක් සීමාවන පරිදි මිල ගණන් සංශෝධනය කිරීමට පියවර ගත හැක. ඇලුමිනියම් සහ ලී වල මිල ගණන් හැර මූලික ගොඩනැගිලි ද්‍රව්‍ය වල මිල ගණන් තීරණය කර ඇත්තේ 2020 වසරේ පෙබරවාරි සහ මාර්තු මාස වල පැවති VAT රහිත මිල ගණන් පදනම් කරගෙනය. 2020.05.18 දින නිකුත් කරන ලද ඇලුමිනියම් වල මිල ගණන් ලේඛණය හා 2020.08.10 දින රාජ්‍ය දැව සංස්ථාව විසින් නිකුත් කරන ලද ලී මිල ගණන් ලේඛණය පදනම් කර ගෙන ඇලුමිනියම් හා ලී වල මිල ගණන් තීරණය කර ඇත. එම මිල ගණන් සඳහා වට්ටම් ඇතුළත් වී නැත.

04. මෙම රේට් මිල ගණන් පිළියෙල කර ගැනීමට උපයෝගී කරගෙන ඇති ගොඩනැගිලි ද්‍රව්‍ය සහ භාණ්ඩවල ප්‍රමිතිය (Specification), ගුණාත්මක බව (quality) සහ ඉදිකිරීම් නිමාව (Workmanship) ශ්‍රී ලංකා ප්‍රමිති (SLS), බ්‍රිතාන්‍ය ප්‍රමිති (BS - EN) සහ (A.S.T.M) ප්‍රමිතීන්ට අනුකූලව සහ ICTAD පිරිවිතර SCA/3/1, SCA/3/2, SCA/3/3, SCA/4(VOL - I), SCA/4(VOL - II), SCA/5, SCA/8 යන ප්‍රකාශනවල සඳහන් අවශ්‍යතාවයන් සහ ගුණාංගයන් සපුරාලන බව උපකල්පනය කරමිනි. ඒ අනුව මෙම මිල ගණන් උපයෝගී

| විදේශීය ප්‍රධාන ලේකම් பிரதான செயலாளர் Deputy Chief Secretary | ප්‍රධාන தலைவர் Administration Tel: 0112092606 Fax: 0112092609 dcsadmin@cs.wpc.gov.lk | පිරිස් හා පුහුණු ஆளும் மற்றும் பயிற்சி Personnel & Training Tel: 0112092631 Fax: 0112092647 dcstpt@cs.wpc.gov.lk | මූල්‍ය தீர் Finance Tel: 0112092640 Fax: 0112092636 dcsfinance@cs.wpc.gov.lk | සංලලුච්ඡි திட்டமிடல் Planning Tel: 0112092532 Fax: 0112092533 dsplan@cs.wpc.gov.lk | ඉංජිනේරු பொறியியல் Engineering Tel: 0112092501 Fax: 0112092505 dcs@eng.wpc.gov.lk | ප්‍රධාන අභ්‍යන්තර විමර්ශක பிரதான உள்நகல் சான்றாவரர் Chief Internal Auditor Tel: 0112092628 Fax: 0112092625 cia@cs.wpc.gov.lk | |
|--|---|---|---|---|--|---|--|
|--|---|---|---|---|--|---|--|

කර ගෙන මුළු පිරිවැය ඇස්තමේන්තු සැකසීමේ දී සහ එකී ඇස්තමේන්තු පාදක කරගෙන ගිවිසුම් වලට එළඹ ගෙවීම් කිරීමේ දී ඉහත ප්‍රකාශනවල අඩංගු ප්‍රමිතීන්ට අනුකූල ගොඩනැගිලි ද්‍රව්‍ය පමණක් උපයෝගී කර ගෙන පුහුණු ශ්‍රමිකයන්ගේ දායකත්වයෙන්ද යුතුව ඉදිකිරීම් සිදුවිය යුතු බව අවධාරණය කරනු කැමැත්තෙමි.

05. මෙම රේට් මිල ගණන් පදනම් කරගෙන පිළියෙල කරන ලද මුළු පිරිවැය ඇස්තමේන්තුව, උද්ධමනය හෝ වෙනත් හේතූන් නිසා ප්‍රසම්පාදන මාර්ගෝපදේශ සංග්‍රහයේ වගන්ති අංක 4.3.3 ප්‍රකාරව යාවත්කාලීන කර ගැනීමට අවශ්‍ය අවස්ථාවන්හිදී මිල විචලන සඳහා CIDA ආයතනයේ ප්‍රකාශිත ලංසු ලේඛන වල ඇතුළත් සූත්‍ර A හෝ B පදනම් කරගෙන රේට් මිල ලේඛණය වලංගු කළ දින සහ ඇස්තමේන්තු කරන දින අතර කාලවකවානුව තුළ සිදුව ඇති මිල විචලනය ගණනය කර ගැනීම සුදුසුය.

06. මෙම ගොඩනැගිලි ගාස්තු උපලේඛණයේ රේට් මිල ගණන් අදාළ කර ගෙන පිළියෙල කරනු ලබන මුළු පිරිවැය ඇස්තමේන්තු තාත්වික වනුයේ ප්‍රසම්පාදන සංග්‍රහයේ වගන්ති අංක 3.1, 3.2, 3.3, 3.4, 3.5, 3.6 සහ 3.8 හි සඳහන් ප්‍රසම්පාදන ක්‍රමවේද අනුගමනය කරමින් ඉටු කිරීමට අපේක්ෂිත “වැඩ” (Works) කොන්ත්‍රාත් සඳහා පමණි. වගන්ති අංක 3.7 හි සඳහන් සේව්‍යයාගේ සේවකයන් (එනම් සෘජු කම්කරු ශ්‍රමය, ද්‍රව්‍ය සහ උපකරණ යොදා Force Account යටතේ) හෝ සේව්‍යා විසින් ද්‍රව්‍ය සපයා ශ්‍රම කොන්ත්‍රාත් මත හෝ ප්‍රජා දායකත්වය යටතේ ඉදිකිරීමට අපේක්ෂිත වැඩ සඳහා මෙම රේට් මිල ගණන් වලංගු නොවන අතර එවැනි ඉදිකිරීම් සඳහා 20% ලාභාංශ සහ අනෙකුත් වියදම් සමානුපාතිකව අඩුකර මුළු පිරිවැය ඇස්තමේන්තු සකස් කළ යුතුවේ.

07. මෙම ගොඩනැගිලි ගාස්තු ලේඛනයේ වැඩ විස්තර සහ රේට් මිල ගණන් පදනම් කර ගෙන සකස් කර ගන්නා ප්‍රසම්පාදන ලියකියවිලි කට්ටලයට ඇතුළත් විය යුතු අනෙකුත් ලිපි ලේඛන සහ ගොඩනැගිලි ගාස්තු ලේඛණය පරිශීලනය කිරීමේදී සෑම නිලධාරියෙකු විසින්ම දැන සිටිය යුතු කරුණු සංක්ෂිප්තව ඇස්තමේන්තු අත්පොතේ (Estimating manual) හි ඇතුළත් කර ඇත. එම අත්පොත ඉහත වෙබ් අඩවියේ ඇතුළත් කර ඇත. මෙම අත්පොත නිරන්තරයෙන් යාවත්කාලීන වන ලේඛණයක් බැවින් වරින් වර වෙබ් අඩවියට ඇතුළු වී යාවත්කාලීන කරන ලද ලේඛණයේ (version) අංකය සමග සසඳා පරිශීලනයට ගත යුතු වේ.

08. පරිසරයට සිදුවන හානිය අවම කර ගැනීම සඳහා රජය විසින් නිකුත් කර ඇති චක්‍රලේඛ වල උපදෙස් ප්‍රකාර ගංගා වලින් ලබා ගන්නා වැලි වෙනුවට ශ්‍රී ලංකා ඉඩම් ගොඩකිරීම් හා සංවර්ධනය කිරීමේ සංස්ථාව (SLRDC) විසින් අලෙවි කරනු ලබන “washed off-shore sand” හෝ “manufactured sand ” යොදා ගත හැකි පරිදි රේට් මිල ගණන් ගලපා ඇත.

09. මෙම රේට් මිල ගණන් ගණනය කිරීමට පදනම් කර ගත් කම්කරු ගාස්තු, විශේෂිත ශ්‍රම කොන්ත්‍රාත්කරුවන්ගේ සේවා ගාස්තු, විශේෂිත උප කොන්ත්‍රාත්කරුවන්ගේ (එනම් ද්‍රව්‍ය සහ ශ්‍රමිකයන් සමඟ සේවා/ වැඩ සපයන්නන්ගේ) සේවා ගාස්තු, ගොඩනැගිලි ද්‍රව්‍ය මිල ගනන්, නිම් භාණ්ඩ වල මිල ගණන්, සහ ප්‍රවාහන ගාස්තු ඉහත වෙබ් අඩවියේ ඇතුළත් කර ඇත.

10. තරඟකාරී මිල ගණන් යටතේ ලංසු කැඳවීමේදී රේට් මිලක තාත්වික බව තීරණය වනුයේ විවිධ සාධක මතය. ඉන් ප්‍රධාන සාධක කිහිපයක් පහත දැක්වේ.

- I. කොන්ත්‍රාත්කරුවකු විසින් ප්‍රමාණ බිල්පතට අයත් වැඩ කොටස් ඉටු කරනු ලබන ආකාරය (එනම් පහත අයිතම අංක 11 “අ” සිට “ඇ” දක්වා වූ ක්‍රමවේද අතුරින් එකක් මත වීම)
- II. ඉටුකරනු ලබන ඉදිකිරීමේ අවධානම (risk) මත

- III. ඉදිකිරීමට අදාළ ප්‍රාරම්භක අයිතම (preliminaries) ප්‍රමාණ බිල්පතට ඇතුළත්ව තිබේද යන්න මත
- IV. කොන්ත්‍රාත්කරුවකු සතු උපකරණ සහ අනෙකුත් මෙවලම්
- V. ඉදිකිරීමක සීමිත කොටසක් පමණක් නිම කළ යුතුව තිබෙන අවස්ථාවක කම්කරු දායකත්වයට වඩා ද්‍රව්‍ය වල දායකත්වය වැඩි වීම, අඩුවීම සහ/ හෝ විශේෂිත උප කොන්ත්‍රාත්/ ශ්‍රම කොන්ත්‍රාත් ලබා දීම සීමිත වීම.
- VI. කොන්ත්‍රාත්කරුවන්ගේ ඉදිකිරීම් කළමනාකරණ හැකියාව
- VII. සේව්‍යාගේ මූල්‍ය හැකියාව, විශ්වාසනීයත්වය සහ සේව්‍යා විසින් නම් කරනු ලබන කොන්ත්‍රාත් කළමනාකරණයට සම්බන්ධ නිලධාරීන්ගේ ප්‍රවීණත්වය
- VIII. ඉදිකිරීමේ සංකීර්ණ බව හා ව්‍යාපෘතියේ භූගෝලීය පිහිටීම
- IX. කොන්ත්‍රාත්කරුවකු විසින් ගොඩනැගිලි ද්‍රව්‍ය මිලදී ගැනීමේදී එම ද්‍රව්‍ය සඳහා ලබා ගන්නා වට්ටම් සහ සහන ගෙවීම් කාලය මත
- X. ලංසුව ඉදිරිපත් කරන අවස්ථාවේ කොන්ත්‍රාත්කරු සතුව පවත්නා අනෙකුත් වැඩ වල වටිනාකම

මෙම සියළු කරුණු පදනම් කර ගෙන මුළු වර්ෂය සඳහා ස්ථාවර වූ තාත්වික රේට් මිල ගණනක් තීරණය කිරීම ප්‍රායෝගිකව අපහසු වේ. එබැවින් මෙම රේට් මිල ගණන් තීරණය කර ඇත්තේ මිලියන 150 ට අඩු වටිනාකමින් යුතු මහල් 5 කට පමණ සීමා වන ගොඩනැගිලි ඉදිකිරීම් කටයුතු සඳහා පහත අංක 11 හි සඳහන් ක්‍රමවේද අතුරින් එක් ක්‍රමවේදයක් අනුගමනය කරමින් මෙම ලේඛනයේ සඳහන් ප්‍රමිතීන්ට අනුකූල ගොඩනැගිලි ද්‍රව්‍ය සහ පුහුණු ශ්‍රමිකයන් යොදා ගනිමින් ඉදිකිරීම් ඉටුකරනු ලබන්නේ යැයි යන උපකල්පනය මත රඳෙමිනි.

එම නිසා මෙම රේට් මිල ගනන් හුදෙක් ඇස්තමේන්තුගත රේට් මිල ගනන් බවට අවධාරණය කරනු ලබන අතර ඒවායේ නිරවද්‍යතාව බොහෝ දුරට ඉදිකිරීමේ ස්වභාවය, භූමියේ පිහිටීම සහ සංකීර්ණත්වය මත රඳා පවතී.

මෙම රේට් මිල ගනන් වලට අයත් නොවන රේට් මිල ගනන් තීරණය කිරීමේදී මෙම ලේඛනයට පදනම් කර ගත් කම්කරු ගාස්තු සමඟ ඉදිකිරීම් ඉටුකිරීමට යෝජිත ප්‍රදේශයෙන් ලබාගත් ද්‍රව්‍ය මිල ගනන් හෝ මෙම ලේඛනයට පදනම් කර ගත් මූලික මිල ගනන් සමඟ 20% ලාභාංශය ඇතුළත් වන පරිදි ඉදිකිරීම් ඉටුකිරීමට උපයෝගී කර ගත හැකි ක්‍රමවේදය “method statement” පිළිබඳව නිසි අවබෝධයෙන් යුතුව පිළියෙල කර ප්‍රාදේශීය ඉංජිනේරුගේ අනුමැතිය ගත යුතු අතර ගොඩනැගිලි අධ්‍යක්ෂ/ අධ්‍යක්ෂ ඉංජිනේරුගේ අවධානයට යොමුකර අනාගතයේදී එවැනි විශේෂිත රේට් මිල ගනන් විශ්ලේෂණ නැවත පරිශීලනය සඳහා ඩිජිටල් තාක්ෂණයෙන් ගබඩා කිරීම සඳහා පියවර ගත යුතු වේ.

11. තවද මෙම රේට් මිල ගනන් ගණනය කිරීම සඳහා නිරන්තරයෙන් එකතුවන නවීන තාක්ෂණ “මෙවලම්” උපකරණ යොදා ගනිමින් අඩු ශ්‍රමයක් උපයෝගී කර ගෙන ඉටු කරනු ලබන කාර්යයන් සඳහා සම්ප්‍රදායික මිල විශ්ලේෂණ පදනම් කර ගෙන ගණනය කරනු ලබන රේට් මිල ගනන් තාත්වික නොවන බව පසුගිය වසර 10 තුළ සිදු කළ අධ්‍යයනයේදී නිරීක්ෂණය විය. ඒ අනුව වර්තමානයට ගැලපෙන පරිදි “Work study” සහ “Method study” මගින් තහවුරු කරගත් ගොඩනැගිලි මිල විශ්ලේෂණයක අවශ්‍යතාව පිළිබඳව අවධාරණය කරනු ලබන අතර එවැනි ලේඛනයක් සැකසෙනතුරු එතෙක් පහත ක්‍රම අතුරින් වඩාත් සුදුසු යැයි සහ මධ්‍ය පරිමාණයේ ගොඩනැගිලි ඉදිකිරීම් සඳහා CIDA ආයතනයේ ලියාපදිංචි කොන්ත්‍රාත්කරුවන් වැඩි දෙනෙකු විසින් අනුගමනය කරනු ලබන ක්‍රමවේද මත රඳෙමින් මෙම රේට් මිල විශ්ලේෂණය කර ඇත.

එසේ විශ්ලේෂණය කරන ලද මිල ගනන් වල තාක්ෂණික බව ඉදිකිරීම් කර්මාන්ත ක්ෂේත්‍රයේ නියුතුවන් සමඟ සාකච්ඡා කර තහවුරු කර ඇත.

(අ) කොන්ත්‍රාත්කරු විසින් භාණ්ඩ මිලදී ගෙන තම සාප්පු කම්කරුවන් (පුහුණු සහ නුපුහුණු) යොදවා ඉටු කරනු ලබන කාර්යයන් (මෙම කාර්යයන් විශ්ලේෂණය සඳහා CIDA ආයතනයෙන් මුද්‍රණය කර අලෙවි කරන මිල විශ්ලේෂණ ලේඛනය හැකිතාක් දුරට පාදක කර ගනිමින්)

(ආ) ප්‍රධාන කොන්ත්‍රාත්කරු ද්‍රව්‍ය සපයා විශේෂිත සේවා සපයන උප කොන්ත්‍රාත් ශ්‍රමිකයන් යොදවා (නිදසුන : පින්තාරු කිරීම)

(ඇ) උප කොන්ත්‍රාත්කරුවන් ලෙස විශේෂිත උප කොන්ත්‍රාත්කරුවන් විසින් (ද්‍රව්‍ය සහ ශ්‍රමය සපයා) ඔවුන් විසින් ඉටු කරනු ලබන කාර්යයන් (නිදසුන : ජල ප්‍රතිරෝදනය)

12. මෙම රේට් මිල ගණන් තුළ ඇතුළත් 20% උඩ්ස් හා ලාභාංශ සඳහා CIDA ආයතනයේ නිර්දේශ පරිදි යම් ඉදිකිරීමකට අදාළ වන්නා වූ ප්‍රාරම්භක අයිතම (preliminaries) වල මිල අඩංගු නොවේ. එබැවින් යම් වැඩකට ප්‍රමාණ බිල්පත පිළියෙල කිරීමේදී ඉදිකිරීමේ ස්වභාවය ප්‍රාරම්භක (preliminaries) අයිතම ලංසුකරුට තරඟකාරී ලෙස මිල කිරීම සඳහා ප්‍රමාණ බිල්පතට ඇතුළත් කිරීම අනිවාර්ය වේ.

Preliminary items ඇතුළත් ලැයිස්තුවක් වෙබ් අඩවියේ ඇතුළත් කර ඇති අතර එම අයිතම අතුරින් ඉදිකිරීමට අත්‍යවශ්‍ය වන්නාවූ අයිතම පමණක් ඇතුළු කළ යුතු වේ.

13. එක් එක් රේට් මිල ගණන් වලට ඇතුළත් විය යුතු අයිතම පිළිබඳ විග්‍රහයක් "General preamble" සහ "Pricing preamble" වල ඇතුළත් කර ඇති අතර එකී ලේඛන මෙම රේට් මිල ගණන් වලට කොටසක් ලෙස සැලකිය යුතු අතර මෙම රේට් මිල ගණන් පදනම් කර ගෙන සකස් කරනු ලබන ප්‍රමාණ බිල්පත් ලංසු කැඳවීමට උපයෝගී කර ගන්නා අවස්ථාවන්හිදී එකී "General preamble" සහ "Pricing preamble" ද ලංසු ලේඛන වල කොටසක් විය යුතු අතර ඒවාද පැහැදිලිව ඇතුළත් වී ඇති බවට සනාථ කර ගත යුතු වේ. මෙම "General preamble" සහ "Pricing preamble" අවස්ථානුකූලව සහ වරින් වර වැඩිදියුණු කරනු ලබන බැවින් ලංසු කැඳවන අවස්ථාවේ වෙබ් අඩවියේ ඇතුළත් යාවත්කාලීන කරන ලද නව පිටපත බාගත (download) කරගත යුතු බව අවධාරණය කරමි.

14. මෙම රේට් මිල ගනන් හුදෙක් උපකල්පන මත රැඳෙමින් සකස් කරන ලද ඇස්තමේන්තු ගත රේට් මිල ගණන් බව අවධාරණය කරනු ලබන අතර තරගකාරී ක්‍රමයට කැඳවන ලද ලංසු එකිනෙක සමඟ සැසඳීම සඳහා පාදක කර ගත යුතු මෙවලමක් ලෙස භාවිතා කිරීමට සහ යම් ව්‍යාපෘතියකට මුදල් වෙන් කිරීමේදී මුළු පිරිවැය ඇස්තමේන්තුවක් යම්තාක් දුරට නිරවද්‍යතාවයකින් යුතුව සකසා ගැනීම සඳහා මෙම රේට් මිල ගණන් පදනම් කර ගැනීම සුදුසු බවට වැඩිදුරටත් අවධාරණය කරනු ලැබේ.

15. මුළු පිරිවැය ඇස්තමේන්තු පිළියෙල කිරීමේදී භාවිතා කිරීම සඳහා මෙම ලේඛනයේ පිටපත් අදාළ තාක්ෂණ නිලධාරීන් වෙත කරුණාකර නිකුත් කරන්න.

*සටහන: මෙම ගාස්තු ලේඛණයේ Fine Aggregate (වැලි) උපයෝගී කර ගනු ලබන අයිතම වල රේට් මිල ගණන් තීරණය කර ඇත්තේ ශ්‍රී ලංකා ඉඩම් ගොඩනිර්මිත හා සංවර්ධනය කිරීම් සංස්ථාව විසින් අලෙවි කරනු ලබන off-shore sand මිල ගනන් පදනම් කර ගෙනය. ඒ අනුව කොන්ත්‍රාත්තුවේ ඉංජිනේරුවරයා විසින් වැර ගැන්වූ කොන්ක්‍රීට් සඳහා මෙම වැලි උපයෝගී කර ගැනීමට අවසර දීමේදී

පහත සඳහන් ලේඛණ පරීක්ෂාවට ලක් කිරීමෙන් අනතුරුව ශ්‍රී ලංකා ප්‍රමිති 1397:2010 පිරිවිතරව අනුකූල බවට සහතික කළ යුතු වේ.

- (අ) කොන්ත්‍රාත්කරු විසින් වැලි සපයනු ලබන ආයතනයන් විසින් SLS 1397:2010 වගන්ති අංක 5 ප්‍රකාර ලිඛිත තොරතුරු ඉදිරිපත් කළ යුතු වේ.
- (ආ) වැඩ බිමට වැලි ගෙන ඒමෙන් පසු අහඹු ලෙස තෝරා ගත් සාම්පල් රසායනාගාර පරීක්ෂණයකට ලක් කර Shell content (සිප්පි කටු ප්‍රමාණය), Chloride content (ක්ලෝරයිඩ් අයන ප්‍රමාණය) සහ Gradation (වැලි ඇටවල විහිදීම) SLS 1397:2010 සඳහන් නිර්ණායක වලට අනුකූල බවට සනාථ කර ගත යුතු වේ.

ඒ.ඒ.පී.එස්.කේ.කරුණාරත්න,
නියෝජ්‍ය ප්‍රධාන ලේකම් (ඉංජිනේරු),
බස්නාහිර පළාත.

ඒ. ඒ. පී. එස්. කේ. කරුණාරත්න
නියෝජ්‍ය ප්‍රධාන ලේකම් (ඉංජිනේරු)
ප්‍රධාන ලේකම් කාර්යාලය (බ.ප.)
පස්වන මහල, අංක 204,
ඩෙන්සිල් කොඩිබැකඩුව මාවත,
බත්තරමුල්ල.

පිටපත්:

- | | | |
|----|---|---|
| 1. | ප්‍රධාන ලේකම් (බ.ප.) | : කරු.දැ.ස. |
| 2. | දිස්ත්‍රික් ලේකම්වරුන් (කොළඹ/ ගම්පහ/ කළුතර) | : දිස්ත්‍රික් ලේකම් කාර්යාලයේ ඉංජිනේරුවරුන්ගේ දැනගැනීම සඳහා යොමුකරන්න |
| 3. | බස්නාහිර පළාතේ සියලුම අමාත්‍යාංශ ලේකම්වරුන් | : දැ.ස. |
| 4. | නියෝජ්‍ය ප්‍රධාන ලේකම් (මූල්‍ය/ සැලසුම්) | : දැ.ස. |
| 5. | අධ්‍යක්ෂ (අභ්‍යන්තර විගණන) | : දැ.ස. |
| 6. | විගණන අධිකාරී | : දැ.ස. |

BUILDING SCHEDULE OF RATES – 2020/2021

EFFECTIVE FROM 2020.09.01

VERSION 01 OF 2020/09/01

**PROVINCIAL ENGINEERING ORGANIZATION
WESTERN PROVINCE-PROVINCIAL COUNCIL**

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | <u>B - EXCAVATION AND EARTH WORK</u> | | |
| | <u>Excavation</u> | | |
| B 01 | Clearing site vegetation manually including removal of bushes, shrub removing rubbish up to a distance of 30'-0". | Sqr. | 585.00 |
| B 02 | Removing top soil manually to a depth not exceeding 6" and removing all debris away from site up to a distance of 30'-0". (Removing top soil up to 2 sqrs.) | Sqr. | 507.00 |
| B 03 | Removing top soil machinery to a depth not exceeding 6" and removing all debris away from site up to a distance of 30'-0". | Sqr. | 322.00 |
| B 04 | Manual Excavation over site to reduce level in any material (except rock requiring blasting) including depositing and levelling as directed up to a distance not exceeding 30'-0". (Manual excavation upto 10 cubes) | Cube | 3,490.00 |
| B 05 | Manual Excavation over site to reduce level in any material (except rock requiring blasting) including depositing and levelling as directed distance exceeding 30'-0" but not exceeding 1/4 mile.(Manual excavation upto 10 cubes) | Cube | 3,832.00 |
| | Shoring, dewatering and rock blasting if necessary for the excavation, shall be paid separately for items B 06 to B 20 | | |
| B 06 | Manual Excavation for column, wall, staircase foundations in any soft/loose soil (except rock requiring blasting) up to 5'-0" depth, part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 1,859.00 |
| B 07 | Manual Excavation for column, wall, staircase foundations in any Ordinary soil (except rock requiring blasting) up to 5'-0" depth, part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 3,261.00 |
| B 08 | Manual Excavation for column, wall, staircase foundations in hard dense soil (except rock requiring blasting) up to 5'-0" depth, part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 4,897.00 |
| B 09 | Manual Excavation for column, wall, staircase foundations in mud/wet soil (except rock requiring blasting) up to 5'-0" depth, part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 4,547.00 |
| B 10 | Manual Excavation for column, wall, staircase foundations in soft disintegrated rock (except rock requiring blasting) up to 5'-0" depth, part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 3,495.00 |
| B 11 | Manual Excavation for column, wall, staircase foundations in any soft/loose soil (except rock requiring blasting) depth exceeding 5'-0" but not exceeding 10'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 3,010.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| B 12 | Manual Excavation for column, wall, staircase foundations in any Ordinary soil (except rock requiring blasting) depth exceeding 5'-0" but not exceeding 10'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 6,416.00 |
| B 13 | Manual Excavation for column, wall, staircase foundations in hard dense soil (except rock requiring blasting) depth exceeding 5'-0" but not exceeding 10'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 9,688.00 |
| B 14 | Manual Excavation for column, wall, staircase foundations in mud/wet soil (except rock requiring blasting) depth exceeding 5'-0" but not exceeding 10'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 8,987.00 |
| B 15 | Manual Excavation for column, wall, staircase foundations in soft disintegrated rock (except rock requiring blasting) depth exceeding 5'-0" but not exceeding 10'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 6,884.00 |
| B 16 | Manual Excavation for column, wall, staircase foundations in any soft/loose soil (except rock requiring blasting) depth exceeding 10'-0" but not exceeding 15'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 5,365.00 |
| B 17 | Manual Excavation for column, wall, staircase foundations in any Ordinary soil (except rock requiring blasting) depth exceeding 10'-0" but not exceeding 15'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 9,571.00 |
| B 18 | Manual Excavation for column, wall, staircase foundations in hard dense soil (except rock requiring blasting) depth exceeding 10'-0" but not exceeding 15'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 14,479.00 |
| B 19 | Manual Excavation for column, wall, staircase foundations in mud/wet soil (except rock requiring blasting) depth exceeding 10'-0" but not exceeding 15'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 13,427.00 |
| B 20 | Manual Excavation for column, wall, staircase foundations in soft disintegrated rock (except rock requiring blasting) depth exceeding 10'-0" but not exceeding 15'-0", part return fill in and ram and surplus deposited within site as directed. (Transport of material to be paid separately) | Cube | 10,272.00 |
| B 21 | Bulk excavation using machinery and deposited within site as directed. . | Cube | 1,413.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| | <u>Earth Work Supports</u> | | |
| B 22 | Temporary earth work supports, in open planking in trenches total depth up to 5'-0" and details given in Drawing No:- ST/TYPE PLAN/FOUND/2020/DETAIL 01. (shoring designed to carry soil load only) | Sq.ft. | 63.00 |
| B 23 | Temporary earth work supports, in close planking in trenches of loose soil, total depth up to 5'-0" and details given in Drawing No:- ST/TYPE PLAN/FOUND/2020/DETAIL 01. (shoring designed to carry soil load only) | Sq.ft. | 108.00 |
| B 24 | Temporary shoring with steel R.S.J's / 10 mm thick Steel plate combination , with steel R.S.J's (6" x 6" x 10 mm thick) vertically driven at 4'-0" c/c permissible intervals and steel sheets inserted between R.S.J's; the R.S.J's shall be driven to an appropriate depth below the final formation of the bottom of excavation to withstand as free-standing cantilevers to hold back the unsupported earth. (Shoring designed to carry soil load only) Contractor shall design the shoring method based on soil report recommendations to suit the specific site requirements and method specification to be submitted before excavation to the Divisional Engineer for approval. | Sq.ft. | 899.00 |
| | <u>Filling & Compaction</u> | | |
| | <u>Note:-</u> | | |
| | Approved earth shall mean filling materials that comply to the following : | | |
| (a) | The earth shall be free of vegetation, roots, boulders, easily decomposable materials, chemicals, industrial waste, plastic etc. | | |
| (b) | The maximum size of particle shall not exceed 7.5mm. | | |
| (c) | The earth shall be well graded and the silt and clay (fines) content shall not be more than 25% | | |
| (d) | The Standard proctor density shall be greater than 1.70g/cm³ | | |
| B 25 | Approved Earth spreading , leveling watering and compaction manually using standard cast iron stamper or equivalent and filling in 150 mm thick layers (loose volume) in restricted areas (Earth available at site) - Earth measured as a volume in loose state before spreading and compaction. (Quantities not exceeding 5.0 Cubes for the entire work are permitted) | Cube | 3,490.00 |
| B 26 | Approved earth supplying and piled at site. (measured at piled volume) | Cube | 6,192.00 |
| B 27 | River Sand supplying spreading laying and compacting in foundation trenches where measured on compacted volume. | Cube | 21,681.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| B 28 | Dense graded 37.5mm Aggregate Base Course (ABC) supplying, pilling, spreading , levelling , watering in 225mm thick layers and compaction using machine Rammer. (measured on loose volume). Rate include hire charges of the machine rammer & exclude transport). | Cube | 8,953.00 |
| B 29 | Graded Quarry dust 4.5mm downwards supplying, spreading , levelling , watering in 225mm thick layers and compaction using machine Rammer.(loose volume). Rate include hire charges of the machine rammer. In case where measurements are to be done on compacted volume multiply the rate by 1.20. | Cube | 14,475.00 |
| B 30 | Supplying and spreading of graded gravel backing surrounding the Pre-cast Soakage pit. This rate is only incorporated with item No. U 37. (Refer Drawing No:- WSS/2020/ST-SP/05) | Cube | 4,182.00 |
| B 31 | Approved earth spreading & levelling manually including watering in 225mm thick layers (measured on piled volume) & Compaction using machine Rammer. Rate include hire charges of the machine rammer. This rate is applicable for building construction with earth work not exceeding 25 cubes. (earth available at site). | Cube | 2,041.00 |
| B 32 | Spreading & Levelling using backhoe loader or approved equivalent and Compaction of Earth using Vibrating roller (1/2-1 ton) or equivalent including watering in 225mm thick layers (measured on piled volume) . Rate include hire charges of JCB & Vibrating roller. This rate is applicable for building construction with earth work exceeding 25 cubes. (earth available at site). | Cube | 1,048.00 |
| B 33 | Manually spreading and levelling piled approved earth (applicable for filling out side the building area) rate without compaction. | Cube | 458.00 |
| | <u>Transport</u> | | |
| | (a)The rate of payment for transport shall be made under any relevant item selected from item codes B 34 to B 36 irrespective of the type of vehicle to be used. (up to 2 cubes) | | |
| | (b)However in case the quantity involved is more than 2.0cube for the entire project per kilometer run and in situations other than stipulated in above, the rate of payment for transport shall be selected from item codes B 37 to B 39. | | |
| B 34 | Transport of soil 25m to 100 m by any means (including loading and unloading) | Cube | 1,820.00 |
| B 35 | Transport 100m to 0.5km by any means (Excluding loading and unloading) | Cube | 878.00 |
| B 36 | Transport 0.5km to 1.0km by any means (Excluding loading and unloading) | Cube | 943.00 |
| B 37 | Transport of any Material / Debris by any means in bulk including loading (for distance less than or equal 3 kilometers) | Cube | 1,079.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|----------|----------------|
| B 38 | Transport of any Material / Debris by any means in bulk excluding loading (from 3km up to 10km Distance) | Cube/km | 102.00 |
| B 39 | Transport of any Material / Debris by any means in bulk excluding loading (for distance more than 10 km Distance) | Cube/km | 88.00 |
| B 40 | Transporting debris cleared away from site by tractor trailer including loading (approx. Dumping up to 3 km). | Per Load | 810.00 |
| | <u>Anti-termite Treatment</u> | | |
| B 41 | Anti-termite treatment for the new construction with applying Biflexthrine 10Tc (Biflex) or approved equivalent as per manufacturer's standards of application including horizontal & vertical barriers with 10 years warranty on application (Measured on plinth area). | Sq.ft. | 26.00 |
| B 42 | Anti-termite treatment for the post construction (Existing building) with applying Biflexthrine 10Tc (Biflex) or approved equivalent as per manufacturer's standards of application with 5 years warranty on application (Measured on plinth area). | Sq.ft. | 31.00 |
| | <u>C - CONCRETE</u> | | |
| | Rates for concrete are grouped under following categories | | |
| | 1. In-situ plain concrete (mixed at site either manually or with machine) Item No. C01, C02, C03 | | |
| | 2. Reinforced concrete of Grade 25 & 30 (mixed at site with a concrete mixer) Item No. C04, C05 , C06, C07, C08 & C09 | | |
| | These items are meant for Footings, Columns, Plinth beams, Floor beams, Tie-beams & Stair case. i.e. load bearing members. | | |
| | 3. Ready mixed concrete of Grade 20 ,Grade 25 . Grade 30 & Grade 35A Item Nos. from C29 to C33. | | |
| | 4. Site produced concrete of Grade 20 - (machine mix or in case of small quantities manually mixed) Item No.C11 (along with Item Nos. from C13 to C28 which are derived from C11) | | |
| | These items are meant for pre-cast lintols, stiffeners, copings,concrete drains, etc. | | |
| | 5. Curing for In situ plain concrete, In situ reinforced concrete, Site produced concrete of Grade 20 & Ready mix concrete Items C-01 to C-33 should be paid under Item no. C 38. | | |
| | <u>In - Situ Plain Concrete (mixed at site either manually or with machine)</u> | | |
| C 01 | Cement concrete 1:3:6 (1 1/2") in wall foundations including placing, compacting. | Cube | 43,269.00 |
| C 02 | Cement concrete 1:3:6 (1") laid to a thickness of 2" under column/stair footings, including placing in position,compacting. | Sqr. | 7,535.00 |
| C 03 | Cement concrete 1:3:6 (1") in wall foundations, under column/stair footings including placing in position,compacting. | Cube | 45,207.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|------------|---|------|----------------|
| | In - Situ Reinforced Concrete Of Grade 25 &30 (mixed at site with a concrete mixer) | | |
| 1 | Grade 25 concrete shall be used for footings, columns, beams, staircases, tie-beams of reinforced concrete elements in multi-storied building (excluding lintols, stiffener columns, copings, non-structural columns and Drains). | | |
| | Site mixed Grade 30 concrete shall be used only for specific structural works with the approval of the Divisional Engineer. | | |
| 2 | The rates appearing in BSR Item No. C04,C05 and C06 are strictly applicable for Grade 25 & BSR Item No. C07,C08 and C09 are strictly applicable for Grade 30 concrete produced at site with machine mixer and shall comply to the following requirements in order to be eligible for payment | | |
| 3 | Constituent material shall comply to following; | | |
| | (i) Cement of strength class 42.5N and shall comply with SLS 107 (Ordinary Portland Cement) & SLS 1253 (Portland Limestone Cement) , that has been stored under proper conditions and has manufactured within 90 days at the time of concreting. | | |
| | (ii) Use of sulfate resistant Portland Cement or Blended Hydraulic Cement confirming to BSEN 197-1:2011 & comply with SLS 1247 . Sulfate resistant class is recommended for aggressive environmental conditions with the specific approval of Divisional Engineer. | | |
| | (iii) Clean river sand without impurities and clay particles of grain distribution falling within the prescribed grading limit in BS 882:1992. | | |
| | (iv) Well graded coarse aggregate free of impurities with maximum aggregate size being 20mm. grain distribution falling within the prescribed grading limit in BS 882:1992. | | |
| | (v) Clean portable water | | |
| 4 | Volume batching of constituent material | | |
| (a) | The equivalent nominal mix suggest for volume batching the Grade 25 & 30 concrete is given in table 4.4 of ICTAD specification for Building Work SCA/4/I of July 2004 for a 50kg cement bag and measuring boxes is reproduced below. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 | | | | | | | | | | | | | | |
|-------------------------|---|-------------------------------------|---------------------------------|------------------------------------|--|----------------|------------------|-----------|----|-------------------------------------|---------------------------------|-------|----|-------------------------------|--------------------------------|--|--|
| | Table 4.4 | | | | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th rowspan="2">Specified Mix by Volume</th><th rowspan="2">Equivalent Concrete Grade</th><th colspan="2">Quantities per 50 kg bag of Cement</th></tr> <tr> <th>Fine Aggregate</th><th>Coarse Aggregate</th></tr> </thead> <tbody> <tr> <td>1:1 1/2:3</td><td>25</td><td>0.053 m³ 1 1/2 boxes</td><td>0.105 m³ 3 boxes</td></tr> <tr> <td>1:1:2</td><td>30</td><td>0.035 m³ 1 box</td><td>0.07 m³ 2 boxes</td></tr> </tbody> </table> | Specified Mix by Volume | Equivalent Concrete Grade | Quantities per 50 kg bag of Cement | | Fine Aggregate | Coarse Aggregate | 1:1 1/2:3 | 25 | 0.053 m ³ 1 1/2 boxes | 0.105 m ³ 3 boxes | 1:1:2 | 30 | 0.035 m ³ 1 box | 0.07 m ³ 2 boxes | | |
| Specified Mix by Volume | Equivalent Concrete Grade | | | Quantities per 50 kg bag of Cement | | | | | | | | | | | | | |
| | | Fine Aggregate | Coarse Aggregate | | | | | | | | | | | | | | |
| 1:1 1/2:3 | 25 | 0.053 m ³ 1 1/2 boxes | 0.105 m ³ 3 boxes | | | | | | | | | | | | | | |
| 1:1:2 | 30 | 0.035 m ³ 1 box | 0.07 m ³ 2 boxes | | | | | | | | | | | | | | |
| (b) | Coarse aggregate to be proportioned for the volume batching using the measurement boxes as indicated in the Clause 4.3.1 ICTAD/SCA/4/I. The internal dimensions of the boxes are 400 x 350 x 250mm (which is 0.035m ³ and corresponds to the volume of 1 bag of cement weighing 50 kg). The proportioning of sand shall be on the basis of its dry volume and in the case of damp sand allowance for bulkage shall be made as given in Appendix 4C of ICTAD specification. | | | | | | | | | | | | | | | | |
| (c) | Water:Cement ratio shall not exceed 0.45. Based on this Water:Cement ratio, volume of water required (either weight or converted volume of water) shall be decided for a given cement content. Required water content shall then be added by measuring the volume from a calibrated measuring Jar. | | | | | | | | | | | | | | | | |
| (d) | Cement shall be added in bag form. | | | | | | | | | | | | | | | | |
| (e) | Slump of site mixed concrete before pouring shall be within 150mm±25mm range. | | | | | | | | | | | | | | | | |
| | In order to achieve this slump without exceeding the 0.45 water:cement ratio, the use of a water reducing admixture (super plasticer) complying to BS EN 934-2 is permitted to be added to the concrete mix. Contractor shall ensure that the selected plasticer brand is compatible with the cement brand used for concreting. | | | | | | | | | | | | | | | | |
| | Super plasticer shall be added to the water and properly mixed. Thereafter only the dry concrete shall be mixed with water containing super-plasticer. Under no circumstances shall the super-plasticer be directly added to the dry concrete. Dosage of super plasticer shall be determined based on manufacture's recommendation with the specific approval of Divisional Engineer. | | | | | | | | | | | | | | | | |
| 5 | In order to ensure that the consistency of the mix is in par with the specified values given above, a trial mix shall be prepared at the site and prior approval to be obtained from the Divisional Engineer. | | | | | | | | | | | | | | | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| 6 | After adding water to the dry concrete, it shall be used within 60 minutes. The layers of concrete shall be so placed that the bottom layer does not fully set before the top layer is placed. Compaction shall be completed before the initial setting starts i.e. within 30 minutes of addition of water to the dry mixture. Re-tempering of concrete with water shall not be permitted. | | |
| 7 | Contractor shall made available following equipment at site before starting to concrete. | | |
| | (i) Cube moulds -6Nos | | |
| | (ii) Mixer and Vibrator (in working condition) | | |
| | (iii) Gauge Boxes (size as per ICTAD Specification for Building Works) | | |
| | (iv) In case volume of water and admixture to be measured by measuring Jar, accuracy of 0.5ml to measure the volume be available in the Jar. | | |
| | (v) An admixture (super-plasticer) compatible with the cement brand (Technical literature and dosage shall be submitted to the Divisional Engineer well in advance for approval) | | |
| | (vi) Slump cone apparatus | | |
| | (vii) Weighing scale | | |
| | (viii) Covering material for curing | | |
| | (ix) A Supervisor / Forman not below the rank of a NVQ Level 3 in "Construction" category | | |
| | (x) Quality assurance sheet | | |
| | (xi) A written request from the contractor for concreting with date and time, (Request shall forward to the Divisional Engineer at least 3 working days in advance) | | |
| 8 | Immediately after (removal of formwork) (initial setting is starts), columns shall be continuously cured for 7 consecutive days. | | |
| | Note: Divisional Engineer or Senior technical officer shall authorize the concreting only after receiving a method statement (in either language) from the contractor. | | |
| 9 | Payment for concreting shall be made upon submission of following. | | |
| | (a).Concrete cube crushing strength test results; 28 day results shall be available to make full payment. | | |
| | (b).Quality assurance report signed by the contractor's technical officer or agent, Divisional Engineer's technical officer who has witnessed the concreting along with senior technical officer in charge of the site. | | |
| C 04 | Volume Batched Grade 25 concrete prepared at site using mixer and vibrator in ground floor. | Cube | 54,969.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 | | | | | | | | | | | | | | |
|-------------------------|---|-------------------------|---------------------------|------------------------------------|--|----------------|------------------|-------|----|---------------------|---------------------|--|--|---------|---------|--|--|
| C 05 | Volume Batched Grade 25 concrete prepared at site using mixer and vibrator in first floor. | Cube | 56,619.00 | | | | | | | | | | | | | | |
| C 06 | Volume Batched Grade 25 concrete prepared at site using mixer and vibrator in second floor. | Cube | 57,718.00 | | | | | | | | | | | | | | |
| C 07 | Volume Batched Grade 30 concrete prepared at site using mixer and vibrator in ground floor. | Cube | 65,901.00 | | | | | | | | | | | | | | |
| C 08 | Volume Batched Grade 30 concrete prepared at site using mixer and vibrator in first floor. | Cube | 67,878.00 | | | | | | | | | | | | | | |
| C 09 | Volume Batched Grade 30 concrete prepared at site using mixer and vibrator in second floor. | Cube | 69,196.00 | | | | | | | | | | | | | | |
| | <u>Site produced concrete of Grade 20 - (machine mix or in case of small quantities manually mixed)</u> | | | | | | | | | | | | | | | | |
| 1 | The equivalent nominal mixes suggest for the Grade 20 concrete is given in table 4.4 for a 50kg cement bag and measuring boxes as given below. When concrete is prepared at the site with volume batching, instructions given in the ICTAD Publication SCA/4/I shall be followed. | | | | | | | | | | | | | | | | |
| 2 | Concrete shall be mixed by a mechanical mixer unless otherwise the Technical officer in-charge permits for hand mixing. In-case of hand mixing, mixture shall be prepared in a surface that will not allow loss of water. | | | | | | | | | | | | | | | | |
| | <u>Table 4.4</u> | | | | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th rowspan="2">Specified Mix by Volume</th><th rowspan="2">Equivalent Concrete Grade</th><th colspan="2">Quantities per 50 kg bag of Cement</th></tr> <tr> <th>Fine Aggregate</th><th>Coarse Aggregate</th></tr> </thead> <tbody> <tr> <td>1:2:4</td><td>20</td><td>0.07 m³</td><td>0.14 m³</td></tr> <tr> <td></td><td></td><td>2 boxes</td><td>4 boxes</td></tr> </tbody> </table> | Specified Mix by Volume | Equivalent Concrete Grade | Quantities per 50 kg bag of Cement | | Fine Aggregate | Coarse Aggregate | 1:2:4 | 20 | 0.07 m ³ | 0.14 m ³ | | | 2 boxes | 4 boxes | | |
| Specified Mix by Volume | Equivalent Concrete Grade | | | Quantities per 50 kg bag of Cement | | | | | | | | | | | | | |
| | | Fine Aggregate | Coarse Aggregate | | | | | | | | | | | | | | |
| 1:2:4 | 20 | 0.07 m ³ | 0.14 m ³ | | | | | | | | | | | | | | |
| | | 2 boxes | 4 boxes | | | | | | | | | | | | | | |
| 3 | In order to ensure that the consistency of the mix is in par with the Appendix 4D of ICTAD Specification, trial mix shall be prepared at the site and prior approval to be obtained from the Divisional Engineer. | | | | | | | | | | | | | | | | |
| | Constituent material shall comply to following; | | | | | | | | | | | | | | | | |
| | (a) Cement should be compressive strength Class of 42.5 N. | | | | | | | | | | | | | | | | |
| | (b) River sand/washed sand marketed by SLRDC / Manufactured sand shall satisfy with the grading criteria prescribed in Table 4.2 in the ICTAD Publication SCA/4/I. | | | | | | | | | | | | | | | | |
| | (c) Coarse aggregate shall meet the grading criteria prescribed for the volume batching using the measurement boxes as indicated in the Clause 4.3.1 ICTAD/SCA/4/I. | | | | | | | | | | | | | | | | |
| | (d) The proportioning of sand shall be on the basis of its dry volume and in the case of damp sand allowance for bulkage shall be made as given in Appendix 4C of ICTAD specification. | | | | | | | | | | | | | | | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| | (e) Cement shall be added in bag form. The internal dimensions of the boxes are 400 x 350 x 250mm (which is 0.035m ³ and corresponds to the volume of 1 bag of cement weighing 50 kg). | | |
| 5 | For more detail refer Chapter 4 of ICTAD specification for building work SCA/4/I. | | |
| 6 | Water Content (either weight or converted volume of water) shall be measured at site, keeping the maximum water/cement ratio at 0.45 | | |
| 7 | Slump of site mixed concrete before pouring shall be within 150mm±25mm range. | | |
| 8 | In order to achieve this slump without exceeding the 0.45 water:cement ratio, following guidelines can be adopted. | | |
| | (i) The use of a water reducing admixture (super plasticer) complying to BS EN 934-2 is permitted to be added to the concrete mix. Contractor shall ensure that the selected plasticer brand is compatible with the cement brand used for concreting. | | |
| | (ii) Super plasticer shall be added to the water and properly mixed. Thereafter only shall the dry concrete be mixed with water containing super-plasticer. Under no circumstances shall the super-plasticer be directly added to the dry concrete. Dosage of super plasticer shall be determined based on manufacture's recommendation with the specific approval of Divisional Engineer. | | |
| 9 | After adding water to the dry concrete, it shall be used within 60 minutes. | | |
| 10 | The layers of concrete shall be so placed that the bottom layer does not finally set before the top layer is placed. Compaction shall be completed before the initial setting starts i.e. within 30 minutes of addition of water to the dry mixture. Re-tempering of concrete with water shall not be permitted. | | |
| C 10 | Volume Batched Grade 20 concrete prepared at site manually for reinforced and unreinforced concrete floors laid on ground , lintols, copings, stiffeners and drains. (Applicable for small quantities not exceeding 1.0 Cube for the entire project) | Cube | 57,533.00 |
| C 11 | Volume Batched Grade 20 concrete prepared at site using mixer and vibrator for reinforced and unreinforced concrete floors laid on ground cast in situ lintols, copings, stiffeners and drains. | Cube | 52,256.00 |
| C 12 | Pre-cast lintols size 9" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in ground floor. | L.ft. | 558.00 |
| C 13 | Pre-cast lintols size 9" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in first floor. | L.ft. | 575.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| C 14 | Pre-cast lintols size 9" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in second floor. | L.ft. | 586.00 |
| C 15 | Pre-cast lintols size 4 1/2" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in ground floor. | L.ft. | 427.00 |
| C 16 | Pre-cast lintols size 4 1/2" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in first floor. | L.ft. | 440.00 |
| C 17 | Pre-cast lintols size 4 1/2" x 6" deep in Grade 20 concrete, reinforced with 2 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 6" c/c including necessary formwork in second floor. | L.ft. | 448.00 |
| C 18 | Stiffener columns size 4" x 6" in Grade 20 concrete, reinforced with 2 nos of 10mm dia. Tor steel bars , including necessary form work. | L.ft. | 404.00 |
| C 19 | Stiffener columns size 4 1/2" x 6" in Grade 20 concrete, reinforced with 2 nos of 10mm dia. Tor steel bars , including necessary form work. | L.ft. | 413.00 |
| C 20 | Stiffener columns size 9" x 6" in Grade 20 concrete, reinforced with 2 nos of 10mm dia. Tor steel bars and 6mm mild steel stirrups @ 6" c/c , including necessary form work. | L.ft. | 550.00 |
| C 21 | Copings on the 4 1/2" thick walls, size of 6 1/2" x 3" in Grade 20 concrete, reinforced with 1 no of 10mm dia. Tor steel bar, including necessary form work & 1:3 cement plastering, as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 02 | L.ft. | 485.00 |
| C 22 | Copings on the 9" thick walls, size of 11" x 6" approx. in Grade 20 concrete, reinforced with 2 nos of 10mm dia. Tor steel bars and 6mm mild steel @ 6" c/c, including necessary form work & 1:3 cement plastering, as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 02 | L.ft. | 692.00 |
| C 23 | Cement concrete drains of internal size 9" wide and depth varies from 6" - 9" ,consist of 3" thick base and side walls in Grade 20 concrete including 1/2" thick 1:3 rendering without ramp including necessary formwork. (Excavation paid seperately) | L.ft. | 627.00 |
| C 24 | Cement concrete drains of internal size 9" wide and depth varies from 6" - 9" ,consist of 3" thick base and side walls in Grade 20 concrete including 1/2" thick 1:3 rendering with 3" thick & 1'-6" width concrete ramp, including necessary formwork. (Excavation paid seperately) | L.ft. | 1,109.00 |
| C 25 | Cement concrete drains of internal size 9" wide and depth varies from 6" - 9" ,consist of 3" thick base and side walls in Grade 20 concrete including 1/2" thick 1:3 rendering with 3" thick & 2'-6" width concrete ramp, including necessary formwork. (Excavation paid seperately) | L.ft. | 1,344.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|----------------|----------------|
| C 26 | Construction of concrete drain 300mm width x 350mm depth and varies up to 400mm. Consists of 75mm thick concrete base and walls in Grade 20 concrete, fair finish internal surface with size 450mm wide x 600mm long, 75mm thick Grade 20 removable cover slabs with side formwork. Drain and cover slab reinforced with tor steel 10mm at 150mm c/c both ways. (Excavation paid separately) | L.ft. | 2,290.00 |
| C 27 | Construction of concrete drain 300mm width x 350mm depth and varies up to 400mm. Consists of 5mm thick concrete base and walls in Grade 20 concrete, fair finish internal surface without cover slab. Drain reinforced with tor steel 10mm at 150mm c/c both ways. (Excavation paid separately) | L.ft. | 1,678.00 |
| | <u>READY MIX CONCRETE</u> | | |
| 1 | Requirement for Ready mixed concrete | | |
| | (i) Ready mix concrete is confirming to SLS 1144-1997. | | |
| | (ii) Minimum cement content shall be 300 kg/m³ | | |
| | (iii) Nominal maximum size of aggregate shall be 20mm. | | |
| | (iv) Slump shall be as per the mix design. | | |
| | (v) Maximum temperature 30⁰ C | | |
| | (vi) Maximum free water / cement ratio to be 0.5 | | |
| | (vii) Coarse and Fine aggregate used shall confirm to BS 882 latest version. Seive analysis reports within 6 months should be submitted for approval . | | |
| | (viii) Concrete grade shall be as specified. | | |
| | (ix) Concrete mix design shall be approved by the Divisional Engineer . | | |
| | (x) The Ready mix supplier's plant should have been calibrated in the recent past. | | |
| | (xi) Admixures should be compatible with the cement and it should be confirmed by Admixture supplier and Cement supplier. | | |
| | (xii) Testing | | |
| | (xiii) Collection of samples for testing shall be at the point of placing. One sample per 5m³. | | |
| 2 | Rate include the transport of 20km from batching plant. | | |
| C 28 | Ready mix concrete of grade 15 (15 N/mm ²). | m ³ | 13,860.00 |
| C 29 | Ready mix concrete of grade 20 (20 N/mm ²). | m ³ | 15,180.00 |
| C 30 | Ready mix concrete of grade 25(25 N/mm ²). | m ³ | 15,675.00 |
| C 31 | Ready mix concrete of grade 30(30 N/mm ²). | m ³ | 16,445.00 |
| C 32 | Ready mix concrete of grade 35(35 N/mm ²). | m ³ | 17,435.00 |
| C 33 | Ready mix concrete of grade 35A (35A N/mm ²). | m ³ | 18,590.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|----------------|----------------|
| C 34 | Transport charges per Km per 5m ³ truck load for over and above 20 km. | Km/truck | 72.00 |
| C 35 | Placing , levelling & compacting the pumpable concrete. | m ³ | 325.00 |
| C 36 | Pumping charge for quantities up to 30 m ³ . | Item | 28,050.00 |
| C 37 | For more than 30 m ³ additional pumping charges. (Rate for every m ³ over and above 30 m ³) | m ³ | 898.00 |
| C 38 | Continuous curing of exposed reinforced concrete slabs with ponding water or covering with polythene sheets. In case of columns, , beams, staircase,Plinth beam & Ground beam etc , covering the exposed concrete surface with gunnies and spraying water and keeping wet for a period of 7 days. | sq.ft/day | 1.50 |
| | <u>D - FORM WORK</u> | | |
| | <u>Note:</u> | | |
| 1 | Shuttering boxes for columns of over 5'-0" height are not permitted under any circumstances for the pouring of manually produced (site mix) concrete. | | |
| | If a contractor made an appeal to use shuttering boxes (Customary steel boxes or plywood boxes) of over 5'-0" height, then ,Divisional Engineer may personally approve for casting a column shaft up to a maximum height of 4'-0" at a time subject to the fulfillment of following conditions. | | |
| | (a) The concrete mix designed based on material available at the site for a W/C ratio of 0.45 and to be able to Pour without segregation. | | |
| | (b) The method statement of pouring concrete in to the column shaft signed by a competent technical person from the contractor's side should be submitted. | | |
| | (c)In case of tremie pipe, it shall have a diameter of not less than 4" with a funnel. | | |
| | (d)How the funnel and pipe is lowered and kept in position without disturbing the formwork shall be indicated in the method statement. | | |
| | (e) A Method statement for compaction shall be submitted. | | |
| | (f) Divisional Engineer, upon satisfaction himself/herself to the arrangement of placing concrete and having paying special attention to the method of compaction by a person standing at a height and lowering his head and doing compaction in a restricted cross-section with a tremie pipe inside; may be allowed to proceed with a log note. | | |
| D 01 | Shuttering for sides of foundation with 1" thick rubber planking including dismantling | Sqr. | 5,886.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| D 02 | Shuttering for sides of foundation with 15mm thick Plywood board including dismantling and subject to specific approval by the Divisional Engineer. | Sqr. | 11,200.00 |
| D 03 | Shuttering for sides of plinth beams, ground beams on top of foundation including dismantling in 15mm thick plywood | Sqr. | 11,813.00 |
| D 04 | Shuttering for slabs up to 3'-0" height for special purposes (pantry work tops etc.) including dismantling in 15mm thick Plywood board or steel boarding supported by timber props. | Sqr. | 10,400.00 |
| D 05 | Shuttering for floor slab including dismantling in 15mm thick Plywood board or steel boarding up to 11'-0" soffit height supported by props and details given in Drawing No:- ST/TYPE PLAN/SLAB BEAM/2020/DETAIL 04. | Sqr. | 18,049.00 |
| D 06 | Shuttering for floor Beams including dismantling in 15mm thick plywood board upto 12'-0" soffit height supported by props and details given in Drawing No:- ST/TYPE PLAN/SLAB BEAM/2020/DETAIL 02 & 03. | Sqr. | 22,344.00 |
| D 07 | Shuttering for floor slab including dismantling in 15mm thick Plywood board or steel boarding support by steel jack above 11'-0" upto maximum height of 14'-0" and details given in Drawing No:- ST/TYPE PLAN/SLAB/2020/DETAIL 02 & 03. | Sqr. | 20,080.00 |
| D 08 | Shuttering for columns including dismantling in 15mm thick Plywood board & side supports with props. | Sqr. | 19,579.00 |
| | The rate given for item D 09 applicable for pre-fabricated steel shuttering box halves | | |
| D 09 | Shuttering for Columns including dismantling using pre-fabricated steel shutter halves including dismantling. | Sqr. | 15,817.00 |
| D 10 | Shuttering for sides of concrete walls upto 2'-0" height with 12mm thick plywood boards including dismantling. | Sqr. | 8,853.00 |
| D 11 | Shuttering for sides of concrete walls above 2'-0" up to 4'-6" including dismantling in 15mm thick Plywood board supported by timber props. | Sqr. | 9,927.00 |
| D 12 | Shuttering for lintols in 12mm thick plywood boards including dismantling. | Sqr. | 7,983.00 |
| D 13 | Shuttering for stiffener columns in 12mm thick plywood boards between wall panels in 9" walls, 4 1/2" walls and in boundary walls including dismantling. | Sqr. | 6,736.00 |
| D 14 | Shuttering for R.C.C. copings in 12mm thick plywood boards in top of balcony hand rails, stairway hand rails, boundary walls including dismantling. | Sqr. | 7,397.00 |
| D 15 | Shuttering for sides of pre-cast concrete cover slabs (man hole covers, septic tank & soakage pit covers, drain covers, water tank covers and other pre-cast concrete items) with 12mm thick rubber planks including dismantling. | Sqr | 5,540.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| D 16 | Shuttering for sides of R.C.C retaining walls upto 8' 0" height including dismantling in 15mm thick Plywood board supported by timber props. | Sqr | 12,661.00 |
| | <u>E - REINFORCEMENT</u> | | |
| E 01 | Mild steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in Ground floor (Laps should be measured as per the drawings). | Kg | 282.00 |
| E 02 | Mild steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in first floor (Laps should be measured as per the drawings). | Kg | 290.00 |
| E 03 | Mild steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in second floor (Laps should be measured as per the drawings). | Kg | 296.00 |
| E 04 | Tor steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in Ground floor (Laps should be measured as per the drawings). | Kg | 282.00 |
| E 05 | Tor steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in first floor. (Laps should be measured as per the drawings). | Kg | 290.00 |
| E 06 | Tor steel reinforcement to slabs, beams, lintols, columns, footings etc.. bent to shape, laid in position and tied with 16 B.W.G. Aneal binding wire in second floor. (Laps should be measured as per the drawings). | Kg | 296.00 |
| E 07 | Sppllyng and laying in position of B.R.C mesh (6mm dia.) - 8" x 8" | sq.ft | 57.00 |
| E 08 | Sppllyng and laying in position of B.R.C mesh (6mm dia.) - 6" x 6" | sq.ft | 72.00 |
| E 09 | Sppllyng and laying in position of B.R.C mesh (6mm dia.) - 4" x 4" | sq.ft | 102.00 |
| | <u>F - BRICK MASONRY</u> | | |
| F 01 | Brick work in cement and sand in 1:8 in foundation up to D.P.C. level. | Cube | 60,789.00 |
| F 02 | Brick work in cement and sand 1:8 in 9" thick walls of ground floor. | Cube | 60,989.00 |
| F 03 | Brick work in cement and sand 1:8 in 9" thick walls of 1st floor level. | Cube | 64,038.00 |
| F 04 | Brick work in cement and sand 1:8 in 9" thick walls of 2nd floor level. | Cube | 65,258.00 |
| F 05 | Brick work in cement and sand 1:5 in 4 1/2" thick wallsof ground floor. | Sqr. | 27,881.00 |
| F 06 | Brick work in cement and sand 1:5 in 4 1/2" thick walls of 1st floor | Sqr. | 29,275.00 |
| F 07 | Brick work in cement and sand 1:5 in 4 1/2" thick walls of 2nd floor | Sqr. | 29,833.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------------|----------------|
| F 08 | Brick drain internal size 9" x 9"(average depth) , including excavation, back filling , 3" thick plain concrete 1:3:6(1") base, 4 1/2" thick Brick side walls in cement and sand mortar 1:5 , rendering 1/2" thick cement and sand 1:3 and finish smooth with cement slurry. | L.ft. | 1,200.00 |
| F 09 | Steps 1' - 1 1/2" in brick in cement and sand 1:5 finished with 1/2" thick rendering in cement and sand 1:3 and smoothened with cement slurry including 6" high foundation. | L.ft. | 619.00 |
| F 10 | Brick piers in cement and sand 1:5 in ground floor. | Cube | 67,092.00 |
| | <u>G - BLOCK MASONRY</u> | | |
| G 01 | 8" thick cement sand Cellular block wall (blocks confirming to S.L.S. 855 and subject to the approval in sample blocks) in cement and sand mortar 1:5 in ground floor. | Sqr. | 29,460.00 |
| G 02 | 6" thick cement sand Cellular block wall (blocks confirming to S.L.S. 855 and subject to the approval of sample blocks) in cement and sand mortar 1:5 in ground floor. | Sqr. | 24,983.00 |
| G 03 | 4" thick cement sand Cellular block wall (blocks confirming to S.L.S.855 and subject to the approval of sample blocks) in cement and sand mortar 1:5 in ground floor. | Sqr. | 18,885.00 |
| G 04 | Supply and fixing 1'-0" x 1'-0" x 4" thick Concrete grill on wall. | Sq.ft. | 714.00 |
| G 05 | Supply and fixing 1'-0" x 1'-0" x 2" thick Cement grill on wall. | Sq.ft. | 283.00 |
| G 06 | Supply and fixing glass blocks size 8" x 8" x 4" thick. | Sq.ft. | 1,449.00 |
| | <u>H - RUBBLE MASONRY</u> | | |
| H 01 | Random rubble (6"-9") masonry in cement sand mortar 1:5. | Cube | 39,789.00 |
| H 02 | Lifting random rubble masonry or concrete every 1.5 m beyond the initial 1.5m for retaining walls | Cube / lift | 3,507.00 |
| H 03 | Lowering random rubble masonry or concrete every 1.5m beyond the initial 1.5 m for retaining walls | Cube / lwr | 2,338.00 |
| | <u>J - FLOORING</u> | | |
| J 01 | 3/4" thick D.P.C. in cement sand 1:3 finished with 2 coats of D.P.C. tar and blinded with sand. | Sqr. | 14,478.00 |
| J 02 | Gauge 750 polythene damp proof membrane with 6" laps laid under floors. | Sqr. | 388.00 |
| J 03 | Rendering 1/2" thick in cement and sand 1:3 in R.C.C. floors and paved floors finished smooth with cement slurry and colour pigment. | Sqr. | 7,371.00 |
| J 04 | Rendering 1/2" thick in cement and sand 1:3 in R.C.C. stair case including tread, rise & nosing finished smooth with cement slurry and colour pigment. | Sqr. | 8,091.00 |
| J 05 | Rendering 1/2" thick in cement and sand 1:3 in R.C.C. floors and paved floors finished smooth with cement slurry. | Sqr. | 7,184.00 |
| J 06 | Rendering 1/2" thick in cement and sand 1:3 in R.C.C. stair case inc. tread, rise & nosing finished smooth with cement slurry. | Sqr. | 7,884.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| J 07 | 1/2" thick Rendering to the top surface of the sunshade with cement and sand 1:3 finished smooth to a slope of 1:80 and treated with two coats of "Aqua Tuff " by M/s Lankem or approved equivalent water proofing agent. | Sqr. | 9,386.00 |
| J 08 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating including forming groove in ground floor. | L.ft. | 140.00 |
| J 09 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating including forming groove in first floor. | L.ft. | 141.00 |
| J 10 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating including forming groove in second floor. | L.ft. | 144.00 |
| J 11 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating & Colour pigment including forming groove in ground floor. | L.ft. | 140.00 |
| J 12 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating & Colour pigment including forming groove in First floor. | L.ft. | 142.00 |
| J 13 | Skirting 4" x 1/2" thick in cement and sand 1:3 projected or flush to walls finished with cement slurry floating & Colour pigment including forming groove in Second floor. | L.ft. | 145.00 |
| J 14 | Rendering 1/2" thick in cement sand 1:3 finished smooth with cement slurry without colour pigment and expansion joints filled with construction expansion joint sealant including the cost for cleaning the joints prior application of construction expansion joint sealant by M/s Bitumix or approved equivalent. | Sqr. | 7,795.00 |
| J 15 | Rendering 1/2" thick in cement sand 1:3 finished smooth with cement slurry with colour pigment and expansion joints filled with construction expansion joint sealant including the cost for cleaning the joints prior application of construction expansion joint sealant by M/s Bitumix or approved equivalent. | Sqr. | 8,002.00 |
| | Water Proofing | | |
| | The rates for Items J 17 to J 20 are strictly applicable, subject to the fulfillment of the following conditions. | | |
| 1 | The water proofing material shall conform to relevant British, Euro or ASTM specifications | | |
| 2 | Recommended Distributors/Agents who are marketing water proofing material/product are | | |
| | 1. M/s Finco Ltd. | | |
| | 2. M/s HE Engineering | | |
| | 3. M/s Ranki International | | |
| | 4. M/s Solico Engineering | | |
| | 5. M/s Sika Lanka | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| 3 | The contractor shall submit; | | |
| | (a) A written certificate stating that all material and workmanship are in conformity with the specifications and the manufacturer's requirements. | | |
| | (b) The contractor shall jointly with manufacturer/supplier of the waterproofing materials shall furnish a warranty to the Employer valid for a period of 10 years / 5 years after handing over of the work against dampness and/or moisture penetration through treated surfaces due to defective materials and/or workmanship | | |
| | payments for items J 16 to J 19 shall be made on receipt of above certificate | | |
| | The rates for items J 16 and J 19 include the cost of surface preparation, but does not include the cost of protective masonry screed. Appropriate B.S.R. item rate shall be used for protective layer. The approving authority for products shall be the Deputy Chief Secretary (Engineering)/ Director (Building)/ Director (Engineering) or Divisional Engineer. | | |
| J 16 | Type - 1 - Internal Wet Areas without Exposure to Sunlight (Cementitious water proofing using Barralastic or approved equivalent) | Sq.ft. | 320.00 |
| | Application of cementitious water proofing using Barralastic or approved equivalent for internal wet areas such as toilet floors and walls where the surfaces are not directly exposed to sunlight and weathering. Rate shall include for cleaning the substrate and all other work as per manufacturer's specifications on application and shall include ponding test for a 300mm water height kept for a period of 48 hours for horizontal surfaces. | | |
| J 17 | Type - 2 - Areas exposed to sunlight (Balconies, Sun-Shades, Concrete Gutters etc) (Elastomeric water proofing using thorseal or approved equivalent.) | Sq.ft. | 225.00 |
| | Application of two coats of elastomeric water proofing material using thorseal or approved equivalent capable to withstand temperature variation for wet areas exposed to sunlight and weathering. (balconies, sun-shades, concrete gutters etc.) rate shall include for cleaning the substrate and all other work as per manufacturer's specifications on application and shall include ponding test for a 300mm water height kept for a period of 48 hours for horizontal surfaces. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| J 18 | Type - 3 - Water tanks, Sumps, Swimming pools (water proofing material suitable for portable water storage) (Using XYPEX "modification or approved equivalent). | Sq.ft. | 240.00 |
| | Application of crystalline type waterproofing using XYPEX "modification or approved equivalent for under ground sumps, water tanks, (water proofing material recommended for portable water storage tanks) products marketed/installed by a specialist contractor registered at ICTAD. | | |
| J 19 | Type - 4 - Application of membrane type water proofing material for Large flat roofs) | Sq.ft. | 390.00 |
| | On large flat roofs laying of Topseal 3 mm thick, Torch-on membrane or any other equivalent product marketed/installed by a specialist contractor registered at ICTAD under water proofing category including 1:3 cement, sand protective screed laid to slope. Rate shall include the formation of edges, torch welding and fixing metal strip on vertical walls at termination edges. | | |
| | <u>K - PLASTERING</u> | | |
| | <u>Note:</u> | | |
| | 1. The rate for plastering items includes the cost of "Febmix" as a workability enhancer. | | |
| | 2. For coarse textured plaster (identified as "semi-rough") all the sand should pass through 4.0mm sieve. | | |
| K 01 | 5/8" thick plastering to plinth wall in cement sand 1:3 including finishing with cement slurry floating. Rate includes cost of "Febmix" as a workability enhancer. | Sqr. | 8,909.00 |
| K02 | 5/8" thick plastering to plinth wall in cement sand 1:3 including finishing with cement slurry floating with colour pigment. Rate includes cost of "Febmix" as a workability enhancer. | Sqr. | 9,116.00 |
| K 03 | Plastering 5/8" thick to walls in cement and sand 1:5 finished semi-rough. Rate includes cost of "Febmix" as a workability enhancer. | Sqr. | 8,722.00 |
| K 04 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished semi-rough. Rate includes cost of "Febmix" as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 120.00 |
| K 05 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished semi-rough in first floor. Rate includes cost of "Febmix" as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 123.00 |
| K 06 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished semi-rough in second floor. Rate includes cost of "Febmix" as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 126.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| K 07 | Applying two coats of skim coat (Not exceeding 3 mm thick) to walls inc. preparation surface.. | Sqr. | 2,294.00 |
| K 08 | Plastering 5/8" thick to walls in cement and sand 1:5 finished smooth with two coats of skim coat. Rate includes cost of "Febmix"as a workability enhancer. | Sqr. | 11,097.00 |
| K 09 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished smooth with two coats of skim coat in ground floor. Rate includes cost of "Febmix"as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 136.00 |
| K 10 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished smooth with two coats of skim coat in first floor. Rate includes cost of "Febmix"as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 140.00 |
| K 11 | Plastering 5/8" thick to reveals width not exceeding 6" in cement and sand 1:5 finished smooth with two coats of skim coat in second floor. Rate includes cost of "Febmix"as a workability enhancer. (Reveals should be measured both side separately.) | L.ft. | 143.00 |
| K 12 | Plastering 3/8" thick to soffit of slab, sunshade, sides and soffit of beams, stair cases and sides of columns in cement & sand 1:3 & finished semi rough. Rate includes cost of "Febmix"as a workability enhancer. | Sqr. | 9,002.00 |
| K 13 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished semi-rough in ground floor. Rate includes cost of "Febmix"as a workability enhancer. | L.ft. | 144.00 |
| K 14 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished semi-rough in first floor. Rate includes cost of "Febmix"as a workability enhancer. | L.ft. | 148.00 |
| K 15 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished semi-rough in second floor. Rate includes cost of "Febmix"as a workability enhancer. | L.ft. | 151.00 |
| K 16 | Plastering 3/8" thick to soffit of slab, sunshade, sides and soffit of beams, stair cases and sides of columns in cement & sand 1:3 & finished smooth with two coats of skim coat. Rate includes cost of "Febmix"as a workability enhancer. | Sqr. | 12,564.00 |
| K 17 | Plastering 3/8" thick to concrete wall cement & sand 1:3 & finished semi rough. Rate includes cost of "Febmix"as a workability enhancer. | Sqr. | 7,087.00 |
| K 18 | Plastering 3/8" thick to concrete wall cement & sand 1:3 & finished smooth with two coats of skim coat. Rate includes cost of "Febmix"as a workability enhancer. | Sqr. | 9,319.00 |
| K 19 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished smooth with skim coat in ground floor. Rate includes cost of "Febmix"as a workability enhancer. | L.ft. | 172.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| K 20 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished smooth with skim coat in first floor. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 177.00 |
| K 21 | Plastering 3/8" thick to reveals at columns & beams width not exceeding 6" in cement and sand 1:3 finished smooth with skim coat in second floor. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 181.00 |
| K 22 | Applying two coats of skim coat (Not exceeding 3 mm thick) to soffit of slab, sunshade & stair cases Inc. preparation surface. | Sqr. | 3,583.00 |
| K 23 | Applying two coats of skim coat (Not exceeding 3 mm thick) to sides and soffit of beams and sides of columns Inc. preparation surface. | Sqr. | 5,066.00 |
| K 24 | Forming drip for sunshade edge cement & sand 1: 3 finished semi rough in ground floor. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 201.00 |
| K 25 | Forming drip for sunshade edge cement & sand 1: 3 finished semi rough in first floor. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 203.00 |
| K 26 | Forming drip for sunshade edge cement & sand 1: 3 finished semi rough in second floor. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 205.00 |
| K 27 | Plastering 3/4" thick to black board in cement & sand 1:3 finished semi rough and Rendering cement floating coat using black cement finished smooth with carborandum stone. Including preparation of border. Rate includes cost of "Febmix" as a workability enhancer. | Sqr. | 18,267.00 |
| K 28 | Plaster bands 6" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in ground floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 190.00 |
| K 29 | Plaster bands 6" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in first floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 192.00 |
| K 30 | Plaster bands 6" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in second floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 194.00 |
| K 31 | Plaster bands 9" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in ground floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 205.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| K 32 | Plaster bands 9" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in first floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 207.00 |
| K 33 | Plaster bands 9" x 1/2" in cement & sand 1:3 finished semi rough, extra over the plastering in second floor as per the Drawing No:- AR/DETAIL DRG/2010/01/10 & Sheet No. 01. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 209.00 |
| K 34 | Roof plaster band in middle & edge 4" wide in cement, sand mortar 1:3 and coloured to match the tiles. Rate includes cost of "Febmix" as a workability enhancer. | L.ft. | 186.00 |
| | <u>L - TILING</u> | | |
| | <u>Note:</u> | | |
| | Ceramic Tiles should comply to SLS 1181:2019 "specification and shall comply to relevant abrasion resistant class. | | |
| | Copy of the first grade tile purchase bill should be produced at the time of payment. | | |
| | For Item L01- L05 Should be tile range manufactured by Lanka Wall Tile or approved equivalent. | | |
| | <u>Wall Tiling (Ceramic)</u> | | |
| L 01 | Glazed Ceramic wall tiling of size 8" x 8" approved colour, supplying and fixing to walls on a 1:3 cement sand mortar layer, and pointed with tile grout to match the tile. (Rate does not include the 1:3 cement sand mortar layer and is separately measured under item L06) (Prime Cost of tile Rs.65.00) | Sqr. | 30,726.00 |
| L 02 | Glazed Ceramic wall tiling of size 8" x 12" approved colour, supplying and fixing to walls on a 1:3 cement sand mortar layer, and pointed with tile grout to match the tile. (Rate does not include the 1:3 cement sand mortar layer and is separately measured under item L06) (Prime Cost of tile Rs.85.00) | Sqr. | 28,527.00 |
| L 03 | Glazed Ceramic wall tiling of size 12" x 12" approved colour, supplying and fixing to walls on a 1:3 cement sand mortar layer, and pointed with tile grout to match the tile. (Rate does not include the 1:3 cement sand mortar layer and is separately measured under item L06) (Prime Cost of tile Rs.139.00) | Sqr. | 30,810.00 |
| L 04 | Glazed Ceramic wall tiling of size 12" x 18" approved colour, supplying and fixing to walls on a 1:3 cement sand mortar layer, and pointed with tile grout to match the tile. (Rate does not include the 1:3 cement sand mortar layer and is separately measured under item L06) (Prime Cost of tile Rs.251.00) | Sqr. | 33,603.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| L 05 | Glazed Ceramic wall tiling of size 12" x 24" approved colour, supplying and fixing to walls on a 1:3 cement sand mortar layer, and pointed with tile grout to match the tile. (Rate does not include the 1:3 cement sand mortar layer and is separately measured under item L06) (Prime Cost of tile Rs.422.00) | Sqr. | 39,031.00 |
| L 06 | Cement and sand 1:3 screed of 1/2" thick backing to receive wall tiles. | Sqr. | 8,304.00 |
| | <u>Floor Tiling</u> | | |
| | <u>Luxuary Range</u> | | |
| | <u>Note :</u> | | |
| (a) | For Item No. L07 to L14 Shall be Homogenous, porcelain floor tiles of industrial grade floor tile range manufactured by Rocell , Lanka Wall Tile or approved equivalent. | | |
| (b) | Rates include the cost of 1:3 cement:sand motar leveling bed. | | |
| (c) | Copy of the first grade tile purchase bill should be produced at the time of payment. | | |
| L 07 | Homogeneous porcelain semi - glazed/mat floor tile 12" x 12" paving on 1:3 cement & sand bedding and pointed with tile grout to match the tile. (Prime Cost of tile is Rs.206.00) | Sqr | 36,879.00 |
| L 08 | Homogeneous porcelain semi - glazed/mat floor tile 16" x 16" paving on 1:3 cement & sand bedding and pointed with tile grout to match the tile. (Prime Cost of tiles is Rs.361.00) | Sqr. | 38,165.00 |
| L 09 | Homogeneous porcelain semi - glazed/mat floor tile 12" x 24" paving on 1:3 cement & sand bedding and pointed with tile grout to match the tile. (Prime Cost of tile is Rs.583.00) | Sqr | 47,681.00 |
| L 10 | Homogeneous Porcelain semi - glazed/mat floor tile 24" x 24" paving on 1:3 cement & sand bedding and pointed with tile grout to match the tile. (Prime Cost of tile is Rs.1061.00) | Sqr. | 45,660.00 |
| L 11 | Supply and laying of 4" high skirting including tile grout to match the tile of tiling confirming to items L 07 to L 10 | L.ft. | 140.00 |
| L 12 | Supply and laying of 4" high skirting including tile grout to match the tile for staircases. | L.ft. | 185.00 |
| | <u>Granite</u> | | |
| | For the Granite, tiles specified sizes, colour and details of paving decided by Architect/ Divisional Engineer and sample should be approved by the Architect/ Divisional Engineer before laying. | | |
| | Granite should be homogeneous in required texure and free from defects (cracks, decay, weathering or flaws) | | |
| L 13 | Polished Granite 1" thick for vanity tops, laid on 1/2" thick cement sand 1:3 screed level off using cement slurry and 3mm joints to be absolutely in line and flush and grout. Size & colour should be decided by the Architect. | Sqr. | 248,600.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| L 14 | Polished Granite floor slabs 1" thick , laid on 1/2" thick cement sand 1:3 screed level off using cement slurry and 3mm joints to be absolutely in line and flush and grout. Size & colour should be decided by the Architect. (Prime Cost of tile Rs.1750.00 per sq.ft) | Sqr. | 212,300.00 |
| L 15 | Granite floor slabs of size 1" thick rough finish, laid on 1/2" thick cement sand 1:3 screed level off using cement slurry and 3mm joints to be absolutely in line and flush and grout. Size & colour should be decided by the Architect. (Prime Cost of tile Rs.1500.00 per sq.ft)) | Sqr. | 201,300.00 |
| | <u>Titanium Floor Finish</u> | | |
| | Before commence the titanium flooring sub contractor , Manufacturer's method specification and material specifications should be approved by the Divisional Engineer. | | |
| L 16 | Supplying and laying 3mm thick titanium layer on the 3mm thick rough finish bed including 3mm thick glass expansions, after 24 hours wetting the floor for 4 -5 days, and cutting with 100 sanding grit while watering , then cut with 400 sanding grit & after that smooth the floor with 1000 sanding grit pads & apply two coats of sealer on dried clean floor. sealering should be carried out as per the manufacturer's specification. Finally polish with buffing pads to achieve good shine. | Sqr. | 26,070.00 |
| | <u>Power Trowelling Flooring</u> | | |
| L 17 | Power floating freshly laid concrete floor with power floating machinery before concrete is fully dry. Rate shall include cost of curing using liquid membrane curing compound such as MASTERKURE 181 or 128 or any other equivalent. Power floating sub contractor should be approved by the Divisional Engineer. | sq.ft | 59.00 |
| | <u>M - COLOUR WASHING, PAINTING & POLISHING</u> | | |
| | Painting applications for new wood work should be done after carrying out pressure impregnation treatment for the timber to maintain 12% to 15% final moisture level and timber should be free from grease wax or resin traces. | | |
| | Method of application is according to the manufacturer's method specifications | | |
| M 01 | Painting walls with one coat of interior wall primer including preparing surface for interior application before application of emulsion paint. | Sqr. | 1,505.00 |
| M 02 | Painting walls with one coat of Exterior wall primer including preparing surface for exterior application before application of emulsion paint. | Sqr. | 1,653.00 |
| M 03 | Painting walls with one coat of emulsion paint including preparing surface. | Sqr. | 2,023.00 |
| M 04 | Painting walls with two coats of emulsion paint including preparing surface. | Sqr. | 3,806.00 |
| M 05 | Painting soffit with one coat of emulsion paint including preparing surface. | Sqr. | 2,394.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| M 06 | Painting soffit with two coats of emulsion paint including preparing surface. | Sqr. | 4,548.00 |
| M 07 | Painting walls with one coat of weathershield paint including preparing surface. | Sqr. | 2,594.00 |
| M 08 | Painting walls with two coats of weathershield paint including preparing surface. | Sqr. | 4,427.00 |
| M 09 | Painting walls & soffits with one coat of crack binder primer. | Sqr. | 3,509.00 |
| M 10 | Painting walls with one coat of enamel paint including preparing surface. | Sqr. | 2,673.00 |
| M 11 | On existing wall surfaces where emulsion paint has peel-off, application of plaster coatings of thickness not less than 2mm using "Joint compound powder ", or approved equivalent to walls, slab, beam, column facings. Rate shall include for sand papering and surface preparation .(Applying only for the internal surfaces.) | Sqr. | 7,060.00 |
| M 12 | Painting Slab soffits, Side of Beams /Asbestos ceiling with one coat of primer and two coat of emulsion paint including preparing surface. | Sqr. | 4,063.00 |
| M 13 | Painting internal walls of teatre with two coat of antibacterial paint with one coat of primer including preparing surface and subject to specific approval by the Divisional Engineer. | Sqr. | 6,721.00 |
| M 14 | Painting black boards with two coats of blackboard paint including preparing surface. (Prime cost of 500 ml is Rs. 480.00) | Sqr. | 4,016.00 |
| M 15 | Preparing and painting old wood work with one coat of enamel paint. | Sqr. | 2,926.00 |
| M 16 | Preparing and painting old wood work with two coats of enamel paint. | Sqr. | 4,939.00 |
| M 17 | Preparing and painting new wood work with one coat of primer and two coats enamel paint. | Sqr. | 6,534.00 |
| M 18 | Varnishing two coats with polyurethane varnish after sand papering and application of one coat of sanding sealer. | Sqr. | 6,138.00 |
| M 19 | Applying two coats of wood preservative (Clear) to wood work. | Sqr. | 2,015.00 |
| M 20 | Spray Painting for the wood work as per specified in SCA/4/1 clause 14.9 (f). | Sqr. | 5,507.00 |
| | <u>Water Based Application</u> | | |
| | <u>Luxuary Range</u> | | |
| | All water base products are none toxic and conform to EN 71 standards. | | |
| M 21 | Preparing and application two coats of water based stain and two coats of water based top coat to new wood work. Rate shall include for preparing the surface and sanding with sand paper 80, 120, 180 and 320 or 400 . (Prime cost of "JAT - Sayerlack Brand" is water base stain - 4 L is Rs.8916.00.00 & water base top coat - 5L is Rs.16887.00 with 5 year product warranty) | Sqr. | 21,127.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| | <u>Normal Range</u> | | |
| M 22 | Preparing and application two coats of water based stain and two coats of water based top coat to new wood work. Rate shall include for preparing the surface and sanding with sand paper 80, 120, 180 and 320 or 400 . (Prime cost of "JAT - Masters Brand" is water base stain - 4 L is Rs.5093.00.00 & water base top coat - 5L is Rs.9445.00 with 5 year product warranty) | Sqr. | 17,271.00 |
| | <u>Maintainance Coat For Water Based Application</u> | | |
| M 23 | Application of two coats of maintainance wax once two years to maintain the surface where applied two coats of water based stain and two coats of water based top coat to new wood work. Rate shall include for preparing the surface and sanding with sand paper 320 or 400 and subject to specific approval by the Divisional Engineer (Prime cost of "JAT - Sayerlack Brand" of maintainance wax - 4 L is Rs.11000.00.00 with 5 year product warranty) | Sqr. | 6,870.00 |
| | <u>Painting Floors</u> | | |
| M 24 | Wax polishing to timber in panels and floors. | Sqr. | 1,714.00 |
| M 25 | Applying one coat of approved type floor polish including smoothing. | Sqr. | 1,650.00 |
| M 26 | Painting floors / plinth wall with one coat of quick drying floor paint including washing and cleaning surfaces. | Sqr. | 2,652.00 |
| | <u>Steel Painting</u> | | |
| M 27 | Painting steel work (window grills) with two coats of enamel paint and one coat anti-corrosive primer with turpentine or thinner including removing corroded scale and wire brushing. | Sqr. | 6,034.00 |
| M 28 | Painting steel work (in roof trusses) with two coats of Epoxy Zinc phosphate primer including removing corroded scale and wire brushing. | Sqr. | 4,315.00 |
| M 29 | Painting steel work with one coat of enamel paint with mineral turpentine or thinner including removing corroded scale and wire brushing. | Sqr. | 2,726.00 |
| M 30 | Painting steel work with one coat of anti-corrosive primer with mineral turpentine or thinner including removing corroded scale and wire brushing. | Sqr. | 2,563.00 |
| M 31 | Painting steel work with two coat of anti-corrosive primer with mineral turpentine or thinner including removing corroded scale and wire brushing. | Sqr. | 4,348.00 |
| M 32 | Painting Galvanized or aluminium work with one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint including removing corroded scale and wire brushing. | Sqr. | 6,623.00 |
| | <u>Labour Rate for Painting</u> | | |
| M 33 | Labour rate for two coats of Emulsion Painting walls including scaffolding (Paint & Brushes supplied by the client) | Sqr. | 2,225.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| M 34 | Labour rate for single coat of Emulsion Painting walls including scaffolding (Paint & Brushes supplied by the client) | Sqr. | 1,113.00 |
| M 35 | Labour rate for two coats of enamel painting (Paint & Brushes supplied by the client) | Sqr. | 2,596.00 |
| | <u>N - TIMBER DOORS AND WINDOWS</u> | | |
| | <u>Timber :</u> | | |
| 1 | Refer preamble note for approved timber species for Doors & Windows. | | |
| 2 | All timber for doors & windows should be well drying subjected to pressure impregnation treatment using chemical of copper sulphate pentahydrate, Sodium dichromate dihydrate and Boric acid to reduce the moisture level up to 8%- 10% (Final moisture level should be maintain 12% to 15% after Stabilize with the Environment.) | | |
| 3 | Glass thickness to be 5mm. | | |
| 4 | Following Brass or stainless steel furniture are recommended for timber Doors/ Windows/ Fan lights. Rate with out following heavy duty brass furniture. | | |
| | (a)Doors :- 3 no. 4"x 3" Solid brass hinges | | |
| | (b)Doors :- 2 no. 6" Solid brass barrel bolts | | |
| | (c)Windows of 4'-0" height :- 2 no. 4"x 2" Solid brass hinges | | |
| | (d)Windows above 4'-0" height :- 3 no. 4"x 2" Solid brass hinges | | |
| | (e)Windows :- 1 no. 2" Solid brass ring | | |
| | (f)Windows :- 1 no. 10" Solid brass Casement Stay | | |
| | (g)Windows :- 1 no. Solid brass Casement Fastener | | |
| | <u>Doors</u> | | |
| N 01 | Door flush paneled 1 1/8" thick single sash hung on 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting and lock. | Sq.ft. | 1,712.00 |
| N 02 | Door glazed and paneled 1 1/8" thick single sash hung on 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting and lock. | Sq.ft. | 1,727.00 |
| N 03 | Door flush paneled 1" thick single sash hung on 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting and lock. | Sq.ft. | 1,699.00 |
| N 04 | Door glazed and paneled 1" thick single sash hung with 3 3/4" x 2 3/4" frame . Rate without brass furniture, painting and lock. | Sq.ft. | 1,723.00 |
| N 05 | Door 32mm thick plywood ordinary sash single hung on 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting and lock. | Sq.ft. | 1,177.00 |
| N 06 | Door or window glazed and/or paneled 1 1/8" thick double sash hung on 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting and lock. | Sq.ft. | 2,655.00 |
| N 07 | Ledged, braced & battened door sash made out of 7/8" thick "GINISAPU" timber planks. Rate without brass furniture, painting and lock. | Sq.ft. | 810.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| N 08 | Supply & fixing 1 1/8" thick flush paneled door sash only. Rate without brass furniture's, door lock and painting. | Sq.ft. | 1,465.00 |
| N 09 | Supply & fixing 1" thick flush paneled door sash only. Rate without brass furniture's, door lock and painting. | Sq.ft. | 1,460.00 |
| N 10 | Supply & fixing 1 1/8" thick glazed & paneled door sash only. Rate without brass furniture's, door lock and painting. | Sq.ft. | 1,456.00 |
| N 11 | Supply & fixing 1" thick glazed & paneled door sash only. Rate without brass furniture's, door lock and painting. | Sq.ft. | 1,448.00 |
| N 12 | Supply & fixing 32mm thick plywood door (ordinary) sash only. Rate without brass furniture's, door lock and painting. | Sq.ft. | 531.00 |
| N 13 | Door frame 3 3/4" x 2 3/4" in approved timber supplying & fixing in position. | l.ft. | 687.00 |
| | <u>Windows</u> | | |
| N 14 | Window glazed 1 1/8" sash and 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting. | Sq.ft. | 1,793.00 |
| N 15 | Window glazed 1" sash and 3 3/4" x 2 3/4" frame. Rate without brass furniture, painting. | Sq.ft. | 1,789.00 |
| N 16 | Timber slats with 3 3/4" x 1 3/4" frame , 1" x 2 1/2" vertical slats at 2 1/2" centers. Painting measured separately. | Sq.ft. | 1,076.00 |
| N 17 | Supply & fixing 1 1/8" thick glazed window sash only. Rate without brass furniture's and painting. | Sq.ft. | 1,319.00 |
| N 18 | Supply & fixing 1" thick glazed window sash only. Rate without brass furniture's and painting. | Sq.ft. | 1,311.00 |
| N 19 | Window frame 3 3/4" x 2 3/4" in approved timber supplying & fixing in position. | l.ft. | 786.00 |
| | <u>P - IRON MONGARY</u> | | |
| | <u>Note:</u> | | |
| | All Iron mongary shall be heavy duty and samples should be approved by the D.E. Prior to installation. | | |
| 1 | In view of the variety of door locks available in the market, it has become necessary to prescribe the exact quality requirements in terms of performance and durability aspects. The "Union" brand and respective model numbers have been chosen as a bench mark to establish the said requirements. | | |
| 2 | The brand name and model number appearing in the respective BSR items are purely meant to describe the performance standard of the said fitting/item and does not imply in any manner that only the "Union" brand is recommended or considered to be restricted to the "Union" brand. | | |
| 3 | Any other make/brand that has equivalent performance characteristics are considered as equivalent provided such fittings met with following criteria. | | |
| | (a) has an authorized local agent in Sri Lanka | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | (b) The local agent has been in the trade of the offered make for not less than 5 years. | | |
| | (c) The fittings are manufactured in conformity to BS, JIS, ASTM, AS or SLS standards. | | |
| | (d) The dimensions and performance characteristics are in par with the stated model. | | |
| 4 | The brands that may be considered as equivalent are "Miva" of Japan "Whitco" of Australian make or "Dorma" of European make or any other approved make which prior approval to be obtained from Deputy Chief Secretary(Engineering), Director(Building) or Director(Engineering) after producing necessary catalogues and documents. | | |
| 5 | The BSR Items Nos. P 01 - P 09 are payable only after producing an original invoice from the authorized agent for "Union" brand. | | |
| | <u>Union Brand</u> | | |
| P 01 | Supply and fixing Stainless Steel hinges of size 102 x 76 x 3mm of Union Brand & Model no.- X8203-BB-3 or approved equivalent. | Pair | 3,514.00 |
| P 02 | Supply and fixing Stainless Steel hinges of size 127 x 89 x 3mm of Union Brand & Model no.- X8205-BB-3 or approved equivalent. | Pair | 5,534.00 |
| P 03 | Supplying and fixing Night - latch lock of Union Brand & Model No. - 1022 SEPL or approved equivalent. | Nr. | 13,261.00 |
| P 04 | Supplying and fixing single lever Mortice door lock for single sash of Union Brand & Model no.-678.24.95 CH or approved equivalent. | Nr. | 6,050.00 |
| P 05 | Supplying and fixing two lever Mortice door lock for double sash of Union Brand & Model no.- 678.24.42 CH or approved equivalent. | Nr. | 11,861.00 |
| P 06 | Supplying and fixing cylindrical door lock of Union Brand & Model no. - 96300-SS.or approved equivalent | Nr. | 6,056.00 |
| P 07 | Supplying & fixing rim lock of Union Brand & Model no. -J 1445 BJ BRN 009 or approved equivalent. | Nr. | 12,417.00 |
| P 08 | Supplying & fixing hydraulic door closer of Union Brand & Model no. - 8823 SIL or approved equivalent. | Nr. | 6,512.00 |
| P 09 | Supplying & fixing stainless steel Male or Female Symbol of Union Brand & Model no. - 200SS or approved equivalent. | Nr. | 1,262.00 |
| | <u>M.M.Noorbhoy Fittings</u> | | |
| P 10 | Supplying and fixing 4" x 2 1/2" x 2.5mm thick solid brass hinges inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,585.00 |
| P 11 | Supplying and fixing 4" x 3" x 3mm thick solid brass hinges inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,789.00 |
| P 12 | Supplying and fixing 5" x 3" x 3mm thick solid brass hinges inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 2,133.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| P 13 | Supplying and fixing heavy duty solid brass casement fastener inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,894.00 |
| P 14 | Supplying and fixing heavy duty solid brass casement stay - 12" inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,516.00 |
| P 15 | Supplying and fixing heavy duty solid brass 4" center pivot inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Pair | 1,960.00 |
| P 16 | Supplying and fixing 4" long heavy duty solid brass tower bolt inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,281.00 |
| P 17 | Supplying and fixing 6" long heavy duty solid brass tower bolt inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 1,829.00 |
| P 18 | Supplying and fixing 8" long heavy duty solid brass tower bolt inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 2,372.00 |
| P 19 | Supplying and fixing 10" long heavy duty solid brass tower bolt inclusive of brass screws marketed by M.M.Noorbhoy & company or approved equivalent. | Nr. | 2,920.00 |
| P 20 | Supplying and fixing hydraulic hinge "Hettich - Sensys 8645i" for pantry cupboards marketed by M.M.Noorbhoy & company or approved equivalent. | Pair | 2,405.00 |
| P 21 | Supplying and fixing solid brass Door or Window pull ring of 1" dia. (Small) | Nr. | 365.00 |
| P 22 | Supplying and fixing solid brass Door or Window pull ring of 1 1/4" dia. (Medium) | Nr. | 406.00 |
| P 23 | Supplying and fixing solid brass fanlight catch. | Nr. | 1,517.00 |
| P 24 | Supplying & fixing stainless steel Disabled Symbol | Nr. | 876.00 |
| | <u>Cupboards Accessories</u> | | |
| P 25 | Supply and fixing Stainless Steel hinges of size 76 x 64 x 2mm of Magnum Brand & Model no.- 9104NF or approved equivalent. | Nr. | 984.00 |
| P 26 | Supply and fixing Stainless Steel door handle of 10mm dia, 128mm long of Magnum Brand & Model no.- CH107C or approved equivalent. | Nr. | 960.00 |
| P 27 | Supply and fixing stainless steel multipurpose door lock of Magnum Brand or approved equivalent. | Nr. | 1,080.00 |
| P 28 | Supplying and fixing 1" padlock of "Globe" brand or approved equivalent. | Nr. | 306.00 |
| P 29 | Supplying and fixing 1 1/2" padlock of "Globe" brand or approved equivalent. | Nr. | 534.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| P 30 | Supplying and fixing 2" padlock of "Globe" brand or approved equivalent. | Nr. | 894.00 |
| P 31 | Supplying and fixing hasp & staple | Nr. | 102.00 |
| | <u>Other Fittings</u> (for repair and maintenance in the absence of branded items mentioned above, following may be permitted for small quantities | | |
| P 32 | Supplying & fixing polished brass hinges 4" x 2 1/2" thickness 4.0mm \pm 0.2mm with a weight not less than 265g \pm 5g with a smooth surface finish. | Nr. | 823.00 |
| P 33 | Supplying & fixing polished brass hinges of 4" x 3" thickness 4.2mm \pm 0.2mm with a weight not less than 310g \pm 5g with a smooth surface finish. | Nr. | 923.00 |
| P 34 | Supplying & fixing polished brass hinges 5" x 2 1/2" thickness 5.0mm \pm 0.2mm with a weight not less than 345g \pm 5g with a smooth surface finish. | Nr. | 909.00 |
| P 35 | Supplying & fixing polished brass hinges 5" x 3" thickness 4.3mm \pm 0.2mm with a weight not less than 380g \pm 5g with a smooth surface finish. | Nr. | 1,154.00 |
| P 36 | Supplying & fixing polished brass barrel bolt 4" x 1/2" with a weight not less than 210g \pm 5g with a smooth surface finish. | Nr. | 605.00 |
| P 37 | Supplying & fixing polished brass barrel bolt 6" x 1/2" with a weight not less than 300g \pm 5g with a smooth surface finish. | Nr. | 843.00 |
| P 38 | Supplying & fixing polished brass tower bolt 10" x 1/2" with a weight not less than 345g \pm 5g with a smooth surface finish. | Nr. | 1,239.00 |
| P 39 | Supplying & fixing polished brass 1" dia. Pull ring with a weight not less than 100g \pm 5g with a smooth surface finish. | Nr. | 330.00 |
| P 40 | Supplying and fixing heavy duty solid brass casement fastener 6". | Nr. | 489.00 |
| P 41 | Supplying and fixing heavy duty solid brass casement stay - 10" long. | Nr. | 533.00 |
| P 42 | Supplying and fixing heavy duty solid brass casement stay - 12" long. | Nr. | 840.00 |
| P 43 | Supplying and fixing mortice lock . | Nr. | 4,080.00 |
| P 44 | Supplying and fixing magnet lock. | Nr. | 180.00 |
| | <u>Q - ROOFING AND CEILING</u> | | |
| Q 01 | Roof covering with calicut pattern clay tiles . (Timber frame work and ridge covering measured separately) | Sqr. | 11,280.00 |
| Q 02 | Roof covering with corrugated cement fibre roofing sheets. (Timber frame work and ridge covering measured separately) | Sqr. | 11,623.00 |
| Q 03 | Roof covering with corrugated cement fibre roofing sheets. (Timber frame work and ridge covering measured separately) | Sqr. | 14,839.00 |
| Q 04 | Cement fibre roofing close fitting ridges fixed complete with roofing screws or hook bolts. | L.ft. | 406.00 |
| Q 05 | Cement fibre roofing close fitting ridges - colour fixed complete with roofing screws or hook bolts. | L.ft. | 515.00 |
| Q 06 | Ridging with calicut pattern tiles bedded in cement & sand mortar 1:3 and coloured to match the tiles. | L.ft. | 235.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| Q 07 | Racking and cutting at hipped roof. | L.ft. | 58.00 |
| Q 08 | Supplying and Fixing finished size 4" x 2" Coconut Rafters. | L.ft. | 128.00 |
| Q 09 | Supplying and Fixing finished size 3 1/2 "x1 1/2" Coconut Rafters. | L.ft. | 98.00 |
| | <u>DSI TILES (NIVASI PRODUCT)</u> | | |
| | Item Q 10 - Q 14 are using for the laying of DSI (NIVASI Tiles or approved equivalent as per the M/s Samson Rajarata Tiles (pvt) ltd. Manufactures specifications. | | |
| | Timber frame work sizes specified as follows. | | |
| | a) Ridge plate - 45mm x 190mm | | |
| | b) Wall plate - 117mm x 190mm | | |
| | c) Rafters - 45mm x 117mm maximum length 10'-0" @ 18" c/c | | |
| | d) Reepers - 45mm x 25mm @ 10" c/c | | |
| Q 10 | Roof covering with Natural type main tiles of "Nivasi" or approved equivalent with approx. size 310mm x 310mm and unit weight of 3.1Kg. (Specified Timber frame work and ridge covering measured separately) | Sqr. | 28,388.00 |
| Q 11 | Ridging with Natural type ridge tiles bedded in cement, sand mortar 1:5 and coloured to match the tiles. | L.ft. | 477.00 |
| Q 12 | Roof covering with Natural type gable left tiles or approved equivalent . | L.ft. | 350.00 |
| Q 13 | Roof covering with Natural type gable right tiles or approved equivalent . | L.ft. | 350.00 |
| Q 14 | Roof covering with Natural type corner tiles or approved equivalent . | L.ft. | 327.00 |
| | <u>COLOURCON TILES</u> | | |
| | Item Q 15-Q 16 are using for the laying of COLOURCON TILES or approved equivalent as per the M/s Colourcon (pvt) ltd. Manufactures specifications. | | |
| | Timber frame work sizes specified as follows. | | |
| | a) Ridge plate - 45mm x 190mm | | |
| | b) Wall plate - 117mm x 190mm | | |
| | c) Rafters - 45mm x 117mm maximum length 10'-0" @ 18" c/c | | |
| | d) Reepers - 45mm x 25mm @ 10" c/c | | |
| Q 15 | Roof covering with Natural type main tiles of "COLOURCON" or approved equivalent with approx. size 425 mm x 333 mm and unit weight of 4.2Kg/ft ² . (Specified Timber frame work and ridge covering measured separately) | Sqr. | 18,571.00 |
| Q 16 | Ridging with "COLOURCON" type ridge tiles bedded in cement, sand mortar 1:5 and coloured to match the tiles. | L.ft. | 269.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| | <u>Flashing</u> | | |
| Q 17 | Aluminium valley gutter of 3'-0" wide in gauge 24 Aluminium sheets including fixing into 3/4" thk. Ginisapu timber boarding finished & Application of two coats of wood preservative paid separately. | L.ft. | 1,606.00 |
| Q 18 | Aluminium valley gutter of 3'-0" wide in gauge 24 Aluminium sheets fixing to existing 3/4" thk. Ginisapu timber boarding finished . (Application of two coats of wood preservative to timber boarding paid separately.) | L.ft. | 588.00 |
| Q 19 | G.I. Flashing 20 B.W.G. of 1'6" girth with end laps not less than 6" , turned and tuck up not less 6" in wall and pointed with polyurethane sealant including applying three coats of "SYNROOF HI BUILD" waterproofing paint and sticking (GLASCOTE) as reinforcing membrane by M/s Finex Engineering or approved equivalent.. | L.ft. | 881.00 |
| Q 20 | G.I. Valley gutter of 3'-0" wide in gauge 18 sheets including fixing into 3/4" thk. Ginisapu timber boarding including two coats of anti-corrosive paint to sheets. (Application of two coats of wood preservative to timber boarding paid separately.) (Only applicable to be specified when repairing an existing G.I. gutter) | L.ft. | 2,276.00 |
| | <u>Roof Timber</u> | | |
| | <u>Note :</u> | | |
| | <p>During the past two years, Divisional Engineers have reported that exact imperial sizes on the timber on following categories are not readily available in the market, unless logs are being purchased and sawn to the exact size. Contractor's Association has also made representation indicating that the imperial size specified in the BSR is not available on imported timber varieties, and due to scarcity of the local timber, small scale Contractors are unable to purchase logs and seasoned the timber and sawn to the imperial sizes. Market survey has confirmed the same. Accordingly, it has been decided to indicate the cross sectional size roof timber in the following manner to be in par with sectional sizes readily available in the local market, as it may not be worthwhile to prescribe timber sizes and, then request Contractors to by a large section and produce it to the required size, since there is no standardization of the timber imports. This has been done to avoid subjective decision taken by the Divisional Engineers during the project implementation phase.</p> | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | <p>Accordingly, the following imperial sizes are being now replaced by the following Metric sizes.</p> <p>1" to be replaced by 22mm 2" to be replaced by 45mm 3" to be replaced by 70mm 4" to be replaced by 94mm 5" to be replaced by 117mm 6" to be replaced by 140mm 7" to be replaced by 165mm 8" to be replaced by 190mm</p> | | |
| | <p>Hence, timber will now be prescribed as</p> <p>2"x 1" as 45mm x 22mm 2"x 2" as 45mm x 45mm 4"x 2" as 94mm x 45mm 5"x 2" as 117mm x 45mm 5"x 3" as 117mm x 70mm 4"x 3" as 94mm x 70mm 6"x 2" as 140mm x 94mm 6"x 3" as 140mm x 70mm 6"x 4" as 140mm x 94mm 7"x 2" as 165mm x 45mm 8"x 4" as 190mm x 94mm</p> | | |
| | Refer Preamble Notes for approved timber species. The rate for timber items will remain same irrespective of timber species. | | |
| | All Timber should be treated at an approved klin. Timber preservation paid separately as per Item No:M 18. | | |
| | All timber for roof should be well drying subjected to pressure impregnation treatment using chemical of copper sulphate pentahydrate, Sodium dichromate dihydrate and Boric acid to reduce the moisture level up to 8%- 10% (Final moisture level should be maintain 12% to 15% after Stabilize with the Environment.) | | |
| Q 21 | Roofing with calicut pattern tiles on approved local timber or imported Balau , Bitis or Kempas timber frame work complete with ridge hips etc. comprising of 165mm x 45mm ridge plate , 94mm x 70mm wall plate , 94mm x 45mm rafters @ 18" c/c and 45mm x 22mm reepers @ 12" c/c. Application of two coats of wood preservative paid separately. | Sqr. | 50,815.00 |
| Q 22 | Roofing with cement fibre corrugated sheets on approved local timber or imported Balau , Bitis, or Kempas timber frame work (Ridging measured separately).Comprising of 165mm x 45mm ridge plate , 94mm x 70mm wall plate , 94mm x 45mm rafters @ 30" c/c and 45mm x 45mm battens @ 3'-0" c/application of two coats of wood preservative paid separately. | Sqr. | 33,904.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| Q 23 | Supplying and fixing 190mm x 94mm , 165mm x 45mm , 140mm x 94mm , 140mm x 70mm , 140mm x 45mm , 117mm x 190mm and 45mm x 190mm approved local timber or imported Balau , Kempas or Bitis timber purling , hip/valley rafters etc. Application of two coats of wood preservative paid separately. | Cu.ft. | 7,601.00 |
| Q 24 | Supplying and fixing 117mm x 70mm purling up to 12'-0" length approved local timber or imported Balau, Kempas Application of two coats of wood preservative paid separately. | L.ft. | 612.00 |
| Q 25 | Supplying and fixing 94mm x 70mm wall plates up to 12'-0" length, approved local timber or imported Balau, Kempas Application of two coats of wood preservative paid separately. | L.ft. | 460.00 |
| Q 26 | Supplying and fixing 117mm x 70mm , 117mm x 45mm , 94mm x 70mm approved local timber or imported timber varieties of Balau , Bitis ,Kempas timber purlins, wall plates, rafters etc. Application of two coats of wood preservative paid separately. | Cu.ft. | 5,248.00 |
| Q 27 | Supplying and fixing 94mm x 45mm approved local timber or imported Balau Kempas or Bitis timber purling, rafters etc. Application of two coats of wood preservative paid separately. | L.ft. | 308.00 |
| Q 28 | Supplying and fixing 45mm x 45mm local timber or Balau, Kempas or Bitis timber bearers Application of two coats of wood preservative paid separately. | L.ft. | 118.00 |
| Q 29 | Supplying and fixing 45mm x 22mm local timber or Balau, Kempas or Bitis timber reapers. Application of two coats of wood preservative paid separately. | L.ft. | 61.00 |
| Q 30 | Timber valance/barge board in GINISAPU timber (finished size 225mmX18mm thick) fixed to timber roof frame with 2 nos. of 1 1/2" long screws no. 8 at 1' 6" c/c, Application of two coats of wood preservative paid separately. | L.ft. | 343.00 |
| Q 31 | Timber valance/barge board in GINISAPU timber (finished size 225mm x 18mm thick) fixed to existing iron brackets with 2 nos. of 5 mm dia, 1 1/2" long G.I. nut & bolt at 1' 6" c/c, Application of two coats of wood preservative paid separately. | L.ft. | 339.00 |
| Q 32 | Treating of timber by vacuum pressure impregnation technique or approved kiln treatment by "Browns Commodities & Logistics." or any other Authorized company incl. transport. Application of two coats of wood preservative paid separately.. | Cu.ft. | 680.00 |
| Q 33 | Supply and fixing 20mm x 6mm x 12" long flat iron bracket 2'-0" c/c for fixing valance board/barge board. Rate shall include for two coats of anti-corrosive paint. | Nr. | 182.00 |
| | <u>Ceiling</u> | | |
| Q 34 | 3/4" x 6" wide tongued and grooved lunumidella ceiling planks fixed to underside of existing rafters with brass screws including leveling with timber strip where necessary. | Sqr. | 24,821.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| Q 35 | Cement fibre eaves ceiling with approved timber coves & fillets fixed to under side to existing rafter, size of fillet to be 1" x 1/4" & size of cove moulding 1 1/2" x 1 1/2". | Sqr. | 12,365.00 |
| Q 36 | Cement fibre flat ceiling fixed with coves & fillets to local timber or Balau, Bitis or Kempas timber frame work of 94mm x 45mm @ 4' - 0" c/c, 45mm x 45mm @ 2' - 0" c/c, fillet size to be 1" x 1/4" and cove moulding size to be 1 1/2" x 1 1/2" Application of two coats of wood preservative paid separately. | Sqr. | 40,772.00 |
| Q 37 | Cement fibre flat eaves ceiling fixed with coves and fillets fixed with timber work of approved local timber or imported Balau, Bitis or Kempas timber frame work of 45mm x 45mm @ 2' - 0" c/c, fillet size to be 1" x 1/4" cove moulding size to be 1 1/2" x 1 1/2". Application of two coats of wood preservative paid separately. | Sqr. | 31,106.00 |
| Q 38 | 3/4" thick x 6" wide tongued and grooved lunumidella ceiling planks fixed flat on 94mm x 45mm approved local timber or imported Balau, Bitis or Kempas and timber joist at every 2' - 0" c/c. cove moulding size to be 1 1/2" x 1 1/2". Application of two coats of wood preservative paid separately. | Sqr. | 52,285.00 |
| Q 39 | Supply and fixing of tongued and grooved 3/4"x 6" lunumidella ceiling planks on under side of existing rafters, timber strips size to be 2" x 1/4", cove moulding size to be 1 1/2" x 1 1/2". with double sided aluminium foil fixed on top. Application of water based staining and two coats of water based sealant, application of two coats of wood preservative to be paid separately. | Sqr. | 34,931.00 |
| Q 40 | Mineral fiber ceiling | | |
| | Supplying & installing of suspended mineral fiber ceiling in 600mm x 600 grid size reveal / bevel type with hot dipped GI pre - engineered inter - locking main tees (32mm x 24mm) and cross tees (25mm x 24mm) and wall angles expose areas finished with white baked enamel finish and suspended on 04mm dia. adjustable hanger rods with spring clips. Ceiling panel of 600mm x 600mm x 15mm (thickness) and complete to working order as per manufacture's specifications. (Prime cost of 2'-0" x 2'-0" sheet is Rs.560.00) | Sq.ft. | 369.00 |
| Q 41 | Acoustic ceiling | | |
| | Supplying & installing of suspended acoustic ceiling in 600mm x 600 grid size reveal / bevel type using hot dipped GI pre - engineered inter - locking main tees (32mm x 24mm) and cross tees (25mm x 24mm) and wall angles expose areas finished with white baked enamel finish and suspended on 04mm dia. adjustable hanger rods with spring clips. Ceiling panels of 600mm x 600mm x 15mm (thickness) and complete to working order as per manufacture's specifications. (Prime cost of 2'-0" x 2'-0" sheet is Rs.790.00) | Sq.ft. | 446.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| Q 42 | Gypsum ceiling panel | | |
| | Supplying & installing of suspended Gypsum ceiling in 600mm x 600 grid size reveal / bevel type using hot dipped GI pre - engineered inter - locking main tees (32mm x 24mm) and cross tees (25mm x 24mm) and wall angles expose areas finished with white baked enamel finish and suspended on 4mm dia. adjustable hanger rods with spring clips. Ceiling panels will be SCG Elephant Gypsum Standard tiles 600mm x 600mm x 9mm (thickness) and complete to working order as per manufacture's specifications. (Prime cost of 4'-0" x 2'-0" SCG Gypsum sheet is Rs.610.00) | Sq.ft. | 325.00 |
| Q 43 | Cement fiber ceiling | | |
| | Supplying & installing of suspended cement fiber ceiling in 600mm x 600 grid size reveal / bevel type using hot dipped GI pre - engineered inter - locking main tees (32mm x 24mm) and cross tees (25mm x 24mm) and wall angles expose areas finished with white baked enamel finish and suspended on 4mm dia. adjustable hanger rods with spring clips. Ceiling panel of 600mm x 600mm x 4.5mm (thickness) and complete to working order as per manufacture's specifications. (Prime cost of 8'-0" x 4'-0" sheet (un painted) is Rs.2050.00) | Sq.ft. | 347.00 |
| Q 44 | Aluminium Panel Ceiling | | |
| | Supplying & installing of suspended Aluminium Panel Ceiling in 600mm x 600 grid size reveal / bevel type using hot dipped GI pre - engineered inter - locking main tees (38mm x 14mm) and cross tees (25mm x 14mm) and wall angles expose areas finished with white baked enamel finish and suspended on 4 mm dia. adjustable hanger rods with spring clips. Ceiling panels will be Compton aluminium tiles 600mm x 600mm x 0.7mm (thickness) and complete to working order as per manufacture's specifications.. (Prime cost of 2'-0" x 2'-0" aluminium sheet is Rs.1695.00) | Sq.ft. | 831.00 |
| | <u>R - GUTTERS AND DOWN PIPES</u> | | |
| R 01 | uPVC eaves gutter 4 1/2" square type fixed to valance board with uPVC brackets @ 1' - 6" c/c including necessary mitre joints , gutter joiners , running heads & end caps. | L.ft. | 267.00 |
| R 02 | uPVC down pipes 3 1/2" dia. fixed to wall with 1" clearance to wall and Timber plugging buried to walls and uPVC clips @ 4'-0" c/c including necessary sockets, bends, elbows. | L.ft. | 306.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | <u>S - SANITARY FITTINGS</u> | | |
| | <u>Note :</u> | | |
| 1 | In view of the variety of sanitary ware and fittings available in the market, it has become necessary to prescribe the exact quality requirements in terms of performance and durability aspects. The "Rocell , American Standard, Lanka Tiles - coloma " brands and respective model numbers have been chosen as a bench mark to establish the said requirements. | | |
| 2 | The brand name and model number appearing in the respective BSR items are purely meant to describe the performance standard of the said fitting/item and does not imply in any way that only the "Rocell , American Standard, Lanka Tiles - coloma " brands are recommended or considered to be restricted to the "Rocell & American Standard" brands. | | |
| 3 | Any other make/brand that has equivalent performance characteristics are considered as equivalent provided such fittings meet with the following criteria. | | |
| | (a). Has an authorized local agent in Sri Lanka | | |
| | (b). The local agent has been in the trade of the offered make for not less than 5 years. | | |
| | (c).The cistern mechanism shall have an assurance for the availability of spares for the next 3 years. | | |
| | (d). The fittings are manufactured in conformity to BS, JIS, A.S.T.M., A.S. or S.L.S. standards. | | |
| | (e).The dimensions and performance characteristics are in par with the stated model. | | |
| | (f).Contractor should submit the purchasing bill and the required warranty for all "Rocell , American Standard, Lanka Tiles - coloma " products to the Divisional Engineer. | | |
| 4 | Warranty | | |
| | (a). Manufacturer's Warranty for American Standard Brand. | | |
| | 25 years warranty for Vitreous china ware (VC), 1 year warranty for VC component parts such as Tank fitting, Seat cover, etc., 1 year warranty for Flush valve, 5 years warranty for Faucets (Body) & 1 year warranty for other products. | | |
| | (b). Manufacturer's Warranty for Rocell Brand. | | |
| | 25 years warranty for Bath ware, 5 years warranty for Faucets (Body) & Bath room Accessories & 1 year warranty for Plumbing Accessories. | | |
| | (c).Manufacturer's Warranty for Lanka Tiles - coloma Brand. | | |
| | 25 years warranty for Bath ware, 5 years warranty for Faucets (Body) & Bath room Accessories & 1 year warranty for Plumbing Accessories. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| 5 | In case where wash basin outlet directly falls on to an open drain, the bottle trap may be omitted. | | |
| 6 | For wash basins fixed on open areas plastic tap of item T 01 be specified. | | |
| | <u>Semiluxury Range</u> | | |
| S 01 | Supply and fix white vitreous china (vc) floor standing wash basin and pedestal with overflow hole and single tap hole in center of "Rocell" brand or approved equivalent complete to working order inclusive of the 1 1/4" chromium plated waste outlet of "Rocell" brand or approved equivalent and 1 1/4" chromium plated siphon cleanable bottle trap of "Rocell" brand or approved equivalent. (Prime cost of the floor standing wash basin and pedestal is Rs.10,185.00) | Nr. | 22,909.00 |
| S 02 | Supply and fix white vitreous china (vc) floor standing wash basin and pedestal with overflow hole and single tap hole in center of "Rocell" brand or approved equivalent complete to working order. (Prime cost of the floor standing wash basin and pedestal is Rs.10,185.00) | Nr. | 13,808.00 |
| S 03 | Supply and fix white vitreous china (vc) floor standing close coupled semi back to wall water closet suite with wash down flushing with 6/3 liters dual flushing has horizontal outlet with vario drain bend and two lateral holes for bottom water connection , P trap, cistern with water inlet from rear of "Rocell" brand or approved equivalent complete to working order inclusive of universal bend of "Rocell" brand. (Prime cost of the water closet, tank and seat cover is Rs.17870.00) | Nr. | 28,730.00 |
| S 04 | Supply and fix white vitreous china (vc) floor standing close coupled semi back to wall water closet , P trap, from rear of "Rocell" brand or approved equivalent complete to working order inclusive of universal bend of "Rocell" brand. (Prime cost of the water closet and seat cover is Rs.12500.00) | Nr. | 18,358.00 |
| S 05 | Supply and fix white vitreous china (vc) cistern with water inlet from rear of "Rocell" brand with wash down flushing with 6/3 liters dual flushing has horizontal outlet with vario drain bend and two lateral holes for bottom water connection or approved equivalent complete to working order. Prime cost of the tank is Rs.5370.00. | Nr. | 7,857.00 |
| S 06 | Supply and fix wall hung wash basin with half pedestal and single tap hole in center of "Rocell" brand or approved equivalent complete to working order inclusive of the 1 1/4" chromium plated waste outlet of "Rocell" brand or approved equivalent and 1 1/4" chromium plated siphon cleanable bottle trap of "Rocell" brand or approved equivalent. Prime cost of the tank is Rs.10185.00. | Nr. | 22,799.00 |
| S 07 | Supply and fix plastic seat cover for water closet of "Rocell " brand or approved equivalent complete to working order. (Prime cost of the seat cover is Rs.2407.00) | Nr. | 3,563.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| S 08 | Supply and fix squatting pan with foot rest with p trap of "Rocell" brand or approved equivalent complete to working order. (Prime cost of the squatting pan with foot rest with p trap is Rs. 5278.00) | Nr. | 8,354.00 |
| S 09 | Supply and fix plastic cistern for squatting pan of "Rocell" brand or approved equivalent including connecting pipe between tank and squatting pan complete to working order. (Prime cost of the plastic cistern for squatting pan is Rs. 3435.00) | Nr. | 6,831.00 |
| S 10 | Supply and fix Urinal with sensor of "Rocell" brand or approved equivalent complete to working order. (Prime cost of the Urinal with sensor is Rs. 31778.00) | Nr. | 41,095.00 |
| S 11 | Supply and fix Urinal with flush valve of "Rocell" brand or approved equivalent complete to working order. (Prime cost of the Urinal with sensor is Rs. 25519.00) | Nr. | 33,510.00 |
| S 12 | Supply and fix Chromium plated 1 1/4" dia.siphon cleanable bottle trap of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated 1 1/4" dia.siphon cleanable bottle trap is Rs. 4574.00) | Nr. | 5,764.00 |
| S 13 | Supply and fix Chromium plated 1 1/4" chromium plated waste outlet of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated 1 1/4" chromium plated waste outlet is Rs. 1935.00) | Nr. | 2,613.00 |
| S 14 | Supply and fix Chromium plated 1/2" dia. angle valve of "Rocell" brand model or approved equivalent. (Prime cost of the Chromium plated 1/2" dia. angle valve is Rs. 1231.00) | Nr. | 1,654.00 |
| S 15 | Supply and fix Chromium plated 1/2" dia. 18" long flexible hose of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated 1/2" dia. 18" long flexible hose is Rs. 1148.00) | Nr. | 1,553.00 |
| S 16 | Supply and fix Chromium plated 1/2" dia. 24" long flexible hose of "Rocell" brand model No."20002" or approved equivalent. (Prime cost of the Chromium plated 1/2" dia. 24" long flexible hose is Rs. 1231.00) | Nr. | 1,635.00 |
| S 17 | Supply and fix Chromium plated 1/2" dia. concealed valve of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated 1/2" dia. concealed valve is Rs. 3870.00) | Nr. | 4,852.00 |
| S 18 | Supply and fix chromium plated Bidet Spray of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Bidet Spray is Rs. 1676.00) | Nr. | 2,292.00 |
| S 19 | Supply and fix head shower one spray of "Rocell" brand with shower arm or approved equivalent. (Prime cost of the head shower one spray with shower arm is Rs. 15398.00) | Nr. | 19,308.00 |
| S 20 | Supply and fix 5mm thick mirror of size 18" x 24" double coated with pencil edge back strecher. (Prime cost of the 5mm thick mirror of size 18" x 24" is Rs. 3700.00) | Nr. | 4,800.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| S 21 | Supply and fix Chromium plated pillar tap (cold water) for wash basin of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated pillar tap (cold water) for wash basin is Rs. 3611.00) | Nr. | 4,538.00 |
| S 22 | Supply and fix Chromium plated Bip tap of of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated Bip tap is Rs. 2204.00) | Nr. | 2,833.00 |
| S 23 | Supply and fix Chromium plated Sink tap (Swan neck type) of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated Sink tap (Swan neck type) is Rs. 2556.00) | Nr. | 3,260.00 |
| S 24 | Supply and fix flex shower system with diverter for wall mounting with 1/2" single lever bath mixer of "Rocell" brand or approved equivalent. (Prime cost of the flex shower system with diverter for wall mounting with 1/2" single lever bath mixer is Rs. 30787.00) | Nr. | 37,613.00 |
| S 25 | Supply and fix Chromium plated single level wash basin mixer tap flexible connection of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated single level wash basin mixer tap is Rs. 7213.00) | Nr. | 9,013.00 |
| S 26 | Supply and fix Chromium plated sink mixer tap flexible connection of "Rocell" brand or approved equivalent. (Prime cost of the Chromium plated sink mixer tap is Rs. 8796.00) | Nr. | 10,920.00 |
| S 27 | Supply and fix Geyser (electric water heaters) of 15litres of "Rocell" brand or approved equivalent. (Prime cost of the Geyser (electric water heaters) of 15litres is Rs. 20676.00) | Nr. | 25,556.00 |
| S 28 | Supply and fix Geyser (electric water heaters) of 30litres of "Rocell" brand or approved equivalent. (Prime cost of the Geyser (electric water heaters) of 15litres is Rs. 25954.00) | Nr. | 31,915.00 |
| | <u>Bathroom Accessories</u> | | |
| S 29 | Supply and fix chromium plated Soap holder of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Soap holder is Rs. 2991.00) | Nr. | 3,881.00 |
| S 30 | Supply and fix chromium plated Tumbler Holder of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Tumbler Holder is Rs. 3083.00) | Nr. | 3,943.00 |
| S 31 | Supply and fix chromium plated Towel Ring of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Towel Ring is Rs. 2204.00) | Nr. | 2,888.00 |
| S 32 | Supply and fix chromium plated Robe Hook of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Robe Hook is Rs. 1722.00) | Nr. | 2,309.00 |
| S 33 | Supply and fix chromium plated Toilet Paper Holder of "Rocell" brand or approved equivalent. (Prime cost of the chromium plated Toilet Paper Holder is Rs. 2111.00) | Nr. | 2,776.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| | <u>Normal Range</u> | | |
| S 34 | Supply and fix Urinal with sensor "Lanka Tiles Coloma" brand or approved equivalent complete to working order. (Prime cost of the Urinal with sensor is Rs. 24500.00) | Nr. | 32,274.00 |
| S 35 | Supply and fix Urinal with flush valve "Lanka Tiles Coloma " brand or approved equivalent complete to working order. (Prime cost of the Urinal with flush valve is Rs. 10700.00) | Nr. | 15,549.00 |
| S 36 | Supply and fix flex shower system with diverter for wall mounting with 1/2" single lever bath mixer of "Lanka Tiles Coloma " brand or approved equivalent complete to working order. (Prime cost of the flex shower system with diverter for wall mounting with 1/2" single lever bath mixer is Rs. 37000.00) | Nr. | 45,106.00 |
| S 37 | Supply and fix Chromium plated bathroom floor gully cover square type of "Lanka Tiles Coloma " <i>brand</i> or approved equivalent. (Prime cost of the Chromium plated bathroom floor gully cover square type is Rs. 1950.00) | Nr. | 2,525.00 |
| | <u>Bathroom Accessories</u> | | |
| S 38 | Supply and fix chromium plated Soap dish of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Soap dish is Rs. 3400.00) | Nr. | 4,323.00 |
| S 39 | Supply and fix chromium plated Tooth Brush Holder of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Tooth Brush Holder is Rs. 3400.00) | Nr. | 4,323.00 |
| S 40 | Supply and fix chromium plated Robe Hook of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Robe Hook is Rs. 2500.00) | Nr. | 3,243.00 |
| S 41 | Supply and fix chromium plated Paper Holder of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Paper Holder is Rs. 4600.00) | Nr. | 5,763.00 |
| S 42 | Supply and fix chromium plated Single Towel Bar of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Single Towel Bar is Rs. 4900.00) | Nr. | 6,123.00 |
| S 43 | Supply and fix chromium plated Glass Shelf of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Glass Shelf is Rs. 6400.00) | Nr. | 7,923.00 |
| S 44 | Supply and fix chromium plated Toilet Brush Holder of "Lanka Tiles Coloma - Angelo " brand or approved equivalent. (Prime cost of the chromium plated Toilet Brush Holder is Rs. 5300.00) | Nr. | 6,603.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | <u>Disable Fittings & Accessories- Luxury Range</u> | | |
| S 45 | Supply and fix Twyford Doc "M" Pack For Disabled - white (PK B145 WH) comprising Avalon Rimless HO pan and fixing. Avalon Rimless cistern .fittings and Spatula lever 4/6 liter flush, Avalon seat ring. Stainless steel hinge with stability buffers. Hand rinse 1 center tap hole, Spray mixer lever operated, Mixing valve(Thermostatic TMV3) DOC-M Support rails. DOC-M hinged support rail and toilet roll holder, wall bolts(pairs), Grid waste, Cistern cover clips & Labsin. with 25 years warranty. (Approx. toilet floor area not less than 7' 6" x 8' 6") | Nr. | 280,093.00 |
| S 46 | Supply and fix ceramic wall hung wash basin for disabled of "American Standard" brand &, Model No."TF-0947" with Plush Lock andwaste & overflow of Model No."A-8016-A-N"& Bottle Trap Chrome plated of Model No."A-8104-N" or approved equivalent. | Nr. | 33,546.00 |
| S 47 | Supply and fix Disable close coupled Water Closet "American Standard" brand & Model No."Model No.6927" with seat cover & water tank or approved equivalent complete to working order. (Prime cost of the Water Closet with seat cover & water tank Rs. 125100.00) | Nr. | 152,700.00 |
| S 48 | Supply and fix Chromium plated single hole lava faucet for wash basin (Elbow operator) of "American Standard" brand & Model No."CF-1261.105.50" or approved equivalent. | Nr. | 25,460.00 |
| S 49 | Supply and fix grip bar (hand rail) for disabled of "American Standard" brand, model Apex - HR-320460-01 or approved equivalent. | Nr. | 30,722.00 |
| | J & T Brand | | |
| S 50 | Supply and fix Heavy duty Straight grab bar for disabled of "J&T" brand, model "GB029" or approved equivalent. | Nr. | 9,773.00 |
| S 51 | Supply and fix hand Swing up (Folder) Grab bar for disabled of "J&T" brand, model "GB018" or approved equivalent. | Nr. | 36,233.00 |
| S 52 | Supply and fix Floor to Wall Heavy Duty Grab Bar for disabled of "J&T" brand, model "GB - 008" or approved equivalent. | Nr. | 16,640.00 |
| S 53 | Supply and fix Shower Angle - Horizontal Wall Heavy Duty Grab Bar for disabled of "J&T" brand, model "GB-002" or approved equivalent. | Nr. | 19,160.00 |
| | Rocell Brand | | |
| S 54 | Supply and fix Stainless steel bath seat size 338 x 348mm of "Rocell" brand & model no "HS-01C"or approved equivalent. | Nr. | 10,562.00 |
| | <u>Fittings for rough usage (where probability of breakage may be high due to vandalism) Item Nos. S 55 and S 65.</u> | | |
| S 55 | Supply and fix closet Squatting pan with foot rest - square type | Nr. | 3,869.00 |
| S 56 | Supply and fix ceramic wash basin with approved quality (pedestal) and complete to work in order. Rate without pillar tap & bottle trap. | Nr. | 8,886.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| S 57 | Supply and fix ceramic wall hung corner wash basin with approved quality and complete to work in order. Rate inclusive of brackets and connection to pipe line, but without pillar tap & bottle trap. | Nr. | 5,520.00 |
| S 58 | Supply and fix ceramic water closet with approved quality and complete to work in order. Rate inclusive of brackets and connection to pipe line, | Nr. | 18,053.00 |
| S 59 | Supplying and fixing 1 1/4" (40 mm) dia. PVC Bottle Trap. | Nr. | 879.00 |
| S 60 | Shower rose chromium plated 4" dia. Fixed vertically with 1/2" valve socket including water connection. | Nr. | 1,728.00 |
| S 61 | Supply and fixing plastic seat cover for Water Closet. | Nr. | 965.00 |
| S 62 | Mirror bevelled rectangular 24"x 18" aluminium clips and key hole hanging plate including glass shelves. | Nr. | 2,210.00 |
| S 63 | Supply and fixing Chromium plated tooth brush holder. | Nr. | 1,821.00 |
| S 64 | Supply and fixing Chromium plated Soap Tray. | Nr. | 1,098.00 |
| S 65 | Supply and fixing Chromium plated Single Towel Bar. | Nr. | 1,265.00 |
| | <u>Laboratory Sink</u> | | |
| S 66 | Supply and fix laboratory sink of "Rocell" brand & model "Xenon" or approved equivalent complete to working order. (1 1/4" chromium plated waste outlet of "Rocell" brand & model "A706" and 1 1/4" chromium plated siphon cleanable bottle trap of "Rocell" brand & model "A186"). | Nr. | 24,686.00 |
| | <u>Kitchen Sink</u> | | |
| S 67 | Supply and fix 36" x 18" stainless steel 0.6mm thick shiny finish kitchen sink with single bowl & single drain of "Seal core" by mascons or approved equivalent with 5 year written warranty from the authorized agent. including PVC bottle trap and water connection with flexible hose, all complete to working order. (Swan neck tap paid separately.) | Nr. | 6,918.00 |
| S 68 | Supply and fix 17" x 18" stainless steel 0.6mm thick shiny finish kitchen sink with single bowl of "Seal core" by mascons or approved equivalent with 5 year written warranty from the authorized agent. including PVC bottle trap and water connection with flexible hose, all complete to working order. (Swan neck tap paid separately.) | Nr. | 5,533.00 |
| | <u>T - PLUMBING</u> | | |
| | <u>ACCESSORIES</u> | | |
| | <u>"Pegler" Brand or Approved Equivalent Fittings(T 01 -T 12)</u> | | |
| | The BSR Items Nos. T 01 - T 12 are payable only after producing an original invoice from the authorized agent for "Pegler" brand. | | |
| | <u>Ball valve (Ball cock) - PB 500</u> | | |
| | Ball Valve Should be brass full bore quarter turn with lever and female ends. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| T 01 | Supply and fixing 1/2" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 2,629.00 |
| T 02 | Supply and fixing 3/4" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 3,050.00 |
| T 03 | Supply and fixing 1" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 4,461.00 |
| T 04 | Supply and fixing 1 1/4" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 6,981.00 |
| T 05 | Supply and fixing 1 1/2" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 11,216.00 |
| T 06 | Supply and fixing 2" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 16,233.00 |
| T 07 | Supply and fixing 2 1/2" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 39,530.00 |
| T 08 | Supply and fixing 3" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 44,279.00 |
| T 09 | Supply and fixing 4" dia Brass Ball valve (Ball cock) "Pegler" Brand or approved equivalent. | Nr. | 74,852.00 |
| | <u>Foot Valve</u> | | |
| T 10 | Supply and fixing 1 " dia Foot Valve "Pegler" Brand or approved equivalent. | Nr. | 2,219.00 |
| T 11 | Supply and fixing 1 1/2" dia Foot Valve "Pegler" Brand or approved equivalent. | Nr. | 4,050.00 |
| T 12 | Supply and fixing 2" dia Foot Valve "Pegler" Brand or approved equivalent. | Nr. | 5,485.00 |
| | <u>P.V.C. Items</u> | | |
| | <u>"S-lon" Brand or Approved Equivalent Fittings with 1 year manufacturer's warranty for taps</u> | | |
| T 13 | Supplying and fixing Plastic 1/2" Bib tap of "S-lon" brand or approved equivalent. | Nr. | 607.00 |
| T 14 | Supplying and fixing Plastic 1/2" Angle valve of "S-lon" brand or approved equivalent. | Nr. | 579.00 |
| T 15 | Supplying and fixing Plastic 1/2" Swan-neck tap of "S-lon" brand or approved equivalent. | Nr. | 1,674.00 |
| T 16 | Supplying and fixing Plastic 1/2" Piller tap of "S-lon" brand or approved equivalent. | Nr. | 1,141.00 |
| T 17 | Supplying and fixing Plastic Bidet Shower of "S-lon" brand or approved equivalent. | Nr. | 1,219.00 |
| T 18 | Supply and fixing Plastic 1/2" stop tap of "S-lon" brand or approved equivalent. | Nr. | 474.00 |
| T 19 | Supply and fixing 1/2" dia plastic flexible hose - 12" length. | Nr. | 402.00 |
| T 20 | Supply and fixing 1/2" dia plastic flexible hose - 18" length. | Nr. | 486.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| T 21 | Supplying and fixing Shower rose of "S-lon" brand or approved equivalent. | Nr. | 968.00 |
| T 22 | Supply and fixing 1/2" dia PVC Compact Ball valve. | Nr. | 337.00 |
| T 23 | Supply and fixing 3/4" dia PVC Compact Ball valve. | Nr. | 459.00 |
| T 24 | Supply and fixing 1" dia PVC Compact Ball valve. | Nr. | 501.00 |
| T 25 | Supply and fixing 1 1/4" dia PVC Compact Ball valve. | Nr. | 687.00 |
| T 26 | Supply and fixing 1 1/2" dia PVC Compact Ball valve. | Nr. | 862.00 |
| T 27 | Supply and fixing 2" dia PVC Compact Ball valve. | Nr. | 1,235.00 |
| T 28 | Supply and fixing 3" dia PVC Compact Ball valve. | Nr. | 3,090.00 |
| T 29 | Supply and fixing 1" dia PVC Foot valve. | Nr. | 517.00 |
| T 30 | Supply and fixing 2" dia PVC Foot valve. | Nr. | 1,171.00 |
| | <u>P.V.C. Pipes</u> | | |
| | All P.V.C. pipes should confirm to S.L.S. 147. The fittings should be of the same brand as pipes. | | |
| | <u>Water Supply Pipes.</u> | | |
| T 31 | Supplying laying and/or fixing 1/2" dia. uPVC pipe - PN _T 14 (Type 1000) (Specials paid separately). | L.ft. | 93.00 |
| T 32 | Supplying laying and/or fixing 3/4" dia. uPVC pipe - PN _T 11 (Type 1000) (Specials paid separately). | L.ft. | 131.00 |
| T 33 | Supplying laying and/or fixing 1" dia. uPVC pipe - PN _T 11 (Type 1000) (Specials paid separately). | L.ft. | 145.00 |
| T 34 | Supplying laying and/or fixing 1 1/4" dia. uPVC pipe - PN _T 11 (Type 1000) (Specials paid separately). | L.ft. | 177.00 |
| T 35 | Supplying laying and/or fixing 1 1/2" dia. uPVC pipe - PN _T 11 (Type 1000) (Specials paid separately). | L.ft. | 228.00 |
| T 36 | Supplying laying and/or fixing 2" dia. uPVC pipe - PN _T 11 (Type 1000) (Specials paid separately). | L.ft. | 353.00 |
| | <u>waste pipe</u> | | |
| T 37 | Supplying and Fixing 1 1/4" dia uPVC waste pipe - PN _T 7 (Type 600) Rate without excavation and specials | L.ft. | 145.00 |
| T 38 | Supplying and fixing 1 1/2" dia uPVC waste pipe - PN _T 7 (Type 600) Rate without excavation and specials | L.ft. | 158.00 |
| T 39 | Supplying and fixing 2" dia. uPVC waste pipe - PN _T 7 (Type 600) Rate without excavation and specials | L.ft. | 238.00 |
| | <u>Sewer Pipes.</u> | | |
| T 40 | Supplying and laying 4" dia.uPVC sewer pipe - PN _T 7 (type 600) as per Drg. No:- WSS 270 - Type I . Excavation, Bedding, Haunching & Surrounding to be paid separately. Details of Bedding, Haunching or surrounding are given by the Divisional Engineer as per the location. | L.ft. | 578.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| T 41 | Supplying and laying 6" dia.uPVC sewer pipe - PN _T 7 (type 600) Including cement concrete surrounding 1:3:6: (1") as per Drg. No:- WSS 270 - Type II . Excavation, Bedding, Haunching & Surrounding to be paid separately. Details of Bedding, Haunching or surrounding are given by the Divisional Engineer as per the location. | L.ft. | 1,074.00 |
| T 42 | Supplying and laying 10" dia. uPVC sewer pipes (type 600) Including cement concrete surrounding 1:3:6: (1") as per Drg. No:- WSS 270 - Type II . Excavation, Bedding, Haunching & Surrounding to be paid separately. Details of Bedding, Haunching or surrounding are given by the Divisional Engineer as per the location. | L.ft. | 3,184.00 |
| T 43 | Supplying and laying 4" dia.uPVC sewer pipe - PN _T 7 (type 600) fixed to wall and floor slab with uPVC clips. | L.ft. | 755.00 |
| T 44 | Supplying and laying 6" dia. uPVC sewer pipe - PN _T 7 (type 600) fixed to wall and floor slab with uPVC clips. | L.ft. | 1,281.00 |
| T 45 | Supplying and laying 4" dia. uPVC perforated pipe- PN _T 7 (type 600) with 10mm dia. Holes @ 3" c/c as per details. Necessary excavation & rubble packing to be paid separately. | L.ft. | 636.00 |
| | <u>P.V.C. Specials.</u> | | |
| T 46 | Supplying and fixing 1/2" dia uPVC Socket | Nr. | 100.00 |
| T 47 | Supplying and fixing 1/2" dia. uPVC Valve Socket | Nr. | 106.00 |
| T 48 | Supplying and fixing 1/2" dia. uPVC Faucet Socket | Nr. | 104.00 |
| T 49 | Supplying and fixing 1/2" dia. uPVC Elbow | Nr. | 100.00 |
| T 50 | Supplying and fixing 1/2" dia. uPVC Bend | Nr. | 115.00 |
| T 51 | Supplying and fixing 1/2" dia. uPVC Equal Tee | Nr. | 104.00 |
| T 52 | Supplying and fixing 1/2" dia. uPVC Clips | Nr. | 39.00 |
| T 53 | Supplying and fixing 1/2" dia. uPVC union | Nr. | 167.00 |
| T 54 | Supplying and fixing 3/4" dia uPVC Socket | Nr. | 115.00 |
| T 55 | Supplying and fixing 3/4" dia. uPVC Valve Socket | Nr. | 123.00 |
| T 56 | Supplying and fixing 3/4" dia. uPVC Faucet Socket | Nr. | 124.00 |
| T 57 | Supplying and fixing 3/4" dia. uPVC Elbow | Nr. | 124.00 |
| T 58 | Supplying and fixing 3/4" dia. uPVC Bend | Nr. | 133.00 |
| T 59 | Supplying and fixing 3/4" dia. uPVC Equal Tee | Nr. | 135.00 |
| T 60 | Supplying and fixing 3/4" dia. uPVC Clips | Nr. | 44.00 |
| T 61 | Supplying and fixing 3/4" dia. uPVC Union | Nr. | 183.00 |
| T 62 | Supplying and fixing 1" dia uPVC Socket | Nr. | 134.00 |
| T 63 | Supplying and fixing 1" dia. uPVC Valve Socket | Nr. | 138.00 |
| T 64 | Supplying and fixing 1" dia. uPVC Faucet Socket | Nr. | 138.00 |
| T 65 | Supplying and fixing 1" dia. uPVC Elbow | Nr. | 138.00 |
| T 66 | Supplying and fixing 1" dia. uPVC Bend | Nr. | 154.00 |
| T 67 | Supplying and fixing 1" dia. uPVC Equal Tee | Nr. | 165.00 |
| T 68 | Supplying and fixing 1" dia. uPVC Clips | Nr. | 45.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| T 69 | Supplying and fixing 1" dia. uPVC Union | Nr. | 249.00 |
| T 70 | Supplying and fixing 1 1/4" dia uPVC Socket | Nr. | 163.00 |
| T 71 | Supplying and fixing 1 1/4" dia. uPVC Valve Socket | Nr. | 180.00 |
| T 72 | Supplying and fixing 1 1/4" dia. uPVC Faucet Socket | Nr. | 186.00 |
| T 73 | Supplying and fixing 1 1/4" dia. uPVC Elbow | Nr. | 191.00 |
| T 74 | Supplying and fixing 1 1/4" dia. uPVC Bend | Nr. | 247.00 |
| T 75 | Supplying and fixing 1 1/4" dia. uPVC Equal Tee | Nr. | 222.00 |
| T 76 | Supplying and fixing 1 1/4" dia. uPVC Clips | Nr. | 48.00 |
| T 77 | Supplying and fixing 1 1/4" dia. uPVC Union | Nr. | 500.00 |
| T 78 | Supplying and fixing 1 1/2" dia uPVC Socket | Nr. | 281.00 |
| T 79 | Supplying and fixing 1 1/2" dia. uPVC Valve Socket | Nr. | 286.00 |
| T 80 | Supplying and fixing 1 1/2" dia. uPVC Faucet Socket | Nr. | 296.00 |
| T 81 | Supplying and fixing 1 1/2" dia. uPVC Elbow | Nr. | 325.00 |
| T 82 | Supplying and fixing 1 1/2" dia. uPVC Bend | Nr. | 414.00 |
| T 83 | Supplying and fixing 1 1/2" dia. uPVC Equal Tee | Nr. | 391.00 |
| T 84 | Supplying and fixing 1 1/2" dia. uPVC Clips | Nr. | 76.00 |
| T 85 | Supplying and fixing 1 1/2" dia. uPVC Union | Nr. | 665.00 |
| T 86 | Supplying and fixing 2" dia uPVC Socket | Nr. | 332.00 |
| T 87 | Supplying and fixing 2" dia. uPVC Valve Socket | Nr. | 349.00 |
| T 88 | Supplying and fixing 2" dia. uPVC Faucet Socket | Nr. | 361.00 |
| T 89 | Supplying and fixing 2" dia. uPVC Elbow | Nr. | 399.00 |
| T 90 | Supplying and fixing 2" dia. uPVC Bend | Nr. | 583.00 |
| T 91 | Supplying and fixing 2" dia. uPVC Equal Tee | Nr. | 477.00 |
| T 92 | Supplying and fixing 2" dia. uPVC Clips | Nr. | 77.00 |
| T 93 | Supplying and fixing 2" dia. uPVC Union | Nr. | 887.00 |
| T 94 | Supplying and fixing 2 1/2" dia uPVC Socket | Nr. | 401.00 |
| T 95 | Supplying and fixing 2 1/2" dia. uPVC Valve Socket | Nr. | 484.00 |
| T 96 | Supplying and fixing 2 1/2" dia. uPVC Faucet Socket | Nr. | 529.00 |
| T 97 | Supplying and fixing 2 1/2" dia. uPVC Elbow | Nr. | 584.00 |
| T 98 | Supplying and fixing 2 1/2" dia. uPVC Bend | Nr. | 1,028.00 |
| T 99 | Supplying and fixing 2 1/2" dia. uPVC Equal Tee | Nr. | 634.00 |
| T 100 | Supplying and fixing 2 1/2" dia. uPVC Clips | Nr. | 126.00 |
| T 101 | Supplying and fixing 2 1/2" dia. uPVC Union | Nr. | 1,832.00 |
| T 102 | Supplying and fixing 3" dia uPVC Socket | Nr. | 646.00 |
| T 103 | Supplying and fixing 3" dia. uPVC Valve Socket | Nr. | 736.00 |
| T 104 | Supplying and fixing 3" dia. uPVC Faucet Socket | Nr. | 741.00 |
| T 105 | Supplying and fixing 3" dia. uPVC Elbow | Nr. | 846.00 |
| T 106 | Supplying and fixing 3" dia. uPVC Bend | Nr. | 1,985.00 |
| T 107 | Supplying and fixing 3" dia. uPVC Equal Tee | Nr. | 1,080.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| T 108 | Supplying and fixing 3" dia. uPVC Clips | Nr. | 137.00 |
| T 109 | Supplying and fixing 3" dia. uPVC Union | Nr. | 2,832.00 |
| T 110 | Supplying and fixing 4" dia uPVC Socket | Nr. | 808.00 |
| T 111 | Supplying and fixing 4" dia. uPVC Valve Socket | Nr. | 1,064.00 |
| T 112 | Supplying and fixing 4" dia. uPVC Faucet Socket | Nr. | 1,068.00 |
| T 113 | Supplying and fixing 4" dia. uPVC Elbow | Nr. | 1,157.00 |
| T 114 | Supplying and fixing 4" dia. uPVC Bend | Nr. | 2,864.00 |
| T 115 | Supplying and fixing 4" dia. uPVC Equal Tee | Nr. | 1,469.00 |
| T 116 | Supplying and fixing 4" dia. uPVC Clips | Nr. | 204.00 |
| T 117 | Supplying and fixing 4" dia. uPVC Union | Nr. | 4,499.00 |
| T 118 | Supplying and fixing 2" - 1 1/2" dia. uPVC. Reducing Socket | Nr. | 354.00 |
| T 119 | Supplying and fixing 2" - 1 1/4" dia. uPVC. Reducing Socket | Nr. | 348.00 |
| T 120 | Supplying and fixing 2" - 1" dia. uPVC. Reducing Socket | Nr. | 342.00 |
| T 121 | Supplying and fixing 2" - 3/4" dia. uPVC. Reducing Socket | Nr. | 338.00 |
| T 122 | Supplying and fixing 2" - 1/2" dia. uPVC. Reducing Socket | Nr. | 332.00 |
| T 123 | Supplying and fixing 1 1/2" - 1 1/4" dia. uPVC. Reducing Socket | Nr. | 309.00 |
| T 124 | Supplying and fixing 1 1/2" - 1" dia. uPVC. Reducing Socket | Nr. | 304.00 |
| T 125 | Supplying and fixing 1 1/2" - 3/4" dia. uPVC. Reducing Socket | Nr. | 287.00 |
| T 126 | Supplying and fixing 1 1/2" - 1/2" dia. uPVC. Reducing Socket | Nr. | 270.00 |
| T 127 | Supplying and fixing 1 1/4" - 1" dia. uPVC. Reducing Socket | Nr. | 180.00 |
| T 128 | Supplying and fixing 1 1/4" - 3/4" dia. uPVC. Reducing Socket | Nr. | 169.00 |
| T 129 | Supplying and fixing 1 1/4" - 1/2" dia. uPVC. Reducing Socket | Nr. | 158.00 |
| T 130 | Supplying and fixing 1" - 3/4" dia. uPVC. Reducing Socket | Nr. | 148.00 |
| T 131 | Supplying and fixing 1" - 1/2" dia. uPVC. Reducing Socket | Nr. | 139.00 |
| T 132 | Supplying and fixing 3/4" - 1/2" dia. uPVC. Reducing Socket | Nr. | 131.00 |
| T 133 | Supplying and fixing 2" - 1 1/2" dia. uPVC. Reducing Tee. | Nr. | 520.00 |
| T 134 | Supplying and fixing 2" - 1 1/4" dia. uPVC. Reducing Tee. | Nr. | 515.00 |
| T 135 | Supplying and fixing 2" - 1" dia. uPVC. Reducing Tee. | Nr. | 509.00 |
| T 136 | Supplying and fixing 2" - 3/4" dia. uPVC. Reducing Tee. | Nr. | 504.00 |
| T 137 | Supplying and fixing 2" - 1/2" dia. uPVC. Reducing Tee. | Nr. | 498.00 |
| T 138 | Supplying and fixing 1 1/2" - 1 1/4" dia. uPVC. Reducing Tee. | Nr. | 387.00 |
| T 139 | Supplying and fixing 1 1/2" - 1" dia. uPVC. Reducing Tee. | Nr. | 354.00 |
| T 140 | Supplying and fixing 1 1/2" - 3/4" dia. uPVC. Reducing Tee. | Nr. | 342.00 |
| T 141 | Supplying and fixing 1 1/2" - 1/2" dia. uPVC. Reducing Tee. | Nr. | 321.00 |
| T 142 | Supplying and fixing 1 1/4" - 1" dia. uPVC. Reducing Tee. | Nr. | 224.00 |
| T 143 | Supplying and fixing 1 1/4" - 3/4" dia. uPVC. Reducing Tee. | Nr. | 220.00 |
| T 144 | Supplying and fixing 1 1/4" - 1/2" dia. uPVC. Reducing Tee. | Nr. | 192.00 |
| T 145 | Supplying and fixing 1" - 3/4" dia. uPVC. Reducing Tee. | Nr. | 175.00 |
| T 146 | Supplying and fixing 1" - 1/2" dia. uPVC. Reducing Tee. | Nr. | 164.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| T 147 | Supplying and fixing 3/4" - 1/2" dia. uPVC. Reducing Tee. | Nr. | 148.00 |
| T 148 | Supplying and fixing 1" - 3/4" dia. uPVC. Reducing Foucet Tee. | Nr. | 230.00 |
| T 149 | Supplying and fixing 1" - 1/2" dia. uPVC. Reducing Faucet Tee. | Nr. | 206.00 |
| T 150 | Supplying and fixing 3/4" - 1/2" dia. uPVC. Reducing Faucet Tee. | Nr. | 164.00 |
| T 151 | Supplying and fixing 3/4" - 1/2" dia. uPVC. Reducing Elbow. | Nr. | 141.00 |
| | <u>Special Pipe fittings</u> | | |
| T 152 | Supplying and fixing 4" (110 mm) dia. Double access branch with cleaning eye (Door tee). | Nr. | 1,107.00 |
| T 153 | Supplying and fixing 4" (110 mm) dia. Double access branch with cleaning eye (Equal tee). | Nr. | 913.00 |
| T 154 | Supplying and fixing 4" (110 mm) dia. Double access branch with cleaning eye (Swept Door tee). | Nr. | 1,229.00 |
| T 155 | Supplying and fixing 4" (110 mm) dia. Double access branch with cleaning eye (Swept tee). | Nr. | 1,018.00 |
| T 156 | Supplying and fixing 4" (110 mm) dia Single access branch with cleaning eye (Single Door Y). | Nr. | 1,291.00 |
| T 157 | Supplying and fixing 4" (110 mm) dia Single access branch with cleaning eye (Single Y). | Nr. | 1,057.00 |
| T 158 | Supplying and fixing 4" (110 mm) dia Swept bend with cleaning eye (Door Bend 89°). | Nr. | 963.00 |
| T 159 | Supplying and fixing 4" (110 mm) dia Swept bend (Bend 89°). | Nr. | 651.00 |
| T 160 | Supplying and fixing 4" (110 mm) dia Swept bend with cleaning eye (Door Bend 45°). | Nr. | 873.00 |
| T 161 | Supplying and fixing 4" (110 mm) dia Swept bend (Bend 45°). | Nr. | 729.00 |
| T 162 | Supplying and fixing 4" (110 mm) dia " P " trap. | Nr. | 1,859.00 |
| T 163 | Supplying and fixing 4" (110 mm) dia " S " trap. | Nr. | 2,017.00 |
| T 164 | Supplying and fixing 4" (110 x 63 x 50mm) Multi floor trap (Catch pit). | Nr. | 1,124.00 |
| T 165 | Supplying and fixing 6" (160mm) dia. Bend. | Nr. | 9,841.00 |
| T 166 | Supplying and fixing 6" (160mm) dia. Socket. | Nr. | 1,931.00 |
| T 167 | Supplying and fixing Reducing Tee 6" x 4" (160mm x 110mm) | Nr. | 1,967.00 |
| T 168 | Supplying and fixing 2" (63 mm)dia.Vent Cowl (Wire Dome) | Nr. | 218.00 |
| T 169 | Supplying and fixing 4" (110mm) dia.Vent Cowl (Wire Dome) | Nr. | 323.00 |
| T 170 | Supplying and fixing 1 1/2" (50 mm) dia. Double access branch with cleaning eye (Swept Door tee). | Nr. | 491.00 |
| T 171 | Supplying and fixing 1 1/2" (50 mm) dia. Double access branch with cleaning eye (Swept tee). | Nr. | 463.00 |
| T 172 | Supplying and fixing 1 1/2" (50 mm) dia. Double access branch with cleaning eye (Door tee). | Nr. | 396.00 |
| T 173 | Supplying and fixing 1 1/2" (50 mm) dia. Double access branch with cleaning eye (Equal tee). | Nr. | 289.00 |
| T 174 | Supplying and fixing 1 1/2" (50 mm) dia Single access branch with cleaning eye (Single Door Y). | Nr. | 396.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| T 175 | Supplying and fixing 1 1/2" (50 mm) dia Single access branch with cleaning eye (Single Y). | Nr. | 324.00 |
| T 176 | Supplying and fixing 1 1/2" (50 mm) dia Swept bend with cleaning eye (Door Bend 89°). | Nr. | 307.00 |
| T 177 | Supplying and fixing 1 1/2" (50 mm) dia Swept bend (Bend 89°). | Nr. | 246.00 |
| T 178 | Supplying and fixing 1 1/2" (50 mm) dia Swept bend with cleaning eye (Door Bend 45°). | Nr. | 307.00 |
| T 179 | Supplying and fixing 1 1/2" (50 mm) dia Swept bend (Bend 45°). | Nr. | 240.00 |
| T 180 | Supplying and fixing 1 1/2" (50 mm) dia Swept tee with cleaning eye. | Nr. | 396.00 |
| T 181 | Supplying and fixing 1 1/2" (50 mm) dia Swept tee. | Nr. | 289.00 |
| T 182 | Supplying and fixing 1 1/2" (50 mm) dia Equal tee. | Nr. | 396.00 |
| | <u>Hot water Pipes & Fittings</u> | | |
| T 183 | Supplying , laying and/or fixing 1/2" dia. CPVC - SDR pipes. (Specials paid separately). | L.ft. | 160.00 |
| T 184 | Supplying , laying and/or fixing 1" dia. CPVC - SDR pipes. (Specials paid separately). | L.ft. | 272.00 |
| T 185 | Supplying and fixing 1/2" dia. CPVC Socket. | Nr. | 95.00 |
| T 186 | Supplying and fixing 1" dia. CPVC Socket. | Nr. | 170.00 |
| T 187 | Supplying and fixing 1/2" dia. CPVC Valve Socket. | Nr. | 109.00 |
| T 188 | Supplying and fixing 1" dia. CPVC Valve Socket. | Nr. | 219.00 |
| T 189 | Supplying and fixing 1/2" dia. CPVC Faucet Socket. | Nr. | 126.00 |
| T 190 | Supplying and fixing 1" dia. CPVC Faucet Socket. | Nr. | 243.00 |
| T 191 | Supplying and fixing 1/2" dia. CPVC Tee. | Nr. | 126.00 |
| T 192 | Supplying and fixing 1" dia. CPVC Tee. | Nr. | 428.00 |
| T 193 | Supplying and fixing CPVC Elbow 1/2" x 45° | Nr. | 120.00 |
| T 194 | Supplying and fixing CPVC Elbow 1/2" x 90° | Nr. | 111.00 |
| T 195 | Supplying and fixing CPVC Elbow 1" x 45° | Nr. | 279.00 |
| T 196 | Supplying and fixing CPVC Elbow 1" x 90° | Nr. | 230.00 |
| T 197 | Supplying and fixing CPVC Reducing Socket 1" x 1/2" | Nr. | 174.00 |
| T 198 | Supplying and fixing CPVC Reducing Tee 1" x 1/2" | Nr. | 350.00 |
| T 199 | Supplying and fixing 1/2" dia. CPVC End Cap. | Nr. | 78.00 |
| T 200 | Supplying and fixing 1" dia. CPVC End Cap. | Nr. | 149.00 |
| T 201 | Supplying and fixing 1/2" dia. CPVC Tap End Plug. | Nr. | 97.00 |
| T 202 | Supplying and fixing 1/2" dia. CPVC Union. | Nr. | 613.00 |
| T 203 | Supplying and fixing 1/2" dia. CPVC Elbow Holder. | Nr. | 375.00 |
| T 204 | Supplying and fixing 1" dia. CPVC Elbow Holder. | Nr. | 491.00 |
| T 205 | Supplying and fixing 1/2" dia. CPVC Brass Male Adapter. | Nr. | 650.00 |
| T 206 | Supplying and fixing 1/2" dia. CPVC Brass Female Adapter. | Nr. | 630.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| T 207 | Supplying and fixing 1/2" dia. CPVC Brass Elbow. | Nr. | 295.00 |
| | <u>Water Tanks</u> | | |
| 1 | Water tank should combined with three layers of high density polyethylene except 5000 Ltr. Water tank. | | |
| 2 | The inner and outer layers made of 100% FDA approved virgin raw materials , ensuring non-contamination. | | |
| 3 | Contractor should submit the purchasing bill and the required warranty for water tanks (10 year warranty) manufactured by "Anton , Arpico" to the Divisional Engineer. | | |
| T 208 | Supplying and installing of water tank 500 Ltr. capacity (fittings paid separately) at an average height of 12'-0" including transporting and hoisting in position. | Nr. | 9,394.00 |
| | From T 209 to T 211 hoisting in position paid seperately under item no.Y 59. | | |
| T 209 | Supplying and installing of water tank 1000 Ltr. capacity (fittings paid separately) including the cost of transport. Hoisting in position to be paid seperately. | Nr. | 15,387.00 |
| T 210 | Supplying and installing of water tank 2000 ltr. capacity (fittings paid separately) including the cost of transport. Hoisting in position to be paid seperately. | Nr. | 28,363.00 |
| T 211 | Supplying and installing of water tank 5000 ltr. capacity (fittings paid separately) including the cost of transport. Hoisting in position to be paid seperately. | Nr. | 69,491.00 |
| | <u>Pumps & Accessories</u> | | |
| T 212 | Supplying and fixing water pump single phase manufactured by " Jinasena" Model no:- 10CJ 024S ,size 1" x 1" , 0.75 H.P. , total head 80'-0" , out put 1000 l.g/hr. as per manufacturer's specifications. Rate include for fixing 1" dia. Foot valve approved make, Positioning and mount the pump on a concrete bed 9" x 9" x 3" thick in 1:2:4(3/4") with 10mm dia. hexagonal bolts to required length , Nuts & Washers 1/16" thick complete in working order using necessary uPVC pipes, specials...etc. & electrical supply from the closest DB. Pipes , specials & electricity connection paid separately. | Nr. | 27,603.00 |
| T 213 | Supplying and fixing 1" Deep Well Kit by " Jinasena" Model no:- Type A as per manufacturer's specifications and complete in working order using necessary uPVC pipes, specials...etc. & electrical supply from the closest DB. (Pipes , specials & electricity connection paid separately.) | Nr. | 9,959.00 |
| | <u>Weep Hole</u> | | |
| T 214 | Supplying and placing 4" dia. uPVC (Type 250) wheep holes. | L.ft | 140.00 |
| T 215 | Supplying and placing 2" dia. uPVC (Type 400) wheep holes. | L.ft | 159.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|----------------|----------------|
| | <u>Dewatering</u> | | |
| T 216 | Dewatering using 2" dia. water pump. | Per 8 Hour Day | 4,439.00 |
| | <u>U - DRAINAGE</u> | | |
| | <u>Waste Water Manhole - Brick</u> | | |
| U 01 | Construction of waste water brick manhole internal size of 1'-0" x 1'-0" & depth upto 1'-3", consist of 3" thick Grade 15 concrete base and 4 1/2" thick brick masonry side walls in 1:3 cement sand mix , 1/2" thick cement rendering in 1:2 mix trowel smooth with neat grey cement to internal & external exposed faces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm tor steel @ 4" c/c both ways.) paid seperately. Refer Drawing No:-WSS/2020/01 | Nr. | 3,294.00 |
| U 02 | Construction of waste water brick manhole internal size of 1'-3" x 1'-3" & depth upto 2'-0", consist of 3" thick Grade 15 concrete base and 4 1/2" thick brick masonry side walls in 1:3 cement sand mix , 1/2" thick cement rendering in 1:2 mix trowel smooth with neat grey cement to internal & external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm tor steel @ 4" c/c both ways.) paid seperately. Refer Drawing No:- WSS/2020/01 | Nr. | 6,122.00 |
| U 03 | Construction of waste water brick manhole internal size of 1'-6" x 1'-6" & depth up to 2'-0", consist of 3" thick Grade 15 concrete base and 4 1/2" thick brick masonry side walls in 1:3 cement sand mix , 1/2" thick cement rendering in 1:2 mix trowel smooth with neat grey cement to internal & external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm tor steel @ 4" c/c both ways.) paid seperately. Refer Drawing No:-WSS/2020/01 | Nr. | 8,334.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| U 04 | Construction of waste water brick manhole internal size of 2'-0" x 2'-0" & depth up to 2'-0", consist of 4" thick Grade 15 concrete base and 9" thick brick masonry side walls in 1:3 cement sand mix, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer. Excavation and 4" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm tor steel @ 4" c/c both ways.) paid separately as per Drawing No:- WSS/2020/01 | Nr. | 18,958.00 |
| U 05 | Construction of waste water brick manhole internal size of 2'-6" x 2'-6" & depth vary from 2'-0" -4'-0", consist of 4" thick Grade 15 concrete base and 9" thick brick masonry side walls in 1:3 cement sand mix, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer. Excavation and 4" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm tor steel @ 4" c/c both ways.) paid separately Refer Drawing No:- WSS/2020/01 | Nr. | 30,517.00 |
| | Waste Water Manhole - Concrete | | |
| U 06 | Construction of waste water concrete manhole internal size of 1'-0" x 1'-0" & depth up to 1'-3", consist of 4" thick Grade 25 concrete base and sides, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm dia.M.S. rods @ 4" c/c both ways) paid separately as per Drawing No:-WSS/2020/02 | Nr. | 3,250.00 |
| U 07 | Construction of waste water concrete manhole internal size of 1'-3" x 1'-3" & depth up to 2'-0", consist of 4" thick Grade 25 concrete base and sides, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm dia.M.S. rods @ 4" c/c both ways) paid separately as per Drawing No:-WSS/2020/02 | Nr. | 4,711.00 |
| U 08 | Construction of waste water concrete manhole internal size of 1'-6" x 1'-6" & depth vary from 2'-0" - 3'-0", consist of 3" thick Grade 15 lean concrete & 5" thick Grade 25 RCC base and sides, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid separately as per Drawing No:- WSS/2020/02 | Nr. | 18,184.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| U 09 | Construction of waste water concrete manhole internal size of 2'-6" x 2'-6" & depth vary 2'-0" - 3'-0", consist of 3" thick Grade15 lean concrete & 5" thick Grade 25 RCC base and sides, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/02 | Nr. | 26,730.00 |
| U 10 | Construction of waste water concrete manhole internal size of 2'-6" x 2'-6" & depth vary 3'-0" - 5'-0", consist of 3" thick Grade15 lean concrete & 5" thick Grade 25 RCC base and sides, 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/02 | Nr. | 36,009.00 |
| | <u>Sewer Manhole - Brick</u> | | |
| U 11 | Construction of brick sewer manhole internal size of 2'-1" x 1'-7" & depth vary from 1'-6" - 2'-0", consist of 6" thick Grade 15 lean concrete base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer and forming channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/03 | Nr. | 17,860.00 |
| U 12 | Construction of brick sewer manhole internal size of 2'-6" x 1'-7" & depth vary from 2'-0" - 3'-0", consist of 6" thick Grade 15 lean concrete base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer and forming channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/03 | Nr. | 21,955.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| U 13 | Construction of brick sewer manhole internal size of 3'-4 1/2" x 2'-3" & depth vary from 2'-0" - 3'-0", consist of 6" thick Grade 15 lean concrete base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer and forming channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/04 | Nr. | 29,087.00 |
| U 14 | Construction of brick sewer manhole internal size of 4'-6" x 2'-7 1/2" & depth vary from 2'-0" - 3'-0", consist of 6" thick Grade 15 lean concrete base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer and forming channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/05 | Nr. | 37,098.00 |
| U 15 | Construction of brick sewer manhole internal size of 4'-6" x 2'-7 1/2" & depth vary from 3'-0" - 5'-0", consist of 6" thick Grade 15 lean concrete base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer and forming channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/05 | Nr. | 53,653.00 |
| U 16 | Construction of brick Interceptor manhole internal size 4'-6"x 2'-7 1/2" depth up to 5'-6" consist of 2" thick Grade 15 lean concrete base , 6" thick Grade 20 R.C.C base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer, forming channel with 1:6 benching, interceptor with stopper and M.S steps . Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.) paid seperately as per Drawing No:- WSS/2020/06 | Nr. | 77,532.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| U 17 | Construction of brick drop manhole internal size 4'-6"x 2'-7 1/2" and depth up to 5'-0", consist of 3" thick Grade 15 lean concrete base , 6" thick Grade 20 R.C.C base and 9" thick brick masonry side walls in in 1:3 cement sand mix ,1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces of walls finished 5/8" thick plastering in cement sand 1:3 including finishing with cement slurry floating including cost of "Febmix" as a workability enhancer, forming channel with 1:6 benching and M.S steps . Excavation , 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm tor steel @ 6" c/c both ways.), P.V.C pipes and specials paid seperately as per Drawing No:- WSS/2020/07 | Nr. | 53,706.00 |
| | <u>Sewer Manhole - Concrete</u> | | |
| U 18 | Construction of RCC sewer manhole internal size of 2'-1" x 1'-7" & depth up to 2'-0", consist of 3" thick Grade 15 lean concrete, base and side walls 6" thick Grade 25 concrete r/f with 10mm dia. tor steel @ 8" c/c bothways , 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces and channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/08 | Nr. | 22,730.00 |
| U 19 | Construction of RCC sewer manhole internal size of 2'-6" x 1'-7" & depth vary from 2'-0" - 3'-0" , consist of 3" thick Grade 15 lean concrete, base and side walls 6" thick Grade 25 concrete r/f with 10mm dia. tor steel @ 8" c/c bothways , 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces and channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/08 | Nr. | 26,000.00 |
| U 20 | Construction of RCC sewer manhole internal size of 3'-4 1/2" x 2'-3" & depth vary from 2'-0" - 3'-0", consist of 3" thick Grade 15 lean concrete, base and side walls 6" thick Grade 25 concrete r/f with 10mm dia. tor steel @ 8" c/c bothways , 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces and channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/08 | Nr. | 37,933.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| U 21 | Construction of RCC sewer manhole internal size of 4'-6" x 2'-7 1/2" & depth vary from 2'-0" - 3'-0" , consist of 3" thick Grade 15 lean concrete, base and side walls 6" thick Grade 25 concrete r/f with 10mm dia. tor steel @ 8" c/c bothways , 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces and channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/09 | Nr. | 47,160.00 |
| U 22 | Construction of RCC sewer manhole internal size of 4'-6" x 2'-7 1/2" & depth vary from 3'-0" - 5'-0" , consist of 3" thick Grade 15 lean concrete, base and side walls 6" thick Grade 25 concrete r/f with 10mm dia. tor steel @ 8" c/c bothways , 1/2" thick cement sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces and external exposed surfaces and channel with 1:6 benching. Excavation and 3" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 10mm dia.M.S. rods @ 6" c/c both ways) paid seperately as per Drawing No:- WSS/2020/09 | Nr. | 63,194.00 |
| | <u>Soakage Pits - Brick</u> | | |
| U 23 | Construction of 4'-0" dia. soakage pit in hard soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/01. | Nr. | 27,569.00 |
| U 24 | Construction of 6'-0" dia. soakage pit in hard soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/02. | Nr. | 46,849.00 |
| U 25 | Construction of 8'-0" dia. soakage pit in hard soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/03. | Nr. | 62,060.00 |
| U 26 | Construction of 4'-0" dia. soakage pit in loose soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/04. | Nr. | 88,952.00 |
| U 27 | Construction of 6'-0" dia. soakage pit in loose soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/05. | Nr. | 134,224.00 |
| U 28 | Construction of 8'-0" dia. soakage pit in loose soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/SP/06. | Nr. | 175,589.00 |
| | <u>Septic tanks- Brick</u> | | |
| U 29 | Construction of 30 person Septic tank excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/01. | Nr. | 167,856.00 |
| U 30 | Construction of 50 person Septic tank excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/01. | Nr. | 194,429.00 |
| U 31 | Construction of 70 person Septic tank excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/01. | Nr. | 218,906.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| U 32 | Construction of 100 person Septic tank excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/01. | Nr. | 260,619.00 |
| U 33 | Construction of 150 person Septic tank excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/02. | Nr. | 333,208.00 |
| | <u>Septic tanks- RCC Grade 25</u> | | |
| U 34 | Construction of 100 person RCC Grade 25 Septic tank on hard soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/03. | Nr. | 482,801.00 |
| U 35 | Construction of 150 person RCC Grade 25 Septic tank on hard soil excluding necessary excavation all complete as per Drawing No:- WSS/2020/ST/04. | Nr. | 600,494.00 |
| U 36 | Supplying and fixing 4'-0" dia.x 8'-0" Pre-cast Septic tank manufactured by "SEC" or approved equivalent placed on sand or quarry dust bedding from 1'-0" below bottom of the septic tank and fill upto 2'-0" height surrounding the tank. (Excavation and transport of the septic tank paid seperately). Rate shall include hire charges of boomtruck for placing and subject to specific approval by the Divisional Engineer. All details given in Drawing No:- WSS/2020/ST-SP/05. | Nr. | 68,952.00 |
| U 37 | Supplying and fixing 3'-0" internal dia.x 4'-0" depth Pre-cast Soakage pit with perporated holes manufactured by "SEC" or approved equivalent. (Excavation, cost of the 6" thick gravel backing surrounding the tank and transport of the Soakage pit paid seperately). Rate shall include hire charges of boomtruck for placing and subject to specific approval by the Divisional Engineer. All details given in Drawing No:- WSS/2020/ST-SP/05 | Nr. | 27,186.00 |
| | <u>Gulleys</u> | | |
| U 38 | Construction of gully internal size of 1'-2" x 1'-2" & depth up to 1'-4", consist of 3" thick Grade 20 concrete base and 4 1/2" thick brick masonry side walls in 1:3 cement sand mix , gully trap infill with grade 20 concrete and 1/2" thick cement & sand rendering in 1:2 mix trowel smooth with neat grey cement to all internal surfaces , exposed external surfaces and forming channel with 1:6 benching. Excavation and 2" thick Grade 20 RCC cover slab with lifting hooks (Reinforced with 6mm dia.M.S. rods @ 4" c/c both ways) paid seperately as per as per Drawing No:-WSS/2020/Gully/10 | Nr. | 4,849.00 |
| | <u>Surface Water Drain</u> | | |
| U 39 | Construction of concrete drain 2'-10" width x 2'-0" depth and varies up to 2'-7" Consists of 2" thick Grade 15 concrete base and 5" thick Grade 25 concrete walls , fair finish internal surface with size 2'-0" wide x 2'-0" depth. Excavation and removable grating to be paid seperately. All details given in Drawing No:- WSS/2020/SWD/11 | l.ft. | 2,873.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| | <u>Shoe Drain</u> | | |
| U 40 | Construction of Shoe drain (in Grade 20 Concrete of width 18" , average thickness 8" , height 12".) | L.ft | 1,098.00 |
| | <u>Manhole Covers</u> | | |
| | <u>RCC Manhole cover - Grade 20</u> | | |
| U 41 | RCC Manhole cover 5" thick Consist of Grade 25 concrete reinforced with two layers 10mm dia. Tor steel bars @ 8" C/C both ways. Rate include necessary formwork, lifting hooks and placing in position. All details given in Drawing No:- WSS/2020/MC/12 | Sq.ft. | 857.00 |
| U 42 | RCC Manhole cover 3" thick Consist of Grade 20 concrete & 10mm dia. Tor steel bars @ 6" C/C both ways. Rate include necessary formwork, lifting hooks and placing in position. All details given in Drawing No:- WSS/2020/MC/12 | Sq.ft. | 485.00 |
| U 43 | RCC Manhole cover 2" thick Consist of Grade 20 concrete & 6mm dia. Tor steel bars @ 4" C/C both ways. Rate include necessary formwork, lifting hooks and placing in position. All details given in Drawing No:- WSS/2020/MC/12 | Sq.ft. | 498.00 |
| | <u>Double seal cast iron manhole cover with frame</u> | | |
| | Double seal cast iron manhole cover with frame should comply with European Standard BS EN 124. | | |
| U 44 | Supplying & fixing double seal cast iron manhole cover with frame capable of withstanding a 125kN load use in car parks and pedestrian areas where only occasional vehicular access is likely. | sq.ft | 7,348.00 |
| U 45 | Supplying & fixing double seal cast iron manhole cover with frame capable of withstanding a 400kN load use in areas where cars and lorries have access including carriage ways, hard shoulders and pedestrian areas. | sq.ft | 9,838.00 |
| | <u>Removable Grating For Surface Drain</u> | | |
| U 46 | Supplying & fixing iron grating for surface drain consists of outer angle iron 2 1/2" x 2 1/2" x 6mm thick welded to top angle iron 1" x 1" x 5mm thick @ 3'-0" c/c horizontally and 16mm dia. tor steel @ 1" internal to internal welded to top of angle iron 1" x 1" x 5mm thick. All details given in Drawing No:- WSS/2020/SWD/11 . Rate shall include for applying two coats of anti-corrosive paint. | sq.ft | 1,198.00 |
| | <u>V - ELECTRICAL INSTALLATION.</u> | | |
| | <u>Note:</u> | | |
| | Work shall be done in accordance with specifications for electrical and mechanical works - ICTAD Publication No.SCA/8 of Aug.2000(2nd Edition -Revised) | | |
| 1 | Internal light wiring shall comply with the drawings and shall be in 230/440 volt single core PVC insulated copper cables | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| 2 | All switches and socket outlets shall be plated type make "Clipsal", "Orange X5", "Krypton" or any other approved equivalent complying to SLS1000:1993 for switches & SLS 1998 : 1991 for socket outlets . | | |
| 3 | All Fluorescent fittings shall be zinc coated steel sheet finished with powder coated to 0.45mm thickness complete with electronic choke (Make:- "Atco", "BG" original or -Equivalent) starter and the tube should be Thron, Philips, or Osram | | |
| 4 | Rate to include switch boxes, Rowl plugs, square pin plug base, Chromium plated M.S. chains, brass hooks, ceiling roses, holders and any other item necessary. | | |
| 5 | All distribution boards should be incorporated with multi 9, Orange Industrial, Merlin Gerin, , Hager, LS, Moeller/EATON, clipsal, SIEMENS make MCB's (Miniature circuit Breaker) and cabtree, Clipsal ,Orange Industrial 10 kA, LS , Merlin Gerin, Schinieder make R.C.C.B.'s (Residual Current circuit Breaker) and Schinieder, Merlin Gerin, LS, Dormans Smith ,Orange Industrial (10K), Biticano , Clockner moeller make M.C.C.B.'s (Moulded Case Circuit Breakers) | | |
| 6 | The whole installation shall be carried out according to CEB/IEE wiring regulations. | | |
| 7 | All the M.C.C.B.'s, MCB's and RCCB's for the distribution boards should be purchased from the following authorized agents or from their dealers and a certificate or invoice along with their Company seal and Part No., numbers and warranty should be produced at the time of payment. | | |
| | a). All MCB, RCCB, shall have 20 Years warranty and hence products which comes with 20 years warranty are permitted. | | |
| | b). All MCCB shall have 2 Years warranty and hence products which comes with 2 years warranty are permitted. | | |
| | M.C.C.B.'s Merlin Gerin brand - Figaro Ltd. Schneider brand - Schinder Electrical Lanka PVT LTD Moeller/Eaton brand - Richardson - Electrical (Pvt) Ltd. Orange Industrial brand - Orel Corporation(Pvt) Ltd, LS brand - Aklan Internationak (pvt) Ltd | | |
| | M.C.B.'s SIEMENS brand - RotexLtd. Orange Industrial brand (10 kA) - Orel Corporation(Pvt) Ltd. Moeller/Eaton brand - Richardson - Electrical (Pvt) Ltd. LS brand - Aklan Internationak (pvt) Ltd | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | R.C.C.B's Schnieider brand - Schinder Electrical Lanka Pvt Ltd. Cabtree brand - Nawaloka Ltd. Moeller/Eaton brand - Richardson -Electrical (Pvt) Ltd. OrangeIndustrial brand - Orel Corporation(Pvt) Ltd. LS brand - Aklan Internationak (pvt) Ltd | | |
| | c). Single core PVC insulated copper cable Orel Corporation(Pvt) Ltd. Kelani Cables PLC. ACL Cables PLC. Sierra Cables PLC. | | |
| | d). Arial Bundle Cable (ABC) Kelani Cables PLC. Sierra Cables PLC. | | |
| | e). All socket and switches shall have 20 Years warranty and hence products which comes with 20 years warranty are permitted. | | |
| | Switches and Socket outlet Orange Industrial brand - Orel Corporation(Pvt) Ltd. Krypton brand - Central Industries PLC. | | |
| | f). Powder coated Steel Enclosures Rotex Ltd. Marline Ltd. Figaro Ltd./MSS(Pvt) Ltd Orel Corporation(Pvt) Ltd. | | |
| | g). Plastic Enclosures, PVC Conduits & fittings, PVC Trunking & Fittings - Polycrome Electrical Industries (pvt) ltd | | |
| | h).Lighting Fittings - Myland Marketing (pvt) Ltd Orel Corporation (Pvt) Ltd Greenee - Nature Efficient Electronics Lanka (pvt) Ltd NVC - Overseas Reality Trading (pvt) Ltd. Any product with comparable shapes, material properties and warranties are acceptable | | |
| | All Lighting Fittings shall have 2 Years warranty including bulb and hence products which comes with 2 Years warranty are permitted. | | |
| 8 | The height of the light bracket from floor level is 2.5m. | | |
| 9 | Height of the switches from floor level is 1.5m. | | |
| 10 | No ceiling fan should be installed at a height of less than 2.7m from floor level. | | |
| 11 | The distance of a light source from the wall should be equal to one half the distance between two adjacent light sources and also the distance between light fittings should not exceed 1.5 times the Mounting height. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| 12 | Point wiring only with and including switches (Rate includes wiring from MCB through switch to lamp point and includes the switch, switch box, lamp holder wire and conduit) | | |
| 13 | Point wiring only with and including Socket (Rate includes wiring from MCB to the Socket, socket box, and conduit) | | |
| 14 | In case the cable length of wiring point exceed 80 feet refer item V 65 & V 66 for payment of additional length. | | |
| | <u>Point Wiring Without Earthwire.</u> | | |
| | Items V 01 - V 20 shall be used for light point wiring with Non-Metal casing lamp fittings. | | |
| V 01 | Light point wired through a 10 Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 2,264.00 |
| V 02 | Light points wired through a 10 Amp two gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 2,906.00 |
| V 03 | Light points wired through a 10 Amp three gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 3,537.00 |
| V 04 | Light points wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm (2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 4,156.00 |
| V 05 | Light points-wired through a 10 Amp five gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 4,781.00 |
| V 06 | Light point wired through a 10 Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 3,343.00 |
| V 07 | Light points wired through a 10 Amp two gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 4,237.00 |
| V 08 | Light points wired through a 10 Amp three gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 5,119.00 |
| V 09 | Light points wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 5,990.00 |
| V 10 | Light points wired through a 10 Amp. five gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 6,867.00 |
| V 11 | Light point wired through a 10 Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 2,965.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| V 12 | Light points wired through a 10 Amp two gang one way using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 3,733.00 |
| V 13 | Light points wired through a 10 Amp three gang one way using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 4,489.00 |
| V 14 | Light points wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 5,234.00 |
| V 15 | Light points wired through a 10 Amp. five gang one way plate switch using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 5,985.00 |
| V 16 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 2,836.00 |
| V 17 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 3,915.00 |
| V 18 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044)P.V.C. insulated copper wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 3,537.00 |
| V 19 | Electric Bell with Bell press switch using 2x1/1.13mm (2x1/.044) PVC/insulated copper wire in fully concealed/ surface PVC conduits. (For a switch circuit) | Nr. | 3,289.00 |
| V 20 | Electric Bell with bell press switch using flexible wire (twisted twin wire) in fully surface plastic casing and capping. only in the table legs and floor crossings. (For a switch circuit) | Nr. | 3,393.00 |
| | <u>Point Wiring With Earthwire.</u> | | |
| | Items V 21 - V 40 shall be used for light point wiring for lamp fittings with metal enclosed which has to be earthed. | | |
| V 21 | Light point wired through a 10Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 3,364.00 |
| V 22 | Light point wired through a 10Amp two gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 4,373.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| V 23 | Light point wired through a 10 Amp three gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 5,370.00 |
| V 24 | Light point wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 6,356.00 |
| V 25 | Light point wired through a 10 Amp five gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 7,347.00 |
| V 26 | Light point wired through a 10 Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 4,443.00 |
| V 27 | Light point wired through a 10 Amp two gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 5,703.00 |
| V 28 | Light point wired through a 10 Amp three gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 6,953.00 |
| V 29 | Light point wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 8,190.00 |
| V 30 | Light point wired through a 10 Amp five gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 9,434.00 |
| V 31 | Light point wired through a 10 Amp one gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 4,065.00 |
| V 32 | Light point wired through a 10 Amp two gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 5,199.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| V 33 | Light point wired through a 10 Amp three gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 6,323.00 |
| V 34 | Light point wired through a 10 Amp four gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 7,434.00 |
| V 35 | Light point wired through a 10 Amp five gang one way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 8,552.00 |
| V 36 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 3,936.00 |
| V 37 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 5,015.00 |
| V 38 | Light point wired through a 10 Amp one gang two way plate switch using 2x1/1.13mm(2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire first half in surface plastic casing & capping and other half in conduit. (For a switch circuit) | Nr. | 4,637.00 |
| V 39 | Electric Bell with Bell press switch using 2x1/1.13mm (2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. (For a switch circuit) | Nr. | 4,444.00 |
| V 40 | Electric Bell with Bell press switch using 2x1/1.13mm (2x1/.044) P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. (For a switch circuit) | Nr. | 5,238.00 |
| | Switch Socket Wiring (V 41 - V 45) | | |
| V 41 | Flush mounted 13 Amp switch socket outlet wired using 2x7/0.67(2x7/.029) insulated copper wire & 1x7/0.67(7/.029) copper earth wire in fully concealed/surface P.V.C. conduits.(Each Radial Circuit feed 4 nos. of sockets as per Drawing no. ELE/ST/05) | Nr. | 3,016.00 |
| V 42 | Flush mounted 13 Amp switch socket outlet wired using 2x7/0.67(2x7/.029) insulated copper wire & 1x7/0.67(7/.029) copper earth wire in fully surface plastic casing and capping..(Each Radial Circuit feed 4 nos. of sockets as per Drawing no. ELE/ST/05) | Nr. | 3,413.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------------------------|
| V 43 | Flush mounted 13 Amp switch socket outlet wired using 2x7/0.67(2x7/.029) insulated copper wire & 1x7/0.67(7/.029) copper earth wire in fully concealed/surface P.V.C. conduits and subject to specific approval by the Divisional Engineer. (Each Radial Circuit feed single no. of socket). | Nr. | 4,862.00 |
| V 44 | Flush mounted 13 Amp switch socket outlet wired using 2x7/0.67(2x7/.029) insulated copper wire & 1x7/0.67(7/.029) copper earth wire in surface plastic casing and capping and subject to specific approval by the Divisional Engineer. (Each Radial Circuit feed single no. of socket). | Nr. | 5,467.00 |
| V 45 | Flush mounted 13 Amp. non-reversible type square pin switched socket outlets wired in ring circuit using 4x1x7/0.67 PVC insulated copper wire & 2x7/0.67 PVC insulated copper earth wire in casing and capping (As per Drawing no. ELE/ST/06) . | Nr. | Rate as following formula |
| | $R = \frac{850}{N} \times L + \frac{650}{N} \times N$ | | |
| | N | | |
| | R = Rate per pointt (to be calculated as per formula. | | |
| | L = Distance from DB to last socket (in Meter) | | |
| | N = Number of 13 Amp. sockets | | |
| | Rate for items V 46 - V 55 shall include the cost of wiring, regulator, fan hook & other accessories. For regulator shall be a three star energy. | | |
| V 46 | Fan regulator wired without a switch using 2x1/1.13 mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C. conduits. | Nr. | 3,673.00 |
| V 47 | Fan regulator wired through a 10 Amp plate one gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/surface P.V.C.conduits. | Nr. | 3,871.00 |
| V 48 | Fan regulator wired without a switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. | Nr. | 4,935.00 |
| V 49 | Fan regulator wired through a 10 Amp plate one gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping | Nr. | 5,133.00 |
| V 50 | Fan regulator wired without a switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in half surface with plastic casing and copping and other half in conduit. | Nr. | 4,304.00 |
| V 51 | Fan regulator wired through a 10 Amp plate one gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in half surface with plastic casing and copping and other half in conduit. | Nr. | 4,502.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|---|--|-------|----------------|
| V 52 | Two Fan regulator wired through a 10 Amp plate two gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/ surface PVC conduit | Nr. | 5,222.00 |
| V 53 | Two Fan regulator wired through a 10Amp plate two gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. | Nr. | 6,741.00 |
| V 54 | Three Fan regulator wired through a 10 Amp plate three gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully concealed/ surface PVC conduit | Nr. | 7,098.00 |
| V 55 | Three Fan regulator wired through a 10Amp plate three gang one way switch using 2x1/1.13mm P.V.C. insulated copper wire & 1x7/0.67mm P.V.C. insulated copper earth wire in fully surface plastic casing and capping. | Nr. | 9,131.00 |
| Supply & install only the following V 56 - V 62 | | | |
| Rate of items V 56 - V 57 for Ceiling Fan - Luxury Range | | | |
| V 56 | Ceiling fan of 56" Sweep KDK- brand (M56RG-model) with Air flow rate of 225 cu.m /min @ RPM 270 with tolerance as per SLS 814 and two star energy label as PER SLS 1600 (This item shall be specific requirements) | Nr. | 11,600.00 |
| V 57 | Ceiling fan of 56" Sweep "AVIATOR" brand (-model) with Air flow rate of 250 cu.m /min @ RPM 290 with tolerance as per SLS 814 and two star energy label as PER SLS 1600 (This item shall be specific requirements) | Nr. | 11,256.00 |
| Rate of items V 58 - V 59 for Ceiling Fan - Semiluxury Range | | | |
| V 58 | Ceiling fan of 56" Sweep "Atom Ex" with Air flow of 240 cu.m /min @ RPM 280 with tolerance as per SLS 814 and two star energy label as per SLS 1600. | Nr. | 9,311.00 |
| V 59 | Ceiling fan of 48" Sweep "Technix Plus" with Air flow of 215 cu.m /min @ RPM 330 with tolerance as per SLS 814 and two star energy label as per SLS 1600. ((Approx. floor area not less than 12' 0" x 12' 0") | Nr. | 9,082.00 |
| V 60 | Dimmer type fan regulator with a switch (Orange or equivalent) | Nr. | 1,352.00 |
| V 61 | Exhaust fan 12" dia. With louver - (K.D.K. or approved equivalent) | Nr. | 16,789.00 |
| V 62 | Wall mounted fan - (K.D.K. or approved equivalent) 12960 | Nr. | 15,800.00 |
| V 63 | Supply & Fixing 3/4" dia. x 1.8mm thick GI pipes to extend the ceiling fan rod with applying 2 coats of anti-corrosive paint and one coat of enamel paint. | L.ft. | 168.00 |
| V 64 | Supply & Fixing 1" dia. x 2mm thick GI pipes to extend the ceiling fan rod with applying 2 coats of anti-corrosive paint and one coat of enamel paint. | L.ft. | 211.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| | <u>Cable Wiring.</u> | | |
| V 65 | Supplying and wiring 2 x 1.0mm ² (1/.044") Cu/PVC/PVC cable + 1.0mm ² (1/.044) earth wire to working order excluding conduit. | L.ft. | 58.00 |
| V 66 | Supplying and wiring 2 x 1.0mm ² (1/.044") Cu/PVC/PVC cable complete to working order excluding conduit/casing | L.ft. | 44.00 |
| V 67 | Supplying and wiring 2 x 2.5mm ² (7/.029") Cu/PVC/PVC cable + 2.5mm ² (7/.029) earth wire to working order excluding conduit. | L.ft. | 113.00 |
| V 68 | Supplying and wiring 2 x 4mm ² (7/.036") Cu/PVC/PVC cable + 4mm ² (7/.036) earth wire to working order excluding conduit. | L.ft. | 163.00 |
| V 69 | Supplying and wiring 4 x 4mm ² (7/.036") Cu/PVC/PVC cable + 4mm ² (7/.036) earth wire to working order excluding conduit. | L.ft. | 261.00 |
| V 70 | Supplying and wiring 2 x 6mm ² (7/.044") Cu/PVC/PVC cable + 6mm ² (7/.044") earth wire complete to working order excluding conduit/casing | L.ft. | 228.00 |
| V 71 | Supplying and wiring 2 x 6mm ² (7/.044") Cu/PVC/PVC cable complete to working order excluding conduit/casing | L.ft. | 174.00 |
| V 72 | Supplying and wiring 4 x 6mm ² (7/.044") Cu/PVC/PVC cable + 6mm ² (7/.044") earth wire complete to working order excluding conduit/casing | L.ft. | 362.00 |
| V 73 | Supplying and wiring 2 x 10mm ² (7/.052") Cu/PVC/PVC cable + 10mm ² (7/.052") earth wire complete to working order excluding conduit/casing | L.ft. | 357.00 |
| V 74 | Supplying and wiring 4 x 10mm ² (7/.052") Cu/PVC/PVC cable + 10mm ² (7/.052") earth wire complete to working order excluding conduit/casing | L.ft. | 558.00 |
| V 75 | Supplying and wiring 4 x 10 mm ² (7/.052") Cu/PVC/PVC cable complete to working order excluding conduit/casing | L.ft. | 456.00 |
| V 76 | Supplying and wiring 2 x 16mm ² (7/.064") Cu/PVC/PVC cable + 16mm ² (7/.064") earth wire complete to working order excluding conduit/casing | L.ft. | 518.00 |
| V 77 | Supplying and wiring 4 x 16mm ² (7/0.064") Cu/PVC/PVC cable + 16mm ² (7/.064") earth wire complete to working order excluding conduit/casing | L.ft. | 831.00 |
| V 78 | Supplying and wiring 4 x 16mm ² (7/0.064") Cu/PVC/PVC cable complete to working order excluding conduit/casing | L.ft. | 678.00 |
| V 79 | Supplying and wiring 2 x 25mm ² Cu/PVC/PVC cable + 16 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 718.00 |
| V 80 | Supplying and wiring 4 x 25mm ² Cu/PVC/PVC cable + 16 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 1,211.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| V 81 | Supplying and wiring 4 x 25mm ² Cu/PVC/PVC cable complete to working order excluding conduit/casing. | L.ft. | 1,040.00 |
| V 82 | Supplying and wiring 4 x 35mm ² Cu/XLPE/PVC cable + 16 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 1,604.00 |
| V 83 | Supplying and wiring 4 x 35mm ² Cu/XLPE/PVC cable complete to working order excluding conduit/casing. | L.ft. | 1,467.00 |
| V 84 | Supplying and wiring 4 x 50mm ² Cu/XLPE/PVC cable + 25 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 2,140.00 |
| V 85 | Supplying and wiring 4 x 50mm ² Cu/XLPE/PVC cable complete to working order excluding conduit/casing. | L.ft. | 1,860.00 |
| V 86 | Supplying and wiring 4 x 70mm ² Cu/XLPE/PVC cable +35 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 3,625.00 |
| V 87 | Supplying and wiring 4 x 70mm ² Cu/XLPE/PVC cable complete to working order excluding conduit/casing. | L.ft. | 2,980.00 |
| V 88 | Supplying and wiring 4 x 95mm ² Cu/XLPE/PVC cable + 50 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 4,164.00 |
| V 89 | Supplying and wiring 4 x 95mm ² Cu/XLPE/PVC cable compete to working order excluding conduit/casing. | L.ft. | 3,726.00 |
| V 90 | Supplying and wiring 4 x 120mm ² Cu/XLPE/PVC cable + 70 mm ² earth wire complete to working order excluding conduit/casing. | L.ft. | 5,718.00 |
| V 91 | Supplying and wiring 4 x 120mm ² Cu/XLPE/PVC cable complete to working order excluding conduit/casing. | L.ft. | 5,073.00 |
| V 92 | Supplying and fixing 2 core flexible (0.5mm ²) . | L.ft. | 32.00 |
| V 93 | Supplying and wiring 2.5mm ² (7/.029") earth wire complete to working order excluding conduit/casing. | L.ft. | 39.00 |
| V 94 | Supplying and wiring 6 mm ² (7/.044") earth wire complete to working order excluding conduit/casing. | L.ft. | 71.00 |
| V 95 | Supplying and wiring 10 mm ² (7/.052") earth wire complete to working order excluding conduit/casing. | L.ft. | 106.00 |
| V 96 | Supplying and wiring 16 mm ² (7/.064") earth wire complete to working order excluding conduit/casing. | L.ft. | 155.00 |
| V 97 | Supplying and wiring 2.5mm ² (7/.029") Cu/PVC/PVC twin wire complete to working order excluding conduit/casing. | L.ft. | 81.00 |
| V 98 | Supplying and wiring with 4mm ² (7/.036") Cu/PVC/PVC twin wire complete to working order excluding conduit/casing. | L.ft. | 116.00 |
| V 99 | Supplying and wiring with 2 x 4mm ² (7/.036") Cu/PVC/PVC cable + 4mm ² (7/.036) earth wire complete to working order excluding conduit/casing. | L.ft. | 163.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| V 100 | Supplying and wiring with 4 x 4mm ² (7/.036") Cu/PVC/PVC cable + 4mm ² (7/.036) earth wire complete to working order excluding conduit/casing. | L.ft. | 255.00 |
| V 101 | Supplying and wiring with 4 x 2.5mm ² (7/.029") Cu/PVC/PVC cable + 2.5mm ² (7/.036) earth wire complete to working order excluding conduit/casing. | L.ft. | 176.00 |
| | <u>Arial Bundle Cable</u> | | |
| V 102 | Supplying and laying 3 x 35mm ² + N54.6 mm ² + 16 mm ² Arial Bundl Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 390.00 |
| V 103 | Supplying and laying 3 x 35mm ² + N54.6 mm ² Arial Bundle Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 373.00 |
| V 104 | Supplying and laying 3 x 50mm ² + N54.6 mm ² + 16 mm ² Arial Bundl Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 423.00 |
| V 105 | Supplying and laying 3 x 50mm ² + N54.6 mm ² Arial Bundle Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 406.00 |
| V 106 | Supplying and laying 3 x 70mm ² + N54.6 mm ² + 16 mm ² Arial Bundl Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 520.00 |
| V 107 | Supplying and laying 3 x 70mm ² + N54.6 mm ² Arial Bundle Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 503.00 |
| V 108 | Supplying and laying 3 x 120mm ² + N70 mm ² + 16 mm ² Arial Bundl Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 656.00 |
| V 109 | Supplying and laying 3 x 120mm ² + N70 mm ² Arial Bundle Cable (ABC) complete to working order excluding conduit/casing. | L.ft. | 640.00 |
| | <u>Service Drop Aluminium Cable</u> | | |
| V 110 | Supplying and laying 4 x 16 mm ² service drop aluminium cable complete to working order excluding conduit/casing. | L.ft. | 154.00 |
| V 111 | Supplying and laying 4 x 25 mm ² service drop aluminium cable complete to working order excluding conduit/casing. | L.ft. | 207.00 |
| | <u>AB Cable Accessories</u> | | |
| | Anchor bracket and clamp body are made of corrosion resistant extruded aluminium alloy, metal support is made of stainless steel, wedges are made of weather resistant and anti-UV material with high mechanical strength. | | |
| | Should comply with standard EN-50483-3 | | |
| V 112 | Supplying and installation of large angle assembly with anchor bracket including nut & bolts starting and end pole complete to working order. | Nr. | 6,429.00 |
| V 113 | Supplying and installation of dead end assembly with anchor bracket including nut & bolts starting and end pole complete to working order. | Nr. | 4,112.00 |
| V 114 | Supplying and installation of suspension assembly to support the cable over pole through nutral/ messenger wire complete to working order. | Nr. | 3,219.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| V 115 | Supplying and installation of piercing connector (95mm ²) for connecting AB cable & service drop alluminium cable complete to working order. | Nr. | 976.00 |
| V 116 | Supplying and installation of piercing connector (35mm ²) for connecting AB cable & service drop alluminium cable complete to working order. | Nr. | 750.00 |
| | <u>Stay cable installation</u> | | |
| V 117 | Supplying and installation of anchor stay including angled thimbleye bolt, nut and square washer for 5/8" stay hole 6" from top of the pole, insulator, stay cable, stay wrap, anchor rod, stay anchor with nut complete to working order. Necessary excavation and 2"x 2" x 5" thick Grade 20 concrete pad & guy cable to be paid seperately. All details as per as per Drawing No.ELEC/ST/05. | Nr. | 6,426.00 |
| V 118 | Supplying and installation of stay cable G.S. 7/3.25mm (Grade 700) in position complete to working order. | kg | 407.00 |
| | <u>Electricity transmission RC pole (Grade 40)</u> | | |
| V 119 | Suppling and Placing in position 8.3m long electricity transmission RC pole (Grade 40) including the cost of excavation and transport. | Nr. | 32,680.00 |
| V 120 | Suppling and Placing in position 7.6m long electricity transmission RC pole (Grade 40) including the cost of excavation and transport. | Nr. | 27,760.00 |
| | <u>uPVC conduit pipe</u> | | |
| V 121 | 3/4" - 1" PVC conduits laying in the slab including placing binding wire to draw through conduits. | L.ft. | 47.00 |
| V 122 | Supplying and fixing 3/4" uPVC conduit including clips. | L.ft. | 39.00 |
| V 123 | Supplying and fixing 1" uPVC conduit including clips. | L.ft. | 43.00 |
| V 124 | Supplying and fixing 1 1/4" dia. uPVC conduit pipe | L.ft. | 60.00 |
| V 125 | Supplying and fixing 1 1/2" dia. uPVC conduit pipe | L.ft. | 73.00 |
| V 126 | Supplying and fixing 2" dia. uPVC conduit pipe | L.ft. | 86.00 |
| V 127 | Supplying and fixing 3/4" dia. uPVC conduit bend | Nr. | 33.00 |
| V 128 | Supplying and fixing 1" dia. uPVC conduit bend | Nr. | 38.00 |
| V 129 | Supplying and fixing 1 1/4" dia. uPVC conduit bend | Nr. | 63.00 |
| V 130 | Supplying and fixing 1 1/2" dia. uPVC conduit bend | Nr. | 87.00 |
| V 131 | Supplying and fixing 2" dia. uPVC conduit bend | Nr. | 140.00 |
| V 132 | Supplying and fixing 3/4" or 1" uPVC conduit junction box. | Nr. | 90.00 |
| | <u>uPVC casing</u> | | |
| V 133 | Supplying and fixing 3/4" x 1/2" uPVC casing | L.ft. | 56.00 |
| V 134 | Supplying and fixing 1" x 5/8" uPVC casing | L.ft. | 60.00 |
| V 135 | Supplying and fixing 1 1/2" x 5/8" uPVC casing | L.ft. | 82.00 |
| V 136 | Supplying and fixing 1 1/2" x 1" uPVC casing | L.ft. | 86.00 |
| V 137 | Supplying and fixing 2" x 1" uPVC casing | L.ft. | 101.00 |
| V 138 | Supplying and fixing 2"x 2: box casing. uPVC casing | L.ft. | 153.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| V 139 | Supplying and fixing 3" x 2" uPVC casing | L.ft. | 192.00 |
| V 140 | Supplying and fixing 4" x 2" uPVC casing | L.ft. | 245.00 |
| | <u>Supply and installation of distribution board</u> | | |
| | <u>Plastic encloser</u> | | |
| V 141 | 1-4 ways SP&N or TP & N Distribution Board with thermo plastic frame and door, earth and neutral bars din rail type (protection rating IP40) | Nr. | 2,484.00 |
| V 142 | 8-10 ways SP&N or TP & N Distribution board with thermo plastic frame and door, earth and neutral bars din rail type (protection rating IP40) | Nr. | 2,640.00 |
| V 143 | 10-12 ways SP&N or TP & N Distribution board with thermo plastic frame and door, earth and neutral bars din rail type (protection rating IP40) | Nr. | 2,825.00 |
| V 144 | 12-14 ways SP&N or TP & N distribution board with thermo plastic frame and door, earth and neutral bars din rail type (protection rating IP40) | Nr. | 2,947.00 |
| V 145 | 14-16 ways SP&N or TP & N Distribution board with thermo plastic frame and door, earth and neutral bars din rail type (protection rating IP40) | Nr. | 3,834.00 |
| | <u>Steel Enclosure</u> | | |
| | Steel Enclosure with a)Material - Electro Zinc Coated Sheet Steel (1.0mm - 2.0 mm thick as applicable) b)Surface finished - Powder Coated c)Construction - Hinged door ,Rubber gasket, key lock, outing Plate, Gland Plate Protection - IP 54 | | |
| V 146 | Size -500mm(W) *250mm(H) * 125mm(D) - Single row 18 way | Nr. | 10,277.00 |
| V 147 | Size -500mm(W) *400mm(H) * 125mm(D) - Two row 18 way (each way) | Nr. | 14,535.00 |
| V 148 | Size -500mm(W) *700mm(H) * 150mm(D) - Two row + MCCB 18 way (each row) | Nr. | 22,586.00 |
| V 149 | Size -500mm(W) *600mm(H) * 125mm(D) - Three row 18 way (each row) | Nr. | 18,386.00 |
| V 150 | Size -500mm(W) *700mm(H) * 125mm(D) - Four row 18 way (each row) | Nr. | 23,111.00 |
| V 151 | Size -500mm(W) *850mm(H) * 150mm(D) - Three row + MCCB 18 way (each row) | Nr. | 27,719.00 |
| V 152 | Size -500mm(W) *1000mm(H) * 150mm(D) - Four row + MCCB 18 way (each row) | Nr. | 35,186.00 |
| | <u>Note:</u> | | |
| | Supply, install and wire the following items in the distribution board (Distribution board paid separately) | | |
| V 153 | 40Amp, 30 mA Double Pole ELCB (RCCB) | Nr. | 4,978.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| V 154 | 40Amp, 100 mA Double Pole ELCB (RCCB) | Nr. | 5,715.00 |
| V 155 | 40Amp, 300 mA Double Pole ELCB (RCCB) | Nr. | 5,817.00 |
| V 156 | 63Amp, 30 mA Double Pole ELCB (RCCB) | Nr. | 5,817.00 |
| V 157 | 63Amp, 100 mA Double Pole ELCB (RCCB) | Nr. | 5,941.00 |
| V 158 | 63Amp, 300 mA Double Pole ELCB (RCCB) | Nr. | 5,965.00 |
| V 159 | 40Amp, 30 mA Four Pole ELCB (RCCB) | Nr. | 7,642.00 |
| V 160 | 40Amp, 100 mA Four Pole ELCB (RCCB) | Nr. | 7,926.00 |
| V 161 | 40Amp, 300 mA Four Pole ELCB (RCCB) | Nr. | 8,083.00 |
| V 162 | 63Amp, 30 mA Four Pole ELCB (RCCB) | Nr. | 8,378.00 |
| V 163 | 63Amp, 100 mA Four Pole ELCB (RCCB) | Nr. | 8,378.00 |
| V 164 | 63Amp, 300 mA Four Pole ELCB (RCCB) | Nr. | 8,378.00 |
| V 165 | 100Amp, 300 mA Four Pole ELCB (RCCB) | Nr. | 12,175.00 |
| V 166 | MCCB metal enclosure. Steel Enclosure With a). Material - Electro Sink Coated Sheet Steel (1 - 1.6 mm thick) b). Surface finished - Powder Coated c). Construction - Hinged door, Rubber gasket, key lock, outing Plate, Gland Plate d). Protection - IP 54 e). Size - 250mm(W)X300mm(H)X150mm(D)(Size- approximate) | Nr. | 6,287.00 |
| V 167 | 30,40,60,100 Amp , 18KA Three Pole MCCB without metal enclosure. | Nr. | 9,878.00 |
| V 168 | 30,40,60,100 Amp , 18KA Four Pole MCCB without metal enclosure. | Nr. | 12,376.00 |
| V 169 | 125 Amp , 25KA Three Pole MCCB without metal enclosure. | Nr. | 15,940.00 |
| V 170 | 160 Amp , 25KA Three Pole MCCB without metal enclosure. | Nr. | 18,201.00 |
| V 171 | 250 Amp , 25KA Three Pole MCCB without metal enclosure. | Nr. | 22,706.00 |
| V 172 | 125 Amp , 25KA Four Pole MCCB without metal enclosure. | Nr. | 17,023.00 |
| V 173 | 160 Amp , 25KA Four Pole MCCB without metal enclosure. | Nr. | 19,698.00 |
| V 174 | 250 Amp , 25KA Four Pole MCCB without metal enclosure. | Nr. | 29,263.00 |
| V 175 | 6 - 25 Amp, 10KA Single Pole MCB | Nr. | 809.00 |
| V 176 | 32 Amp, 10KA Single Pole MCB | Nr. | 843.00 |
| V 177 | 40 Amp, 10KA Single Pole MCB | Nr. | 901.00 |
| V 178 | 63 Amp, 10KA Single Pole MCB | Nr. | 921.00 |
| V 179 | 6 - 25 Amp, 10KA Double Pole MCB | Nr. | 1,726.00 |
| V 180 | 32 Amp, 10KA Double Pole MCB | Nr. | 1,743.00 |
| V 181 | 40 Amp, 10KA Double Pole MCB | Nr. | 1,817.00 |
| V 182 | 63 Amp, 10KA Double Pole MCB | Nr. | 1,856.00 |
| V 183 | 6 - 32 Amp, 10KA Three Pole MCB | Nr. | 2,496.00 |
| V 184 | 40 Amp, 10KA Three Pole MCB | Nr. | 2,599.00 |
| V 185 | 63 Amp, 10KA Three Pole MCB | Nr. | 2,769.00 |
| V 186 | 6 - 25 Amp, 10KA Four Pole MCB | Nr. | 2,496.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| V 187 | 32 Amp, 10KA Four Pole MCB | Nr. | 2,530.00 |
| V 188 | 40 Amp, 10KA Four Pole MCB | Nr. | 3,675.00 |
| V 189 | 63 Amp, 10KA Four Pole MCB | Nr. | 3,788.00 |
| V 190 | 40 Amp Double Pole Isolator with plastic enclosure. | Nr. | 1,935.00 |
| V 191 | 63 Amp Double Pole Isolator with plastic enclosure. | Nr. | 2,262.00 |
| V 192 | 100 Amp Double Pole Isolator with plastic enclosure. | Nr. | 2,728.00 |
| V 193 | 40 Amp Three Pole Isolator with plastic enclosure. | Nr. | 2,961.00 |
| V 194 | 63 Amp Three Pole Isolator with plastic enclosure. | Nr. | 3,195.00 |
| V 195 | 100 Amp Three Pole Isolator with plastic enclosure. | Nr. | 3,254.00 |
| V 196 | 40 Amp Four Pole Isolator with plastic enclosure. | Nr. | 3,370.00 |
| V 197 | 63 Amp Four Pole Isolator with plastic enclosure. | Nr. | 3,720.00 |
| V 198 | 100 Amp Four Pole Isolator with plastic enclosure. | Nr. | 4,245.00 |
| | <u>LIGHT FITTINGS</u> | | |
| | <u>Note:</u> | | |
| | Rate for items V 198 - V 208 shall include the cost of adapter, connecting 2core 1mm² cable of length not exceeding 1.5m , galvanized hanging chain. (incase the cable length exceed 1.5m refer item V 66 for Payment of additional length.) | | |
| | <u>Note:</u> | | |
| | Lamp fitting shall include the cost of fitting and bulb & shall be given a two year Warranty and one year warranty for bulb. This rate for Items V 199- V 209. | | |
| | Lamp fitting with given a two year Warranty for fitting . | | |
| | <u>Supply & Install only the following fittings.</u> | | |
| V 199 | Inner diameter of 5" Ceiling recessed down light complete with 12w LED lamp. (Prime cost of the Ceiling recessed down light complete with 12w LED lamp is Rs.2200.00) | Nr. | 3,016.00 |
| V 200 | Inner diameter of 5" Ceiling mounted down light complete with 12w LED lamp. (Prime cost of the Ceiling mounted down light complete with 12w LED lamp is Rs.2900.00) | Nr. | 3,873.00 |
| V 201 | Inner diameter of 4" wall mounted cylindrical shaped upward light fitting with 18 watt LED bulb. (Prime cost of the wall mounted cylindrical shaped upward light fitting with 18 watt LED bulb is Rs.5900.00) | Nr. | 7,545.00 |
| V 202 | Inner diameter of 4" Weatherproof IP65 rated wall mounted cylindrical shaped upward light fitting with 18 watt LED bulb. (Prime cost of the Weatherproof IP65 rated wall mounted cylindrical shaped upward light fitting with 18 watt LED bulb is Rs.5900.00) | Nr. | 7,545.00 |
| V 203 | 8"dia. wall mounted clear transparent glass globe light fitting and bracket with 9 watt LED bulb. (Prime cost of the wall mounted clear transparent glass globe light fitting and bracket with 9 watt LED bulb is Rs.2900.00) | Nr. | 3,873.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| V 204 | Indoor type decorative black and gold type pendent lamp complete with 8/9w LED filament lamp. (Prime cost of the Indoor type decorative black and gold type pendent lamp complete with 8/9w LED filament lamp is Rs.8900.00) | Nr. | 11,217.00 |
| V 205 | Indoor type decorative black and gold type pendent lamp complete with 12w LED filament lamp. (Prime cost of the Indoor type decorative black and gold type pendent lamp complete with 8/9w LED filament lamp is Rs.10900.00) | Nr. | 13,665.00 |
| V 206 | Pendent type 12.5 watt LED bulb. (Prime cost of the 12.5 watt LED bulb is Rs.725.00) | Nr. | 1,341.00 |
| V 207 | Pendent type 20 watt CFL bulb. (Prime cost of the 20 watt CFL bulb is Rs.460.00) | Nr. | 1,007.00 |
| V 208 | IP65 weatherproof 50 watt LED Flood light. (Prime cost of the 50 watt LED Flood light is Rs.6800.00) | Nr. | 8,891.00 |
| V 209 | IP66 weatherproof 100 watt LED Flood light. (Prime cost of the 100 watt LED Flood light is Rs.11550.00) | Nr. | 14,876.00 |
| | Note: | | |
| | For items V 210 to V 226, the rate shall include the bulb lamp complete with the fitting. Bulbs make shall be - Philips, osram, nvc, greenlee & Orange. | | |
| V 210 | 4'-0" long 18 watt single fluorescent batton type T5 LED lamp fitting. (Prime cost of the 4'-0" long 18 watt single fluorescent batton type T5 LED lamp fitting is Rs.1250.00) | Nr. | 1,898.00 |
| V 211 | 2'-0" long 18 watt single fluorescent batton type T5 LED lamp fitting. (Prime cost of the 2'-0" long 18 watt single fluorescent batton type T5 LED lamp fitting is Rs.900.00) | Nr. | 1,457.00 |
| V 212 | 2'-0" x 2'-0" LED 24watt ceiling surface mounted panel light fitting - Square Type. (Prime cost of the 2'-0" x 2'-0" LED 24watt ceiling surface mounted panel light fitting - Square is Rs.2600.00) | Nr. | 3,599.00 |
| V 213 | 0'-9" x 0'-9" LED 18 watt ceiling surface mounted panel light fitting. - Square Type. (Prime cost of the 0'-9" x 0'-9" LED 18 watt ceiling surface mounted panel light fitting. - Square is Rs.1800.00) | Nr. | 2,591.00 |
| V 214 | 0'-7" x 0'-7" LED 12 watt ceiling surface mounted panel light fitting. - Square Type. (Prime cost of the 0'-7" x 0'-7" LED 12 watt ceiling surface mounted panel light fitting. - Square Type is Rs.1450.00) | Nr. | 2,150.00 |
| V 215 | 0'-5" x 0'-5" LED 6 watt ceiling surface mounted panel light fitting.- Square Type. (Prime cost of the 0'-5" x 0'-5" LED 6 watt ceiling surface mounted panel light fitting.- Square Type is Rs.950.00) | Nr. | 1,520.00 |
| V 216 | 0'-9" dia. LED 18 watt ceiling surface mounted panel light fitting.- Circuler Type. (Prime cost of the 0'-9" dia. LED 18 watt ceiling surface mounted panel light fitting.- Circuler Type is Rs.1800.00) | Nr. | 2,591.00 |
| V 217 | 0'-7" dia. LED 12 watt Ceiling Surface Mounted Panel Light fitting. - Circuler Type. (Prime cost of the 0'-7" dia. LED 12 watt Ceiling Surface Mounted Panel Light fitting. - Circuler Type is Rs.1450.00) | Nr. | 2,150.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| V 218 | 0'-5" dia. LED 6 watt ceiling surface mounted panel light fitting. - Circuler Type. (Prime cost of the 0'-5" dia. LED 6 watt ceiling surface mounted panel light fitting. - Circuler Type is Rs.950.00) | Nr. | 1,520.00 |
| V 219 | 2'-0" x 2'-0' LED 40 watt ceiling recessed mounted panel light fitting. - Square Type. (Prime cost of the 2'-0" x 2'-0' LED 40 watt ceiling recessed mounted panel light fitting. - Square Type is Rs.7450.00) | Nr. | 9,710.00 |
| V 220 | 2'-0" x 2'-0' LED 24 watt ceiling recessed mounted panel light fitting. - Square Type. (Prime cost of the 2'-0" x 2'-0' LED 24 watt ceiling recessed mounted panel light fitting. - Square Type is Rs.2200.00) | Nr. | 3,095.00 |
| V 221 | 0'-9" x 0'-9" LED 18 watt ceiling recessed mounted panel light fitting. - Square Type. (Prime cost of the 0'-9" x 0'-9" LED 18 watt ceiling recessed mounted panel light fitting. - Square Type is Rs.1500.00) | Nr. | 2,213.00 |
| V 222 | 0'-7" x 0'-7" LED 12 watt ceiling recessed mounted panel light fitting. - Square Type. (Prime cost of the 0'-7" x 0'-7" LED 12 watt ceiling recessed mounted panel light fitting. - Square Type is Rs.1200.00) | Nr. | 1,835.00 |
| V 223 | 0'-5' x 0'-5" LED 6 watt ceiling recessed mounted panel light fitting. - Square Type. (Prime cost of the 0'-5' x 0'-5" LED 6 watt ceiling recessed mounted panel light fitting. - Square Type is Rs.775.00) | Nr. | 1,299.00 |
| V 224 | 0'-9" dia, LED 18 watt ceiling recessed mounted panel light fitting. - Circuler Type (Prime cost of the 0'-9" dia, LED 18 watt ceiling recessed mounted panel light fitting. - Circuler Type is Rs.1500.00) | Nr. | 2,213.00 |
| V 225 | 0'-7" dia. LED 12 watt ceiling recessed mounted panel light fitting. - Circuler Type (Prime cost of the 0'-7" dia. LED 12 watt ceiling recessed mounted panel light fitting. - Circuler Type is Rs.1200.00) | Nr. | 1,835.00 |
| V 226 | 0'-5" dia. LED 6 watt ceiling recessed mounted panel light fitting. - Circuler Type (Prime cost of the 0'-5" dia. LED 6 watt ceiling recessed mounted panel light fitting. - Circuler Type is Rs.775.00) | Nr. | 1,299.00 |
| | <u>Street Light Lamp Post</u> | | |
| V 227 | Supply,install, commissioning and maintenance of an Individual solar powered 20 w LED single arm street light including following items and as aestechically suited to required locations such as car park areas, seating areas, etc. of the site as directed by the Divisional Engineer - pole height of street light 6m as per Drawing No.ELEC/ST/01 and specifications (post, lamp, panel, charge controller and battery bank) (Prime cost of an Individual solar powered 20 w LED single arm street light is Rs.152778.00) | No | 183,334.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|---------|----------------|
| V 228 | Supply, install, commissioning and maintenance of an Individual solar powered 20 w LED double arm street Light including following items and as aestechically suited to required locations such as car park areas, seating areas, etc. of the site as directed by the Divisional Engineer - pole height of street light 6m as per Drawing No.ELEC/ST/02 and specifications (post, lamp, panel, charge controller and battery bank) (Prime cost of an Individual solar powered 20 w LED double arm street Light is Rs.162038.00) | No | 194,445.00 |
| | Select either item V 229 or else item V 230 in combination with appropriate number of item V 231. Item V 232 meant for high current capacity main panel board. | | |
| V 229 | Provide an earth electrode copper plate 2'-0" x 2'-0" x 3mm thick at 2.0m depth including excavation and backfilling. Rate shall include connection to the main panel, sub main, earth clips, wall plug, screws, & etc. with 1'-0" x 1'-0" x 1'-0" earth pit consist of 4 1/2" brick work , 3" thick Grade 20 concrete cover slab as per Drawing no. ELE/ST/04 .(Earth wire paid separately) | Item | 37,029.00 |
| V 230 | Provide an earth electrode 6'-0" long , 2" dia. x 2.3 mm thick GI pipe. Rate shall include connection to the main panel, sub main, earth clips& etc. with 1'-0" x 1'-0" x 1'-0" earth pit consist of 4 1/2" brick work , 3" thick Grade 20 concrete cover slab as per drawing no. ELE/ST/03. (Earth wire paid separately) | Item | 6,369.00 |
| V 231 | Provide an earth electrode 5'-0" long , 16 mm dia. copper bonded solid steel rod (coating thickness 25 Micron) Rate shall include connection to the main panel, sub main, earth clips & etc as per Drawing no. ELE/ST/04 . (Earth wire paid separately) | Nr. | 1,629.00 |
| V 232 | Supply , Installation and connection of 25 x 3mm copper tape with cupper cad weldingnecessary accessories. Rate shall include for connection of both ends with brass. | L.ft. | 519.00 |
| V 233 | Supply and install D'Bracket (small size) | Nr. | 729.00 |
| V 234 | Supply and install complete "D" shape bracket including insulator, Nuts, bolts ect. fixed to working order. | Per Set | 1,107.00 |
| V 235 | Supply and install 50mm x 50mm x 6mm "L" Iron, including drilling 12mm holes, 10mm G.I. bolt, and application of two coats anticorrosive paint all complete to working order. | L.ft. | 342.00 |
| | <u>Supplying and installation of locable bus bar box</u> | | |
| | Locable bus bar box with a). Material - Electro Zinc Coated Sheet Steel (1.0mm - 2.0 mm thick as applicable) b). Surface finished - Powder Coated c). Construction - Hinged door ,Rubber gasket, key lock, outing Plate, Gland Plate d). Protection - IP 54 | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| V 236 | Supply , installation and connection of 32A - 100A three phase with powder coated locable bus bar box including 4 pole copper bar and earth bar. | Nr. | 9,038.00 |
| V 237 | Supply , installation and connection of 100A - 125A three phase with powder coated locable bus bar box including 4 pole copper bar and earth bar. | Nr. | 12,849.00 |
| V 238 | Supply , installation and connection of 0A - 60A single phase with powder coated locable bus bar box including 2 pole copper bar and earth bar. | Nr. | 7,986.00 |
| V 239 | Testing of the electrical installation and submission of certificate from a chartered Electrical Engineer registered at CEB. | | |
| a) | For Building Floor Area Less than 2500 Sq. ft. | Item | 10,500.00 |
| b) | For Building Floor Area between 2500 - 5000 Sq. ft. | Item | 23,100.00 |
| c) | For Building Floor Area between 5000 - 10000 Sq. ft. | Item | 44,100.00 |
| d) | For Building Floor Area more than 10000 Sq. ft. | Item | 68,250.00 |
| | <u>Miscellaneous</u> | | |
| V 240 | Supply & replacing one gang one way switch without wiring including removing old one. | Nr. | 268.00 |
| V 241 | Supply & replacing two gang one way switch without wiring. Rate including removing old one. | Nr. | 462.00 |
| V 242 | Supply & replacing three gang one way switch without wiring. Rate including removing old one. | Nr. | 621.00 |
| V 243 | Supply & replacing four gang one way switch without wiring. Rate including removing old one. | Nr. | 768.00 |
| V 244 | Supply & replacing five gang one way switch without wiring. Rate including removing old one. | Nr. | 921.00 |
| V 245 | Supply & replacing 13 Amp. Switch socket outlet (max. 6 A) without wiring. Rate including removing old one. | Nr. | 659.00 |
| V 246 | Supply & replacing 13 Amp. Switch socket outlet without wiring. Rate including removing old one. | Nr. | 659.00 |
| | <u>W - METAL WORK</u> | | |
| | <u>Note:</u> | | |
| | Aluminium doors, windows and partitions shall confirm to the following requirements: | | |
| 1 | Aluminium alloy should confirm to- ISO - 9001:2008, SLS 1410:2011 / SLS 1411:2011 | | |
| 2 | Anodized coating thickness should be 25 ± 5 microns | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| 3 | Aluminium extrusions available in the Local Market are being either manufactured in Sri Lanka or imported material. Due to the continuous change of the extrusion profiles and thicknesses from time to time, it has become very difficult to specify standard section sizes that are to be used for door /window frames and sash members. Hence the rates given herein are based on the recommended minimum sizes and thicknesses of profiles published by leading Aluminium profile manufacturers (Alumex Plc, Swisstek Aluminium Limited) as at present for the doors, windows, fanlights and partitions. | | |
| 4 | At the time of bidding, all the Bidders shall specifically be requested to submit the following information. | | |
| (a) | The specifications and thickness of Aluminium extrusions bidder proposes to use on the works. | | |
| (b) | Full size cross sections of profiles. | | |
| (c) | Documentary evidence from the Profile Manufacture to the effect that the proposed profile will serve for the intended purpose. | | |
| (d) | A Manufacturer's test certificate be produced as evidence that the powder coating is of required thickness. | | |
| 5 | Physical properties :- | | |
| | (a) Minimum tensile strength 150 Mpa | | |
| | (b) Elongation 7% | | |
| 6 | All screws should be stainless steel | | |
| 7 | But hinges and bar type hinges should be Aluminium or Stainless Steel. | | |
| 8 | The item descriptions should be read along with the annexed detail drawings. Drawing no:- AR/TYPE PLAN/DOORS & WINDOWS/2020/DETAIL 1 - 21 (Sheet 1 - 21) | | |
| | The over-all profile dimensions used in deriving B.S.R. rates for main members of each component are as follows. Doors - openable - 100mm x 1.5mm thick, Doors -sliding - 80mm x 1.5mm thick, 70mm x 1.3mm thick Windows - Casement - 70mm x 1.5 mm thick, Windows - Sliding -80mm x 1.5 mm thick, Fan Light - 70mm x 1.5mm thick, Partition - 76mm x 1.2mm thick Shop drawings should be submitted to the Divisional Engineer prior to fabrication. | | |
| 9 | The rates shall include Neoprene gasket, pop rivets, Rawl plugs, Screws, Aluminium cleats etc. | | |
| 10 | The rates given herein are for Natural aluminium profiles. | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| 11 | For powder coated aluminium profiles (minimum powder coating thickness of 60 ± 5 microns) the respective item rate shall be increased by 15%. | | |
| 12 | For Bronze anodized aluminium profiles, the respective item rate shall be increased by 5%. | | |
| 13 | When clear glass to be replaced with Tinted glass, the respective item rate shall be increased by 2%. | | |
| 14 | When openable door sashes are to be fitted with floor mounted hinged, deduct 5% from the respective item rate to account for omission of hinges. Add new items for Floor hinge & Door closer to be paid separately as per items W 75, W 76, W 77 & W 78. | | |
| | <u>Doors</u> | | |
| W 01 | <u>Openable Single Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side on bottom & Glazed Panel on top) with Louvers on Top</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and louvers on top , panelling with Polyester coated aluminium composite panel of 0.2mm thick aluminium sheets both sides of total thickness 4mm, at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 02 - D1 | Sq.ft. | 2,817.00 |
| W 02 | <u>Openable Single Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side on bottom & Glazed Panel on top) with Fixed Glass on Top</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and fixed glass on top , panelling with Polyester coated aluminium composite panel of 0.2mm thick aluminium sheets both sides of total thickness 4mm, at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 02 - D2 | Sq.ft. | 2,459.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 03 | <u>Openable Single Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side on bottom & Glazed Panel on top)</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail , panelling with Polyester coated aluminium composite panel of 0.2mm thick aluminium sheets both sides of total thickness 4mm at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 02 - D3 | Sq.ft. | 2,287.00 |
| W 04 | <u>Openable Single Sash Door (Fully Glazed) with Louvers on Top</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and louvers on top , glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 03 - D4 | Sq.ft. | 2,511.00 |
| W 05 | <u>Openable Single Sash Door (Fully Glazed) with Fixed Glass on Top</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and fixed glass on top , glazed with 5mm thick clear glass panes at top and bottom panel , neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 03 - D5 | Sq.ft. | 2,191.00 |
| W 06 | <u>Openable Single Sash Door (Fully Glazed)</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 03 - D6 | Sq.ft. | 2,201.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 07 | <u>Openable Single Sash Door (Fully panelled with Polyester coated 4mm thick Aluminium Composite Panel both side)</u> | | |
| | Natural aluminium single sash butt hinged openable door with middle rail and fully panelling with Polyester coated aluminium composite panel of 0.2mm thick aluminium sheets both sides of total thickness 4mm at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 04 - D7&D8 | Sq.ft. | 2,349.00 |
| W 08 | <u>Sliding Single Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side on bottom & Glazed Panel on top)</u> | | |
| | Natural aluminium single sash sliding door with middle rail , panelling with Polyester coated aluminium composite panel of 0.2mm thick aluminium sheets both sides of total thickness 4mm at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut roller, flush bolt and approved quality lock , door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 05 - D9 | Sq.ft. | 1,750.00 |
| W 09 | <u>Sliding Single Sash Door (Fully Glazed)</u> | | |
| | Natural aluminium single sash fully glazed sliding door with middle rail , glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut roller, flush bolt and approved quality lock , door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 05 - D10 | Sq.ft. | 1,711.00 |
| W 10 | <u>Sliding Single Sash Door (Fully panelled with Polyester coated 4mm thick Aluminium Composite Panel both side)</u> | | |
| | Natural aluminium single sash sliding door with middle rail , fully panelling with panelling with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut roller, flush bolt and approved quality lock , door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 05 - D11 | Sq.ft. | 1,917.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 11 | <u>Openable Double Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side & Glazed Panel) with Fixed Glass on Top</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail and fixed glass on top , panelling with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 06 - D12 | Sq.ft. | 2,314.00 |
| W 12 | <u>Openable Double Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side & Glazed Panel) with Louvers on Top</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail and louvers on top , panelling with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 06 - D13 | Sq.ft. | 2,670.00 |
| W 13 | <u>Openable Double Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side & Glazed Panel)</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail , panelling with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick and glazed with 5mm thick clear glass panes at top panel, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 06 - D14 | Sq.ft. | 2,576.00 |
| W 14 | <u>Openable Double Sash Door (Fully Glazed) with Fixed Glass on Top</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail and fixed glass on top , fully glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2019.03.18/ DETAIL 07 - D15 | Sq.ft. | 2,297.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 15 | <u>Openable Double Sash Door (Fully Glazed) with Louvers on Top</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail and louvers on top , fully glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/DETAIL 07 - D16 | Sq.ft. | 2,537.00 |
| W 16 | <u>Openable double Sash Door (Fully Glazed)</u> | | |
| | Natural aluminium double sash butt hinged openable door with middle rail and fully glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/DETAIL 07 - D17 | Sq.ft. | 2,410.00 |
| W 17 | <u>Sliding Double Sash Door (Polyester coated 4mm thick Aluminium Composite Panel both side & Glazed Panel)</u> | | |
| | Natural aluminium double sash sliding door with middle rail , panelling with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick at bottom panel and glazed with 5mm thick clear glass panes at top panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut roller, flush bolt and approved quality lock , door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/DETAIL 08 - D18 | Sq.ft. | 1,889.00 |
| W 18 | <u>Sliding Double Sash Door (Fully Glazed) with Fixed Glass on Top</u> | | |
| | Natural aluminium double sash fully glazed sliding door with middle rail , fully glazed with 5mm thick clear glass panes at top and bottom panel, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut roller, flush bolt and approved quality lock , door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/DETAIL 08 - D19 | Sq.ft. | 1,818.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 19 | <u>Openable Single Sash Door for Toilets (Fully panelled with 3mm thick Aluminium Composite Panel with both sides Polyester coated aluminium sheets of 0.2mm thick) (50mm x 25mm box bar of 0.9 mm thick outer frame & mid rail)</u> | | |
| | 50 x 25mm 0.9mm thick natural aluminium box bar door frame with door stopper and single sash butt hinged openable door with 50 x 26 Aluminium door section outer rail and middle rail panelling with Polyester coated aluminium composite panel of 0.12 mm thick aluminium sheets both sides of total thickness 3mm at top and bottom panel , rubber beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut and . As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 04 - D20 | Sq.ft. | 1,448.00 |
| | <u>Windows</u> | | |
| W 20 | <u>Casement Window with Louvers on Top (1 Bay)</u> | | |
| | Natural aluminium casement window single sash with louvers on top, consisting of 5mm thick clear glass panes, casement lock, pull rings , screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/DETAIL 09 - W1 | Sq.ft. | 2,603.00 |
| W 21 | <u>Casement Window with Fixed Glass on Top (1 Bay)</u> | | |
| | Natural aluminium casement window single sash with fixed glass on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 09 - W2 | Sq.ft. | 2,286.00 |
| W 22 | <u>Casement Window (1 Bay)</u> | | |
| | Natural aluminium casement window single sash , consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/ DOORS & WINDOWS/2020/DETAIL 09 - W3 | Sq.ft. | 2,419.00 |
| W 23 | <u>Casement Window with Louvers on Top (2 Bays)</u> | | |
| | Natural aluminium casement window double sash with louvers on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/ DOORS & WINDOWS/2020/ DETAIL 10 - W4 | Sq.ft. | 2,394.00 |
| W 24 | <u>Casement Window with Fixed Glass on Top (2 Bays)</u> | | |
| | Natural aluminium casement window double sash with fixed glass on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/ DOORS & WINDOWS/2020/ DETAIL 10 - W5 | Sq.ft. | 2,135.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 25 | <u>Casement Window (2 Bays)</u> | | |
| | Natural aluminium casement window double sash , consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/ DOORS & WINDOWS/2020/ DETAIL 10 - W6 | Sq.ft. | 2,270.00 |
| W 26 | <u>Sliding Window with Louvers on Top (2 Bays)</u> | | |
| | Natural aluminium sliding window with louvers on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 11 - W7 | Sq.ft. | 3,151.00 |
| W 27 | <u>Sliding Window with Fixed Glass on Top (2 Bays)</u> | | |
| | Natural aluminium sliding window with fixed glass on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 11 - W8 | Sq.ft. | 2,078.00 |
| W 28 | <u>Sliding Window (2 Bays)</u> | | |
| | Natural aluminium sliding window ,consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/ DOORS & WINDOWS/ 2020/ DETAIL 11 - W9 | Sq.ft. | 1,916.00 |
| W 29 | <u>Casement Window with Louvers on Top (3 Bays)</u> | | |
| | Natural aluminium casement window with louvers on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 12 - W10 | Sq.ft. | 2,290.00 |
| W 30 | <u>Casement Window with Fixed Glass on Top (3 Bays)</u> | | |
| | Natural aluminium casement window with fixed glass on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 12 - W11 | Sq.ft. | 2,056.00 |
| W 31 | <u>Casement Window (3 Bays)</u> | | |
| | Natural aluminium casement window, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 12 - W12 | Sq.ft. | 2,196.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 32 | <u>Sliding Window with Louvers on Top (3 Bays)</u> | | |
| | Natural aluminium sliding window with louvers on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 13 - W13 | Sq.ft. | 2,185.00 |
| W 33 | <u>Sliding Window with Fixed Glass on Top (3 Bays)</u> | | |
| | Natural aluminium sliding window with fixed glass on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 13 - W14 | Sq.ft. | 2,011.00 |
| W 34 | <u>Sliding Window (3 Bays)</u> | | |
| | Natural aluminium sliding window ,consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 13 - W15 | Sq.ft. | 1,961.00 |
| W 35 | <u>Top Hung Casement Window with Fixed Louvers on Top & Fixed Glass at Bottom (3 Bays)</u> | | |
| | Natural aluminium top hung casement window with fixed glass on top and fixed glass at bottom, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 14 - W16 | Sq.ft. | 3,837.00 |
| W 36 | <u>Top Hung Casement Window with Fixed Louvers on Top & Fixed Glass at Bottom (2 Bays)</u> | | |
| | Natural aluminium top hung casement window with fixed glass on top and fixed glass at bottom, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 14 - W17 | Sq.ft. | 3,945.00 |
| W 37 | <u>Casement Window with Louvers on Top (4 Bays)</u> | | |
| | Natural aluminium casement window with louvers on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 15 - W18 | Sq.ft. | 2,077.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 38 | <u>Casement Window with Fixed Glass on Top (4 Bays)</u> | | |
| | Natural aluminium casement window with fixed glass on top, consisting of 5mm thick clear glass panes, casement lock, screws, pop rivots, gaskets, hinges, weather strip etc.As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 15 - W19 | Sq.ft. | 1,711.00 |
| W 39 | <u>Sliding Window with Louvers on Top (4 Bays)</u> | | |
| | Natural aluminium sliding window with louvers on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 16 - W20. | Sq.ft. | 1,813.00 |
| W 40 | <u>Sliding Window with fixed glass on Top (4 Bays)</u> | | |
| | Natural aluminium sliding window with fixed glass on top consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 16 - W21. | Sq.ft. | 1,615.00 |
| W 41 | <u>Sliding Window (4 Bays)</u> | | |
| | Natural aluminium sliding window consisting of 5mm thick clear glass panes , lock, roller, screws, gaskets, nut felt, pop rivots, cap, plastic guide etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 16 - W22. | Sq.ft. | 1,579.00 |
| W 42 | <u>Louver Panel 1</u> | | |
| | Natural aluminium framed lovers, consisting of screws, pop rivots, etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 17 - W23 | Sq.ft. | 2,358.00 |
| W 43 | <u>Louver Panel 2</u> | | |
| | Natural aluminium framed lovers, consisting of screws, pop rivots, etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 17 - W24 | Sq.ft. | 2,277.00 |
| W 44 | <u>Fixed Glazed Window</u> | | |
| | Natural aluminium fixed glazed window with 5mm thick clear glass and screws, pop rivots, gasket and wool felt etc. and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 18 - FG1 | Sq.ft. | 2,157.00 |
| W 45 | <u>Top Hung Fanlight with Louver panel on top</u> | | |
| | Natural aluminium top hung type fanlight with louver on top consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 19 - FL1 | Sq.ft. | 2,999.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 46 | <u>Top Hung Fanlight with Fixed Glass on top</u> | | |
| | Natural aluminium top hung type fanlight with fixed glass on top consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 19 - FL2 | Sq.ft. | 2,592.00 |
| W 47 | <u>Centre Pivot Fanlight with Louver panel on top</u> | | |
| | Natural aluminium centre pivot type fanlight with louver on top consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 19 - FL3 | Sq.ft. | 3,224.00 |
| W 48 | <u>Centre Pivot with Fixed Glass on top</u> | | |
| | Natural aluminium centre pivot type fanlight with fixed glass on top consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 19 - FL4 | Sq.ft. | 2,817.00 |
| W 49 | <u>Top Hung Fanlight (3 bays)</u> | | |
| | Natural aluminium top hung type fanlight 3 bays, consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 20 - FL5 | Sq.ft. | 1,572.00 |
| W 50 | <u>Top Hung Fanlight (2 Bays + 1 Bay)</u> | | |
| | Natural aluminium top hung type fanlight 2 bays + 1 bay, consisting of locks, screws, pop rivots, gaskets, hinges, weather strip etc. As per the members , sizes and details given in Drawing No:- AR/ TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 20 - FL6 | Sq.ft. | 1,214.00 |
| | <u>Partitions</u> | | |
| W 51 | <u>Fully Board Partition with Plywood board (PVC)</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, top portion is panelled with 2.5mm thick PVC plywood board upto 900mm height and bottom portion is panelled with 2.5mm thick PVC plywood board, upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally , natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 01 | Sq.ft. | 449.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 52 | Fully Board Partition with Melamine MDF | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, top portion is panelled with 5 mm thick Melamine MDF board upto 900mm height and bottom portion is panelled with 5 mm thick Melamine MDF board, upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally , natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 01 | Sq.ft. | 537.00 |
| W 53 | Full Board Partition with Polyester coated 4mm thick Aluminium Composite Panel both side | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, top portion is panelled with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick, upto 900mm height and bottom portion is panelled with aluminium composite panel of total thickness 4mm with 2 nos.of Polyester coated aluminium sheets of 0.2mm thick composite upto 1200mm height, completed with board joints taped with necessary pop rivots, gasket & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 02 | Sq.ft. | 819.00 |
| | Glazed & Board Partition with 2.5mm Plywood (PVC) & 5mm thick clear glass panes | | |
| W 54 | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, top portion is panelled with 5mm thick clear glass plane upto 900mm height and bottom portion is panelled with 2.5mm thick PVC plywood board, upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally , natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 02 | Sq.ft. | 544.00 |
| W 55 | 76 x 1.2mm thick natural aluminium partition frame, panelled three portions, top portion is panelled with 5mm thick clear glass plane upto beam or slab bottom level height and middle portion is panelled with 5mm thick clear glass plane upto 900mm height, bottom portion is panelled with 2.5mm thick PVC plywood board upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally , natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 03 | Sq.ft. | 503.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 56 | <u>Glazed & Polyester coated Aluminium Composite Panel Partition with Polyester coated 4mm thick Aluminium Composite Panel both side & 5mm thick clear glass panes</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, bottom portion is panelled with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick, upto 1200mm height and top portion is panelled with 5mm thick clear glass upto 900mm height in partitioning including with necessary pop rivots, gasket & etc. work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 03 | Sq.ft. | 682.00 |
| W 57 | <u>Full Board Partition with Gypsum board</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, bottom portion is panelled with 9mm thick gypsum board upto 1200mm height and top portion is panelled with 9mm thick gypsum board upto 900mm height kept back to back in partitioning including suitable size of GI channel frame work with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally, natural aluminium skirting, glue & etc. work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 04 | Sq.ft. | 620.00 |
| W 58 | <u>Full Board Partition with veneered plywood board.</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, bottom portion is panelled with 7.5mm thick veneered plywood board (2.5mm thick veneer board + 5mm thick plywood board composite) upto 1200mm height and top portion is panelled with 7.5mm thick veneered plywood board (2.5mm thick veneer board + 5mm thick plywood board composite) upto 900mm height kept back to back in partitioning including suitable size of GI channel frame work with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally, natural aluminium skirting, glue & etc. work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 04 | Sq.ft. | 683.00 |
| W 59 | <u>Glazed & 6mm thick cement board partition</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, top portion is panelled with 5mm thick clear glass plane upto 900mm height and bottom portion is panelled with 6mm thick Cement board upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally , natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 05 (Painting of cement board is to be paid seperately) | Sq.ft. | 556.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 60 | <u>Glazed & 6mm thick cement board partition</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled three portions, top portion is panelled with 5mm thick clear glass plane upto beam or slab bottom level height and middle portion is panelled with 5mm thick clear glass plane upto 900mm height, bottom portion is panelled with 6mm thick Cement board upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally ,, natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 05 (Painting of cement board is to be paid seperately) | Sq.ft. | 537.00 |
| W 61 | <u>6mm thick cement full board partition</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled two portions, bottom portion is panelled with 6mm thick Cement board upto 1200mm height and top portion is panelled with 6mm thick Cement board upto 900mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally ,, natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 06 . (Painting of cement board is to be paid seperately) | Sq.ft. | 474.00 |
| W 62 | <u>6mm thick cement full board partition</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled three portions, top portion is panelled with 6mm thick Cement board upto beam or slab bottom level height and middle portion is panelled with 6mm thick Cement board upto 900mm height, bottom portion is panelled with 6mm thick Cement board upto 1200mm height, two boards in both sides of GI channel completed with board joints taped with necessary pop rivots, gasket and suitable size of GI channels at 600mm c/c horizontally ,, natural aluminium skirting & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 06 (Painting of cement board is to be paid seperately) | Sq.ft. | 434.00 |
| W 63 | <u>5mm thick full glazed partition</u> | | |
| | 76 x 1.2mm thick natural aluminium partition frame, panelled three portions, top portion is panelled with 5mm thick clear glass plane upto beam or slab bottom level height and middle portion is panelled with 5mm thick clear glass plane upto 900mm height, bottom portion is panelled with 5mm thick clear glass plane upto 1200mm height completed with board joints taped with necessary pop rivots, gasket & etc. and work complete in order and details given in Drawing No:- AR/ TYPE PLAN/PARTITIONS/2020/ DETAIL 07 | Sq.ft. | 621.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| | <u>Partition Doors</u> | | |
| | <u>TYPE-I - Partition Door Fully Panelled with Plywood (PVC) (two sheets kept back to back)</u> | | |
| W 64 | 76 x 1.2mm thick & 100 x 1.6mm Natural aluminium single sash butt hinged openable door with middle rail and fully panelled with 2.5mm thick PVC plywood board, two boards kept back to back (Total thickness is 5mm) , neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 21 - D21 | Sq.ft. | 1,703.00 |
| W 65 | 80 x 1.5mm natural aluminium single sash sliding door with middle rail and fully panelled with 2.5mm thick PVC plywood board, two boards kept back to back, (Total thickness is 5mm) neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut, flush bolts, rollers and approved quality lock, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 21 - D22 | Sq.ft. | 1,624.00 |
| | <u>TYPE-II - Partition Door Panelled with one part glazing and other part with plywood board (PVC) (two sheets kept back to back)</u> | | |
| W 66 | 76 x 1.2mm thick & 100 x 1.6mm thick natural aluminium single sash butt hinged openable door with middle rail one part panelled with 2.5mm thick PVC plywood, two boards kept back to back, (Total thickness is 5mm) and other part glazed with 5mm thick clear glass panes, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 21 - D23 | Sq.ft. | 1,735.00 |
| W 67 | 80 x 1.5mm natural aluminium single sash sliding door with middle rail, one part panelled with 2.5mm thick PVC plywood, two boards kept back to back, (Total thickness is 5mm) and other part panelled with 5mm thick clear glass panes, neoprene and wooleed beading, gaskets, pop rivots, threaded bar with nut, flush bolts, rollers and approved quality lock, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 21 - D24 | Sq.ft. | 1,655.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| | <u>TYPE-III - Partition Door Panelled with one part glazing and other part with cement board (two sheets kept back to back)</u> | | |
| W 68 | 76 x 1.2mm thick & 100 x 1.6mm Natural aluminium single sash butt hinged openable door with middle rail one part panelled with 6 mm thick single side cement fibre board, two panels kept back to back and other part glazed with 5mm thick clear glass panes, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 22 - D25 (Painting of cement board is to be paid seperately) | Sq.ft. | 1,780.00 |
| W 69 | 80 x 1.5mm thick Natural aluminium single sash sliding door with middle rail, one part panelled with 6 mm thick single side cement fibre board, two panels kept back to back and other part panelled with 5mm thick clear glass panes, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut, flush bolts, rollers and approved quality lock, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 22 - D26 (Painting of cement board is to be paid seperately) | Sq.ft. | 1,675.00 |
| | <u>TYPE-V - Partition Door Fully Panelled with cement board (two sheets kept back to back)</u> | | |
| W 70 | 76 x 1.2mm thick & 100 x 1.6mm Natural aluminium single sash butt hinged openable door with middle rail and fully panelled with 6mm thick cement board, two boards kept back to back (Total thickness is 12mm) , neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 21 - D27 (Painting of cement board is to be paid seperately) | Sq.ft. | 1,745.00 |
| W 71 | 80 x 1.5mm natural aluminium single sash sliding door with middle rail and fully panelled with 6mm thick cement board, two boards kept back to back (Total thickness is 12mm) neoprene and woold beading, gaskets, pop rivots, threaded bar with nut, flush bolts, rollers and approved quality lock, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 21 - D28 (Painting of cement board is to be paid seperately) | Sq.ft. | 1,666.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| | <u>TYPE-IV - Partition Door Panelled with one part glazing and Polyester coated 4mm thick Aluminium Composite Panel both side</u> | | |
| W 72 | 76 x 1.2mm thick & 100 x 1.6mm thick Natural aluminium single sash butt hinged openable door with middle rail one part panelled with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick, and other part glazed with 5mm thick clear glass panes, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut and approved quality lock, butt hinges, door handle with cap nut. As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/DOORS & WINDOWS/2020/ DETAIL 22 - D29 | Sq.ft. | 1,887.00 |
| W 73 | 80 x 1.5mm thick Natural aluminium single sash sliding door with middle rail, one part panelled with aluminium composite panel of total thickness 4mm, with both sides Polyester coated aluminium sheets of 0.2mm thick, and other part panelled with 5mm thick clear glass panes, neoprene and woold beading, gaskets, pop rivots, threaded bar with nut, flush bolts, rollers and approved quality lock, door handle with cap nut. As per the members , sizes and details given in Drawing No:-AR/TYPE PLAN/DOORS & WINDOWS/ 2020/ DETAIL 22 - D30 | Sq.ft. | 1,807.00 |
| | <u>Door Pull Handle</u> | | |
| W 74 | Supplying and fixing Handle Pair I type "Magnum" Brand & model no "2512I" handle 300 mm long stainless steel door pull handle fixed complete to working order. | Nr. | 8,614.00 |
| | <u>Floor Hinge</u> | | |
| W 75 | Supplying & fixing stainless steel floor hinge of "Union Brand" & model no. - 203E or approved equivalent. Weight of sash upto 65 kg. | Nr. | 28,152.00 |
| W 76 | Supplying & fixing stainless steel floor hinge of "Union Brand" & model no. - 203E or approved equivalent. Weight of sash between 60-85 kg. | Nr. | 29,151.00 |
| | <u>Door closer</u> | | |
| W 77 | Supplying & fixing surface mounted door closer of "Union Brand" & Model no. - N8803 or approved equivalent. Weight of sash upto 60 kg. | Nr. | 8,333.00 |
| W 78 | Supplying & fixing surface mounted door closer of "Union Brand" & Model no. - 88234 or approved equivalent. Weight of upto 80 kg. | Nr. | 9,294.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| | Iron Grill | | |
| W 79 | Supply , fabrication and installation of welded Diamond shaped Iron grill, consisting 20mm x 6mm thick flat iron frame and 5mm dia M.S. rods at 3" centers to form 3" x 6" diamond shape grill. Rate shall include for fixing to the wall rawl plugs and brass screws. Rate Shall include for applying two coats of anti-corrosive paint and spray painting two coats of enamel paints. (Based on 2'-0"x4'-0" area) Details as per the Drawing No:-AR/TYPE PLAN/IRON GRILL/ 2020/DETAIL 01/TYPE 01 | Sq.ft. | 489.00 |
| W 80 | Supply , fabrication and installation of welded Diamond shaped iron grill, consisting 20mm x 6mm thick flat iron frame with 2Nos. mid rails without intermediate joints, 5mm dia. M.S. rods welded to form 3" x 6" diamond shaped isolated panels. Rate shall include for fixing to the wall rawl plugs and brass screws. Rate Shall include for applying two coats of anti-corrosive paint and spray painting two coats of enamel paints. (Based on 9'-0"x6'-0" area) Details as per the Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/DETAIL 01/TYPE 02 | Sq.ft. | 455.00 |
| W 81 | Supply , fabrication and installation of welded openable Iron grill door window including the door frame fabricated with 38mm x 38mm x 6mm thick angle iron to an over-all size of 3'-0" x 9'-0" high inclusive of 2'-3" high Iron grill on top formed with 5mm dia. m.s.rods welded to form 3" x 6" diamond shape. Door sash outer frame fabricated with 25mm x 25mm x 3mm thick bottom hollow sections and two cross members, top part of the sash fixed with 5mm dia. m.s.rods welded to form 3" x 6" diamond shape and bottom part fixed with gauge 22 G.I. sheet, sash fixed to the frame with 3 No. 4" x 3" M.S. butt hinges and locking arrangement comprising of a Iron tower bolt and Hasp & plate. The fixed window grill fabricated with 20mm x 6mm thick flat iron outer frame and two mullions, 5mm dia. m.s.rods welded to form 3" x 6" diamond shape, All details as per Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/DETAIL 01/TYPE 03 . Rate shall include the formation of 9" x 9" x 6" holes to insert the door frame legs filled with grade 20 concrete , spray painting of two coats of anti-corrosive paint and spray painting two coats of enamel paints and fixing to the wall rawl plugs and brass screws. | Sq.ft. | 552.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 82 | Supply , fabrication and installation of welded openable Iron grill door without window. The door frame fabricated with 38mm x 38mm x 6mm thick angle iron to an over-all size of 3'-0" x 9'-0" high inclusive of 2'-3" high Iron grill on top formed with 5mm dia. m.s.rods welded to form 3" x 6" diamond shape. Door sash outer frame fabricated with 25mm x 25mm x 3mm thick bottom hollow sections and two cross members, top part of the sash fixed with 5mm dia. m.s.rods welded to form 3" x 6" diamond shape and bottom part fixed with gauge 22 G.I. sheet, sash fixed to the frame with 3 No. 4" x 3" M.S. butt hinges and locking arrangement comprising of a Iron tower bolt and Hasp & plate. All details as per Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/DETAIL 01/TYPE 04. Rate shall include the formation of 9" x 9" x 6" holes to insert the door frame legs filled with grade 20 concrete , spray painting of two coats of anti-corrosive paint and spray painting two coats of enamel paints and fixing to the wall rawl plugs and brass screws. | Sq.ft. | 621.00 |
| W 83 | Welded Iron grill of rectangular pattern , consisting of a flat Iron frame of 25mm x 6mm thick with out intermediate joints, 2 nos of 25mm x 6mm thick horizontal members , 12mm dia. M.S. round bars as vertical members @ 4" c/c , vertical round bars to be drilled through horizontal flat Irons, fixed complete with counter sunk screws and rawl plugs to the masonry opening or timber. Rate shall include for spray painting of two coats of anti-corrosive paint and spray painting two coats of enamel paints. (for window openings of size 2'-0" x 4'-0"). Details as per the Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/ DETAIL 02. | Sq.ft. | 461.00 |
| | <u>Iron Grill for Sliding Window</u> | | |
| W 84 | Supply, fabrication and installation of welded Diamond shaped Iron grill for sliding window (2 Bay) , overall size (4'-0" x 5'-6")consisting of 20mm x 6mm thick flat iron frame with middle slit 6" high and grided with 5mm dia M.S. rods at 3" centers to form 3" x 6" diamond shape. Rate shall include for fixing to the wall rawl plugs and brass screws. Rate Shall include for applying two coats of anti-corrosive paint and spray painting two coats of enamel paints. Details as per the Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/ DETAIL 03 - TYPE 01 | Sq.ft. | 562.00 |
| W 85 | Supply, fabrication and installation of welded Diamond shaped Iron grill for sliding window (3 Bay) , overall size (6'-0" x 5'-6")consisting of 20mm x 6mm thick flat iron frame with middle slit 6" high and grided with 5mm dia M.S. rods at 3" centers to form 3" x 6" diamond shape. Rate Shall include for applying two coats of anti-corrosive paint and spray painting two coats of enamel paints. Details as per the Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/ DETAIL 03 - TYPE 02 | Sq.ft. | 542.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|--------|----------------|
| W 86 | Supply, fabrication and installation of welded Diamond shaped Iron grill for sliding window (4 Bay) , overall size (8'-0" x 5'-6")consisting of 20mm x 6mm thick flat iron frame with middle slit 6" high and grilled with 5mm dia M.S. rods at 3" centers to form 3" x 6" diamond shape. Rate shall include for fixing to the wall rawl plugs and brass screws. Rate Shall include for applying two coats of anti-corrosive paint and spray painting two coats of enamel paints. Details as per the Drawing No:- AR/TYPE PLAN/IRON GRILL/ 2020/DETAIL 03 - TYPE 03 | Sq.ft. | 540.00 |
| | <u>Aluminium Grill</u> | | |
| | Aluminium grill work should be included in the estimates where the proposed buildings are situated in marine environment. This should be decided by the Divisional Engineer. | | |
| W 87 | Supply , fabrication and installation of honey comb shaped aluminium mesh framed with 19mmx 19mm x 0.9mm thick aluminium angle frame by pop rivert and fixed to the timber opening using brass or stainless steel screws. (Based on 2'-0" x 4'-0" area) Details as per the Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/DETAIL 04 - TYPE 01. | Sq.ft. | 458.00 |
| W 88 | Supply , fabrication and installation of honey comb shaped aluminium mesh framed with 19mmx 19mm x 0.9mm thick aluminium angle and fixed with 50mm x 50mm x 1.2mm thick aluminium box bar to the wall consisting of pop rivert, brass screws, rawl plugs and etc. (Based on 9'-0"x 6'-0" area) Details as per the Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/DETAIL 04 - TYPE 02. | Sq.ft. | 662.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 89 | Supply, fabrication and installation of openable aluminium door window, window consisting of honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed with 50mm x 50mm x 1.2mm thick aluminium box bar to the wall and door frame fabricated with 50mm x 50mm x 1.2mm thick aluminium box bar to an over-all size of 3'-0" x 9'-0" high inclusive of 2'-3" high aluminium grill on top framed with 19mm x 19mm x 0.9mm thick aluminium angle fixed to the 50mm x 50mm x 1.2mm thick aluminium box bar and Single sash butt hinged openable door sash panelled three portion, bottom and middle portion panelling gauge 22 G.I. sheet and top portion panelling honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed with 50mm x 50mm x 1.2mm thick aluminium box bar consisting of pop rivert, brass screws, rawl plugs and etc. , Sash fixed to the frame with 3 No. 4" x 3" butt hinges, inc. door stopper and locking arrangement comprising of a Iron tower bolt and Hasp & plate. Rate shall include the formation of 9" x 9" x 6" holes to insert the door frame legs filled with grade 20 concrete. All details as per Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/DETAIL 04 - TYPE 03. | Sq.ft. | 939.00 |
| W 90 | Supply, fabrication and installation of openable aluminium door, door frame fabricated with 50mm x 50mm x 1.2mm thick aluminium box bar to an over-all size of 3'-0" x 9'-0" high inclusive of 2'-3" high aluminium grill on top framed with 19mm x 19mm x 0.9mm thick aluminium angle fixed to the 50mm x 50mm x 1.2mm thick aluminium box bar and Single sash butt hinged openable door sash panelled three portion, bottom and middle portion panelling gauge 22 G.I. sheet and top portion panelling honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed with 50mm x 50mm x 1.2mm thick aluminium box bar consisting of pop rivert, brass screws, rawl plugs and etc. ,Sash fixed to the frame with 3 No. 4" x 3" butt hinges, inc. door stopper and locking arrangement comprising of a Iron tower bolt and Hasp & plate. Rate shall include the formation of 9" x 9" x 6" holes to insert the door frame legs filled with grade 20 concrete. All details as per Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/DETAIL 04 - TYPE 04. | Sq.ft. | 1,069.00 |
| | <u>Aluminium Grill for Sliding Window</u> | | |
| W 91 | Supply, fabrication and installation of aluminium grill for sliding window (2 Bay), framed with overall size (4'-0" x 5'-6") with middle slit 6" high framed with 50mm x 50mm x 1.2mm thick aluminium box bar covered by honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed to the wall consisting of pop rivert, brass screws, rawl plugs and etc. All details as per Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/ DETAIL 05 - TYPE 01. | Sq.ft. | 1,198.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| W 92 | Supply, fabrication and installation of aluminium grill for sliding window (3 Bay), framed with overall size (6'-0" x 5'-6") with middle slit 6" high framed with 50mm x 50mm x 1.2mm thick aluminium box bar covered by honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed to the wall consisting of pop rivert, brass screws, rawl plugs and etc. All details as per Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/ DETAIL 05 - TYPE 02. | Sq.ft. | 1,018.00 |
| W 93 | Supply, fabrication and installation of aluminium grill for sliding window (4 Bay), framed with overall size (8'-0" x 5'-6") with middle slit 6" high framed with 50mm x 50mm x 1.2mm thick aluminium box bar covered by honey comb shaped aluminium mesh framed with 19mm x 19mm x 0.9mm thick aluminium angle and fixed to the wall consisting of pop rivert, brass screws, rawl plugs and etc. All details as per Drawing No:- AR/TYPE PLAN/ALUMINIUM GRILL/ 2020/ DETAIL 05 - TYPE 03. | Sq.ft. | 1,012.00 |
| | <u>COLLAPSIBLE DOOR</u> | | |
| W 94 | Fabricating and Installation of open type collapsible Iron door consisting with 20mm x 6mm flat iron codling cover and necessary screws, etc.. Rate shall include for applying two coats of anti-corrosive paint. | Sq.ft. | 1,566.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| | <u>ROLLER DOORS</u> | | |
| W 95 | Supply and fixing powder coated zinc aluminium roller door thickness of 0.6mm, center bar, pulleys, side plate with the racers, fabricating the mechanical box with M.S. square tubes and covering the box and fixing on site with the bottom bars and necessary U channels, nylon strips, etc. (Approx. Size: 10'-6" width x 9'-8" high) | Sq.ft. | 946.00 |
| W 96 | Supply and fixing the motor with two remotes for the roller door. | Item | 42,000.00 |
| | <u>Hand Rail</u> | | |
| | <u>G.I Tube Hand Rail</u> | | |
| W 97 | Supplying, fabricating & fixing GI tube hand rail, consisting of 2" x 1.6mm thick dia. GI tube as hand rail and 1 1/2" dia. x 1.6mm thick GI tube @ 4' c/c as vertical members fixed top end weld to 2" dia. x 1.6mm thick GI tube and fixed bottom end to brick/concrete wall with the 3" x 3" x 12mm thick M.S. plate connecting with 4 nos of 10mm anchor bolts, work complete in order. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint. All sizes and details as per Drawing No:- AR/TYPE PLAN/HAND RAIL/ 2020/ DETAIL 01. | L.ft. | 1,107.00 |
| | <u>G.I Box Bar Staircase Hand Rail</u> | | |
| W 98 | Supplying, fabricating & fixing G.I box bar stair case hand rail consist of 2"x2"x1.6mm thick G.I box bar upright @ 4' c/c as vertical members fixed bottom end to steps with the 4"x4"x12mm thick M.S. plate connecting with 4 nos of 10mm dia.anchor bolts and top end weld to 2"x2"x1.6mm thick G.I box bar , 3/4"x3/4"x1.6mm thick G.I box bar @ 6" c/c as vertical intermediate members top end weld to 2"x2"x1.6mm thick G.I box bar and bottom end weld to 2"x1"x1.6mm thick G.I box bar finished smooth and work complete in order. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint All sizes & details as per Drawing No:- AR/TYPE PLAN/HAND RAIL/ 2020/ DETAIL 02. | L.ft. | 2,462.00 |
| W 99 | Supplying, fabricating & fixing G.I box bar stair sase hand rail consist of 2"x2"x1.6mm thick G.I box bar upright @ 4' c/c as vertical members fixed bottom end to steps with the 4"x4"x12mm thick M.S. plate connecting with 4 nos of 10mm dia.anchor bolts and both end weld to 2"x2"x1.6mm thick G.I box bar, 3/4"x3/4"x1.6mm thick G.I box bar @ 6" c/c as vertical members both ends weld to 1 1/2"x1 1/2"x1.6mm thick G.I box bar finished smooth and work complete in order. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint. All sizes & details as per Drawing No:- AR/TYPE PLAN/HAND RAIL/ 2020/ DETAIL 03. | L.ft. | 2,916.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| W 100 | Supplying, fabricating & fixing G.I box bar guard wall hand rail consist of 1 1/2"x1 1/2"x1.6mm thick G.I box bar upright @ 4' c/c as vertical members fixed bottom end to brick/concrete wall with the 4"x4"x12mm thick M.S. plate connecting with 4 nos of 10mm dia.anchor bolts and top end weld to 2"x2"x1.6mm thick G.I box bar , 3/4"x3/4"x1.6mm thick G.I box bar @ 6" c/c as vertical members top end weld to 2"x2"x1.6mm thick G.I box bar and bottom end weld to 1"x1"x1.6mm thick G.I box bar finished smooth and work complete in order. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint. All sizes & details as per Drawing No:- AR/TYPE PLAN/HAND RAIL/ 2020/ DETAIL 04. | L.ft. | 1,534.00 |
| | <u>Sand Blasting Sticker</u> | | |
| W 101 | Supplying & fixing of Guage 100 Microns sand blasting sticker including surface preparation as per working order. | sq.ft | 113.00 |
| | <u>Y - STRUCTURAL STEEL WORK</u> | | |
| Y 01 | Supplying and fixing 50mm x 50mm x 6mm thick angle iron purlin at maximum spacing of 4'-0" centers upto maximum span of 10'-0" for a cement fibre roof . Rate shall include nuts, necessary bolts & washers etc , hoisting and placing in positionand application of two coats of zinc phosphate paint. | L.ft. | 314.00 |
| Y 02 | Supplying and fixing 65mm x 65mm x 6mm thick angle iron purlin at maximum spacing of 4'-0" centers maximum span of 11'-0" (not less than 10'-0") for a cement fibre roof . Rate shall include for necessary nuts, bolts & washers,etc. hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 387.00 |
| Y 03 | Supplying and fixing 75mm x 75mm x 6mm thick angle iron purlin at maximum spacing of 4'-0" centers maximum span of 12'-0" (not less than 11'-0") for a cement fibre roof. Rate shall include necessary nuts, bolts & washers etc, hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 470.00 |
| Y 04 | Supplying and fixing 100mm x 50mm x 6mm thick channel Iron purlin up to 14'-0" span at 4'-0" c/c . Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 702.00 |
| Y 05 | Supplying and fixing 125mm x 65mm x 6mm thick channel Iron purlin up to 16'-0" span at 4'-0" c/c. Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 905.00 |
| Y 06 | Supplying and fixing 150mm x 75mm x 6mm thick channel Iron purlin up to 18'-0" span at 4'-0" c/c. Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 1,086.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| Y 07 | Supply, installation and fixing of angle iron sleepers over the walls to support purlins formed with 50mm x 50mm x 6mm thick angles welded back to back with 75mm x 50mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 01 . Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 1,127.00 |
| Y 08 | Supply, installation and fixing of angle iron sleepers over the walls to support purlins formed with 65mm x 65mm x 6mm thick angles welded back to back with 75mm x 65mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 02 . Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 1,286.00 |
| Y 09 | Supply, installation and fixing of angle iron sleepers over the walls to support purlins formed with 75mm x 75mm x 6mm thick angles welded back to back with 75mm x 75mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 03 . Rate shall include for hoisting and placing in position and application of two coats of zinc phosphate paint. | L.ft. | 1,468.00 |
| | <u>Mild steel Roof truss</u> | | |
| Y 10 | Mild steel Roof truss for Calicut tile roofing 20'-0" (6.0m) span centre to centre, Maximum spacing 10'-0" , 25 ⁰ pitch maximum and 18 ⁰ pitch minimum. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 01 . Rate shall include for fabricating , transporting , hoisting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 77,342.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| Y 11 | Mild steel Roof truss for cement fibre roofing 20'-0" (6.0m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:-ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 02 . Rate shall include for fabricating , transporting , hoisting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 73,659.00 |
| Y 12 | Mild steel Roof truss for Calicut tile roofing 25'-0" (7.5m) span centre to centre, Maximum spacing 10'-0", 25° pitch maximum and 18° pitch minimum. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 03 . Rate shall include for fabricating , transporting , hoisting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 88,018.00 |
| Y 13 | Mild steel Roof truss for cement fibre roofing 25'-0" (7.5m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:-ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 04 . Rate shall include for fabricating , transporting , hoisting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 82,013.00 |
| Y 14 | Mild steel Roof truss for Calicut tile roofing 30'-0" (9.0m) span centre to centre , Maximum spacing 10'-0", 25° pitch maximum and 18° pitch minimum. Consisting of 2 Nos. 65mm x 65mm x 6mm thick angles as top and bottom chords, 2 Nos. 50mm x 50mm x 6mm thick angles as struts , 1 No. 65mm x 65mm x 6mm thick angles as ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 05 . Rate shall include for fabricating , transporting , hoisting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 117,033.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| Y 15 | Mild steel Roof truss for cement fibre roofing 30'-0" (9.0m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum, with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 65mm x 65mm x 6mm thick angles as top and bottom chords, 2 Nos. 50mm x 50mm x 6mm thick angles as struts, 1 No. 65mm x 65mm x 6mm thick angles as ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 06 . Rate shall include for fabricating, transporting, hoisting, fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 106,991.00 |
| | From first floor, hoisting & placing in position paid separately under item no. Y 59 (from Y 16 to Y 30 items) | | |
| Y 16 | Supplying and fixing 50mm x 50mm x 6mm thick angle iron purling at maximum spacing of 4'-0" centers upto maximum span of 10'-0" for a cement fibre roof. Rate shall include nuts, necessary bolts & washers etc and application of two coats of Zinc Phosphate paint. | L.ft. | 312.00 |
| Y 17 | Supplying and fixing 63mm x 63mm x 6mm thick angle iron purling at maximum spacing of 4'-0" centers maximum span of 11'-0" (not less than 10'-0") for a cement fibre roof. Rate shall include for necessary nuts, bolts & washers, etc. and application of two coats of Zinc Phosphate paint. | L.ft. | 385.00 |
| Y 18 | Supplying and fixing 75mm x 75mm x 6mm thick angle iron purling at maximum spacing of 4'-0" centers maximum span of 12'-0" (not less than 11'-0") for a cement fibre roof. Rate shall include necessary nuts, bolts & washers etc, and application of two coats of Zinc Phosphate paint. | L.ft. | 468.00 |
| Y 19 | Supplying and fixing 100mm x 50mm x 6mm thick channel Iron purling up to 14'-0" span at 4'-0" c/c. Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 700.00 |
| Y 20 | Supplying and fixing 125mm x 65mm x 6mm thick channel Iron purling up to 16'-0" span at 4'-0" c/c. Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 903.00 |
| Y 21 | Supplying and fixing 150mm x 75mm x 6mm thick channel Iron purling up to 18'-0" span at 4'-0" c/c. Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 1,083.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| Y 22 | Supply and fixing of angle iron sleepers over the walls to support purlins formed with 50mm x 50mm x 6mm thick angles welded back to back with 75mm x 50mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 01 . Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 1,112.00 |
| Y 23 | Supply and fixing of angle iron sleepers over the walls to support purlins formed with 65mm x 65mm x 6mm thick angles welded back to back with 75mm x 65mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 02 . Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 1,271.00 |
| Y 24 | Supply and fixing of angle iron sleepers over the walls to support purlins formed with 75mm x 75mm x 6mm thick angles welded back to back with 75mm x 75mm x 10mm thick separators @ 2'-0" c/c, fixed to the concrete pad laid on the wall with 2 nos 16 mm dia. rod and 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/SLEEPER/2020/DETAIL 03 . Rate shall include for application of two coats of Zinc Phosphate paint. | L.ft. | 1,454.00 |
| | <u>Mild steel Roof truss</u> | | |
| Y 25 | Mild steel Roof truss for Calicut tile roofing 20'-0" (6.0m) span centre to centre, Maximum spacing 10'-0" , 25 ⁰ pitch maximum and 18 ⁰ pitch minimum. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 01 . Rate shall include for fabricating , transporting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 75,005.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| Y 26 | Mild steel Roof truss for cement fibre roofing 20'-0" (6.0m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:-ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 02 . Rate shall include for fabricating , transporting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 71,322.00 |
| Y 27 | Mild steel Roof truss for Calicut tile roofing 25'-0" (7.5m) span centre to centre, Maximum spacing 10'-0", 25° pitch maximum and 18° pitch minimum. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 03 . Rate shall include for fabricating , transporting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 85,025.00 |
| Y 28 | Mild steel Roof truss for cement fibre roofing 25'-0" (7.5m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 50mm x 50mm x 6mm thick angles as top and bottom chords, 1 No. 50mm x 50mm x 6mm thick angles as struts & ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:-ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 04 . Rate shall include for fabricating , transporting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 79,092.00 |
| Y 29 | Mild steel Roof truss for Calicut tile roofing 30'-0" (9.0m) span centre to centre , Maximum spacing 10'-0", 25° pitch maximum and 18° pitch minimum. Consisting of 2 Nos. 65mm x 65mm x 6mm thick angles as top and bottom chords, 2 Nos. 50mm x 50mm x 6mm thick angles as struts , 1 No. 65mm x 65mm x 6mm thick angles as ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 05 . Rate shall include for fabricating , transporting , fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 113,527.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| Y 30 | Mild steel Roof truss for cement fibre roofing 30'-0" (9.0m) span centre to centre, Maximum spacing 10'-0", 18° pitch maximum and 12° pitch minimum, with 4'-0" wide eaves at both sides. Consisting of 2 Nos. 65mm x 65mm x 6mm thick angles as top and bottom chords, 2 Nos. 50mm x 50mm x 6mm thick angles as struts, 1 No. 65mm x 65mm x 6mm thick angles as ties, 10mm thick gusset plates, base plates & sole plates, mild steel rag bolts, 12" long 75 x 75 x 6 mm purling cleats, etc.. & all details as per the Drawing No:- ST/TYPE PLAN/ROOF TRUSS/2020/DETAIL 06 . Rate shall include for fabricating, transporting, fixing in position and application of two coats of Zinc Phosphate paint. | Nr. | 104,716.00 |
| | <u>Zinc Alum Roofing & Sandwich Panel Roofing</u> | | |
| | Zinc Aluminium Coated Profiled Steel Sheets | | |
| | Note - | | |
| | 1. Work shall be done in accordance with specifications for electrical and mechanical works - ICTAD Publication No.SCA/8 of Aug.2000(2nd Edition -Revised) | | |
| | 2.Material shall be done in accordance with BS 2989:1992 or with BS EN 10147:1992 or ASTM A792M. | | |
| | 3. Coating mass is AZ150 (Min. 150 gms/sq.m total on both sides) zinc alum profile roofing sheet. | | |
| | 4. The nominal base metal thickness should be 0.42 mm and total coated thickness(TCT) not less than 0.47mm, HI-Tensile steel with min. 550 Mpa yield strength, metallic hot dip coated Aluminium-Zinc alloy (55% Aluminium, 43.5% Zinc,1.5% Silicon). | | |
| | 5. The minimum rib size is 28mm. | | |
| | 6.The sheeting shall be fixed to timber purlins using compatible self-drilling hexagon washer head tap screws with neoprene washer & to steel purlins using compatible self drill thread forming nominal 40 µm Zinc coated or 25 µm zinc-tin alloy coated, hexagon washer head screw with EPDM washer. | | |
| | 7. Fasteners shall be fixed on each rib on purlins at top, bottom & laps of sheets, and on every other rib on intermediate purlins. The fastener size shall be calculated as per the design or manufacturer's recommendations. | | |
| | 8.Glamet G5 A40 roofing double skin with zinc aluminium coated metal panel insulated with polyurethane (PU) rigid foam for pitched roof with a minimum slope of 7%. Top sheet should be 0.47mm thick (colour) & bottom sheet should be 0.35mm thick (colour). | | |
| | 9.Insulated material is Polyurethane (PU) of density of 40kg/m3 | | |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| | 10.If PU thickness change, the length of screws should be increased. | | |
| | <u>Non-Colour</u> | | |
| Y 31 | Supply and fix zinc alum profile roofing sheet, laid on existing purlings with joints to be properly connected with an adequate side lap to ensure water tightness along the entire length and complete to working order. | Sqr. | 18,032.00 |
| Y 32 | Supplying and fixing zinc aluminium standard ridge or gable cap (Girth 470mm) using 10 x 16 mm self drilling fasteners at 190mm c/c to existing sheet & work complete in order. | Sqr. | 419.00 |
| Y 33 | Supplying and fixing Zinc alum flashing to wall & existing sheet using 10 x 16 mm self drilling fasteners at 380mm c/c & work complete in order. | L.ft. | 387.00 |
| Y 34 | Supplying and fixing Zinc alum Valley gutter of girth 470mm using 10 x 16 mm self drilling fasteners at 190mm c/c to existing sheet & work complete in order. | L.ft. | 384.00 |
| Y 35 | Supply and fix proprietary coated zincalum gutter size - Girth 470 complete with stop end plates, pop rivot, etc. All joints to be properly connected with an adequate laps not less than 150mm length and with sealant to ensure water tightness along the entire length of the gutter and including compatible galvanized gutter brackets at 450mm centers with an adequate slope as directed and fix in position. | L.ft. | 470.00 |
| Y 36 | Supply and fix proprietary coated zincalum gutter size - Girth 660 complete with stop end plates, pop rivot, etc. All joints to be properly connected with an adequate laps not less than 150mm length and with sealant to ensure water tightness along the entire length of the gutter and including compatible galvanized gutter brackets at 450mm centers with an adequate slope as directed and fix in position and subject to specific approval by the Divisional Engineer. | L.ft. | 710.00 |
| Y 37 | Supply and fix proprietary coated zincalum square down pipe size 100 x 100mm compatible for girth 470mm gutter complete with necessary nozzle , offset, 30' degree bend down pipes, shoe, down pipe bracket, etc. . All joints to be properly connected and with sealant to ensure water tightness along the entire length. Down pipe brackets @ 1.0 m c/c . | L.ft. | 409.00 |
| Y 38 | Supply and fix proprietary coated zincalum square down pipe size 150 x 150mm compatible for girth 660mm gutter complete with necessary nozzle , offset, 30' degree bend down pipes, shoe, down pipe bracket, etc. . All joints to be properly connected and with sealant to ensure water tightness along the entire length. Down pipe brackets @ 1.0 m c/c . | L.ft. | 580.00 |
| Y 39 | Supply and fixing 0.47 mm zinc alum valance board 313 mm girth with 20mm x 5 mm x 12" long flat iron bracket 2'-0" c/c and complete to working order. Rate shall include for scaffolding. | L.ft. | 285.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| | <u>Colour</u> | | |
| Y 40 | Supply and fix zinc alum profile roofing colour sheet, laid on existing purlings with joints to be properly connected with an adequate side lap to ensure water tightness along the entire length and complete to working order. | Sqr. | 20,915.00 |
| Y 41 | Supplying & fixing 30mm thick of PU Zinc Aluminium roofing sandwich panel "Glamet" or approved equivalent laid on existing purlings with joints to be properly connected with an adequate side lap to ensure water tightness along the entire length and complete to working order as per manufacture's specifications. | Sqr. | 63,848.00 |
| Y 42 | Supplying and fixing zinc aluminium standard Colour ridge cap or gable cap (Girth 470mm) using 10 x 16 mm self drilling fasteners at 190mm c/c to existing sheet & work complete in order. . | L.ft. | 449.00 |
| Y 43 | Supplying and fixing Zinc alum colour flashing to wall & existing sheet using 10 x 16 mm self drilling fasteners at 380mm c/c & work complete in order. | L.ft. | 419.00 |
| Y 44 | Supplying and fixing Zinc alum colour Valley gutter of girth 470mm using 10 x 16 mm self drilling fasteners at 190mm c/c to existing sheet & work complete in order. | L.ft. | 417.00 |
| Y 45 | Supply and fix proprietary coated zincalum colour gutter size - Girth 470 complete with stop end plates, pop rivot, etc. All joints to be properly connected with an adequate laps not less than 150mm length and with sealant to ensure water tightness along the entire length of the gutter and including compatible galvanized gutter brackets at 450mm centers with an adequate slope as directed and fix in position. | L.ft. | 507.00 |
| Y 46 | Supply and fix proprietary coated zincalum colour gutter size - Girth 660 complete with stop end plates, pop rivot, etc. All joints to be properly connected with an adequate laps not less than 150mm length and with sealant to ensure water tightness along the entire length of the gutter and including compatible galvanized gutter brackets at 450mm centers with an adequate slope as directed and fix in position and subject to specific approval by the Divisional Engineer. | L.ft. | 785.00 |
| Y 47 | Supply and fix proprietary coated zincalum colour square down pipe size 100 x 100mm compatible for girth 470mm gutter complete with necessary nozzle , offset, 30' degree bend down pipes, shoe, down pipe bracket, etc. . All joints to be properly connected and with sealant to ensure water tightness along the entire length. Down pipe brackets @ 1.0 m c/c . | L.ft. | 458.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| Y 48 | Supply and fix proprietary coated zincalume colour square down pipe size 150 x 150mm compatible for girth 660mm gutter complete with necessary nozzle , offset, 30' degree bend down pipes, shoe, down pipe bracket, etc. . All joints to be properly connected and with sealant to ensure water tightness along the entire length. Down pipe brackets @ 1.0 m c/c . | L.ft. | 627.00 |
| Y 49 | Supply and fix open groove type PvdF coated Aluminium Composite wall cladding of 4mm thickness with both sides PvdF coated aluminium sheets of 0.4mm thick including bronze anodised aluminium inner frame work to vertical walls up to 30'-0". As per the members , sizes and details given in Drawing No:- AR/TYPE PLAN/CLADDING/ 2019.03.18. Rate shall include for scaffolding. | Sq.ft. | 747.00 |
| Y 50 | Supply and fixing 0.47 mm zinc alum colour valance board 313 mm girth with 20mm x 5 mm x 12" long flat iron bracket 2'-0" c/c and complete to working order. Rate shall include for scaffolding. | L.ft. | 310.00 |
| Y 51 | Supply and lay 3 way reinforced double sided aluminium foil heat reflecting material to underside of roof, supported with Gauge 17, 3" x 3" GI mesh and complete to working order. Rate shall include for scaffolding. | Sqr. | 4,033.00 |
| | High tensile Galvanized iron "C" channels | | |
| | Note - | | |
| | 1. Work shall be done in accordance with specifications for electrical and mechanical works - ICTAD Publication No.SCA/8 of Aug.2000(2nd Edition -Revised) | | |
| | 2. Material shall be done in accordance with Standard AS 1397 and Material Tolerance Standard AS 1365. | | |
| | 3. Coating mass is Z275 (Min. 275gms/sq.m total on both sides) | | |
| | 4. Minimum yield strength 450 Mpa, Hot Dipped, Zinc coated & Chromate Passivated. | | |
| Y 52 | Supply and fixing high tensile Galvanized iron "C" channels of 100 x 50 x 14.5 x 2.0mm thick. Rate shall include hoisting. | L.ft. | 472.00 |
| Y 53 | Supply and fixing high tensile Galvanized iron "C" channels of 150 x 65 x 17.5 x 2.0mm thick. Rate shall include hoisting. | L.ft. | 602.00 |
| Y 54 | Supply and fixing high tensile Galvanized iron "C" channels of 200 x 75 x 20 x 2.0mm thick. Rate shall include hoisting. | L.ft. | 698.00 |
| | From first floor, hoisting & placing paid separately under item No. Y 59 (from Y 55 to Y 59 items) | | |
| Y 55 | Supply and fixing high tensile Galvanized iron "C" channels of 100 x 50 x 14.5 x 2.0mm thick | L.ft. | 461.00 |
| Y 56 | Supply and fixing high tensile Galvanized iron "C" channels of 150 x 65 x 17.5 x 2.0mm thick | L.ft. | 590.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------------|----------------|
| Y 57 | Supply and fixing high tensile Galvanized iron "C" channels of 200 x 75 x 20 x 2.0mm thick | L.ft. | 687.00 |
| | <u>Steel Scaffolding Set</u> | | |
| Y 58 | Supplying and erecting steel scaffolding sets. Rate to include for dismantling same after completion of work. | Set per day | 114.00 |
| | <u>Hoisting & Placing</u> | | |
| Y 59 | Hoisting & placing in position angle iron purling, channel Iron purling, high tensile Galvanized iron "C" channel, Roof truss & plastic water tank. | kg/ l.ft | 1.65 |
| Y 60 | Supply and lay glass wool with double sided aluminium foil (total thickness is 50mm and 16kg/m3 density) heat reflecting material to underside of roof, supported with Gauge 17, 3" x 3" GI mesh and complete to working order. Rate shall include for scaffolding. | Sqr. | 8,759.00 |
| Y 61 | Truss joint at hipped fixing in position. Rate shall include 10mm thick gusset plates, welding, etc. and application of two coats of Zinc Phosphate paint. | Nr. | 1,887.00 |
| | <u>Z - MAINTANANCE WORK</u> | | |
| | <u>Demolishing</u> | | |
| Z 01 | Demolishing reinforced cement concrete in suspended floors up to 4" thick , removing reinforcement and clearing debris. | Cube | 44,910.00 |
| Z 02 | Demolishing cement concrete and clearing debris in floors from 4" to 6" thick floors. | Cube | 20,520.00 |
| Z 03 | Demolishing reinforced cement concrete in sun shade up to 4" thick , removing reinforcement and clearing debris. | Cube | 24,182.00 |
| Z 04 | Demolishing reinforced cement, concrete in lintol of 9" x 6" removing reinforcement and clearing debris. | L.ft. | 89.00 |
| Z 05 | Demolishing reinforced cement, concrete in lintol of 4 1/2"x 6" removing reinforcement and clearing debris. | L.ft. | 69.00 |
| Z 06 | Demolishing brick piers, stacking brick and clearing debris away. | Cube | 2,936.00 |
| Z 07 | Demolishing 9" thick brick walls stacking brick and clearing debris away. | Cube | 2,936.00 |
| Z 08 | Demolishing 4 1/2" thick brick walls stacking brick and clearing debris away. | Sqr. | 1,321.00 |
| Z 09 | Demolishing 3" thick brick paved floors and clearing debris away. | Sqr. | 1,710.00 |
| Z 10 | Demolishing drains and clearing debris away. | L.ft. | 57.00 |
| Z 11 | Demolishing rubble masonry built in cement and sand, stacking rubble and clearing debris away. | Cube | 4,697.00 |
| Z 12 | Demolishing floor tiles and clearing debris away. | Sqr. | 3,990.00 |
| Z 13 | Demolishing wall tiles and clearing debris away. | Sqr. | 3,230.00 |
| Z 14 | Chipping cement rendering and clearing debris away. | Sqr. | 2,565.00 |
| Z 15 | Chipping cement plastering and clearing debris away. | Sqr. | 1,762.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| Z 16 | Chipping lime plastering and clearing debris away. | Sqr. | 881.00 |
| Z 17 | Chipping cement plaster in soffits and clearing debris away. | Sqr. | 2,642.00 |
| | <u>Masonry work - Small Quantities Up to 1 Square</u> | | |
| Z 18 | 4 1/2" thick brick work in cement and sand 1:5 up to a 1 square. | Sqr. | 26,935.00 |
| Z 19 | 1/2" thick Rendering in cement and sand 1:3 up to a 1 square finished smooth with neat cement slurry and colour pigments. | Sqr. | 10,086.00 |
| Z 20 | 5/8" thick Plastering to walls in cement, equivalent chemical product (Febmix) and sand 1:5 up to a 1 square finished semi-rough with wooden float. (Sand to be sieved). | Sqr. | 10,113.00 |
| Z 21 | 5/8" thick Plastering to walls in cement, lime or equivalent chemical product (Febmix) and sand 1:1:5 up to a 1 square finished smooth with lime putty. (Sand to be sieved). | Sqr. | 13,295.00 |
| | <u>Roof work</u> | | |
| Z 22 | Removing and stacking calicut tile or half round tile from roof in single storied building. | Sqr. | 1,140.00 |
| Z 23 | Removing and stacking calicut tile or half round tile from roof in two storied building. | Sqr. | 1,762.00 |
| Z 24 | Removing and stacking calicut tile or half round tile from roof in three storied building. | Sqr. | 2,349.00 |
| Z 25 | Removing and stacking corrugated cement fibre or asbestos roofing sheet from roof in single storied building. | Sqr. | 881.00 |
| Z 26 | Removing and stacking corrugated cement fibre or asbestos roofing sheet from roof in two storied building. | Sqr. | 1,175.00 |
| Z 27 | Removing and stacking corrugated cement fibre or asbestos roofing sheet from roof in three storied building. | Sqr. | 1,468.00 |
| Z 28 | Removing roof tiles/cement fibre or asbestos roofing sheets and timber frame work, stacking serviceable materials and clearing debris away in single storied building. | Sqr. | 2,349.00 |
| Z 29 | Removing roof tiles/cement fibre or asbestos roofing sheets and timber frame work, stacking serviceable materials and clearing debris away in two storied building. | Sqr. | 2,936.00 |
| Z 30 | Removing roof tiles/cement fibre or asbestos roofing sheets and timber frame work, stacking serviceable materials and clearing debris away in three storied building. | Sqr. | 3,523.00 |
| Z 31 | Removing and stacking calicut ridge tile. | L.ft | 71.00 |
| Z 32 | Removing and stacking cement fibre or asbestos ridging. | L.ft | 59.00 |
| Z 33 | Removing 2" x 1" reepers , 2" x 2" battens ,stacking at site and clearing debris away in single storied building. | L.ft | 12.00 |
| Z 34 | Removing 2" x 1" reepers , 2" x 2" battens ,stacking at site and clearing debris away in two storied building. | L.ft | 18.00 |
| Z 35 | Removing 2" x 1" reepers , 2" x 2" battens ,stacking at site and clearing debris away in three storied building. | L.ft | 24.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| Z 36 | Removing 2" x 4" rafters , 4" x 3" wall plates , stacking at site and clearing debris away in single storied building. | L.ft | 24.00 |
| Z 37 | Removing 2" x 4" rafters , 4" x 3" wall plates , stacking at site and clearing debris away in two storied building. | L.ft | 30.00 |
| Z 38 | Removing 2" x 4" rafters , 4" x 3" wall plates , stacking at site and clearing debris away in three storied building. | L.ft | 36.00 |
| Z 39 | Removing 5" x 3" / 5" x 2" purlings , stacking at site and clearing debris away in single storied building. | L.ft | 36.00 |
| Z 40 | Removing 5" x 3" / 5" x 2" purlings , stacking at site and clearing debris away in two storied building. | L.ft | 42.00 |
| Z 41 | Removing 5" x 3" / 5" x 2" purlings , stacking at site and clearing debris away in three storied building. | L.ft | 47.00 |
| Z 42 | Removing and stacking valance/Barge board materials and clearing debris away in single storied building. | L.ft | 23.00 |
| Z 43 | Removing and stacking valance/Barge board materials and clearing debris away in two storied building. | L.ft | 30.00 |
| Z 44 | Removing and stacking eaves gutter from roof of single storied buildings. | L.ft | 30.00 |
| Z 45 | Removing and stacking eaves gutter from roof of two storied building. | L.ft | 46.00 |
| Z 46 | Removing and stacking down pipes from roof of single storied building. | L.ft | 29.00 |
| Z 47 | Removing and stacking down pipe from roof of two storied building. | L.ft | 37.00 |
| Z 48 | Removing and stacking G.I. Valley gutter and flashing. | L.ft | 59.00 |
| Z 49 | Re-laying available calicut tiles on the roof in single storied building. | Sqr. | 1,175.00 |
| Z 50 | Re-laying available calicut tiles on the roof in two storied building. | Sqr. | 1,468.00 |
| Z 51 | Re-laying available calicut tiles on the roof in three storied building. | Sqr. | 1,762.00 |
| Z 52 | Re-laying available cement fibre or asbestos roofing sheets on the roof in single storied building. | Sqr. | 1,916.00 |
| Z 53 | Re-laying available cement fibre or asbestos roofing sheets on the roof in two storied building. | Sqr. | 2,395.00 |
| Z 54 | Re-laying available cement fibre or asbestos roofing sheets on the roof in three storied building. | Sqr. | 2,874.00 |
| Z 55 | Fixing available Reepers with wire nails. | L.ft | 14.00 |
| Z 56 | Fixing sorted out & cut to required size available timber to roof or other carpentry work. | Cu.ft | 1,671.00 |
| Z 57 | Fixing available corrugated cement fibre or asbestos roofing sheet with hooks , nuts and bolts to roofing. | Sqr. | 3,607.00 |
| Z 58 | Supply and fixing hooks, nuts & bolts for existing cement fibre or asbestos roof. | Nr. | 49.00 |
| Z 59 | Ridge tile bedded in lime cement mortar 1:1:4 and coloured to match tiles.(Ridge tile available at site) | L.ft | 169.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| Z 60 | Fixing of available barge/Valance boards & fascia including cutting and minor repairs. | L.ft | 59.00 |
| Z 61 | Refixing existing G.I. Valley gutter and flashing including repairing any damaged areas. | L.ft | 185.00 |
| Z 62 | Fixing of existing gutter and down pipe including brackets and repairing any damages to the wall. | L.ft | 84.00 |
| | <u>Ceiling work</u> | | |
| Z 63 | Removing cement fibre or asbestos ceiling sheets including timber frame work, stacking serviceable materials and clearing debris away in single storied building. | Sqr. | 2,720.00 |
| Z 64 | Removing cement fibre or asbestos ceiling sheets including timber frame work, stacking serviceable materials and clearing debris away in two storied building. | Sqr. | 3,894.00 |
| Z 65 | Removing ceiling timber frame work, stacking serviceable materiel and clearing debris away in single storied buildings. | Sqr. | 665.00 |
| Z 66 | Removing ceiling timber frame work, stacking serviceable materiel and clearing debris away in two storied buildings. | Sqr. | 958.00 |
| Z 67 | Removing existing cement fibre or asbestos ceiling sheet, stacking materials at the site and clearing debris away. | Sqr. | 1,545.00 |
| Z 68 | Renewing in small quantities of 6" x 5/8" - 3/4" lunumidella ceiling including scaffolding up to 30'-0" hight. | L.ft | 134.00 |
| Z 69 | Fixing available lunumidella ceiling planks with new wire nails. | Sqr. | 5,375.00 |
| Z 70 | Supplying and fixing 1 1/2" x 1/2" thick Beading , Halmilla or equivalent, planning & chamfering complete with brass screws. | L.ft. | 65.00 |
| | <u>Doors, Windows & Partitions</u> | | |
| Z 71 | Removing and stacking door sash only up to 40 S.ft from existing walls. | Nr. | 323.00 |
| Z 72 | Removing and stacking door sash only over 40 S.ft from existing walls. | Nr. | 484.00 |
| Z 73 | Removing and stacking door or window frame size up to 40 S.ft from existing walls. | Nr. | 2,280.00 |
| Z 74 | Removing and stacking door or window frame size over 40 S.ft from existing walls. | Nr. | 3,420.00 |
| Z 75 | Removing and stacking window sash only up to 40 S.ft from existing walls. | Nr. | 323.00 |
| Z 76 | Removing and stacking window sash only over 40 S.ft from existing walls. | Nr. | 484.00 |
| Z 77 | Removing and stacking trellis work | Sq.ft. | 32.00 |
| Z 78 | Removing and stacking glass panes in doors, windows and fanlights. | Sq.ft. | 95.00 |
| Z 79 | Removing and stacking partitions at site including making good to walls & floors. | Sq.ft. | 37.00 |
| Z 80 | Renewing in short lengths with approved timber in existing door or window frames . | L.ft. | 844.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|----------|----------------|
| Z 81 | Door or window frame altering existing rebate fillet using approved quality timber with screws and fixing available sashes. | Nr. | 4,964.00 |
| Z 82 | Fixing available door or window frame. | L.ft. | 43.00 |
| Z 83 | Fixing available door or window sash. | Sq.ft. | 36.00 |
| Z 84 | Removing damage sashes of door or window and preparing & re-fixing. | Per sash | 658.00 |
| Z 85 | Removing existing mortice lock repairing and re-fixing. | Nr. | 1,080.00 |
| Z 86 | Supply and fixing Trellis work 1/2" x 1/2" laths with 2" apart diagonally, horizontally or vertically on existing timber framing. | Sq.ft. | 457.00 |
| Z 87 | Supply and fixing 3mm thick glass panes for the existing door / window or fanlight sashes with approved timber beading. | Sq.ft. | 344.00 |
| | <u>Sanitary</u> | | |
| Z 88 | Removing wash basin , sink or urinals including all fittings and making walls good. | Nr. | 781.00 |
| Z 89 | Removing squatting pan or standing types water closet with plugging sewer connection and repairing the wall & floor. | Nr. | 2,867.00 |
| Z 90 | Disconnecting flushing cistern and removing with plugging water connection and making good of all damaged walls, floors & etc. | Nr. | 2,680.00 |
| Z 91 | Removing 1/2" to 1 1/2" dia. bib tap or stop cock. | Nr. | 108.00 |
| Z 92 | Fixing available ball valve. | Nr. | 323.00 |
| Z 93 | Fixing lavatory type basin to existing brackets. (Tap , waste pipe and basin are available) | Nr. | 2,658.00 |
| Z 94 | Fixing of wash basin, leveling and connecting to existing water connections and making good (Basin, bracket and fittings are available) | Nr. | 3,406.00 |
| Z 95 | Repairing bib taps and stop cocks by fixing leather washers. | Nr. | 333.00 |
| Z 96 | Removing & repairing pillar tap and re-fixing to the wash basin carefully without any damaged. | Nr. | 557.00 |
| Z 97 | Supply & fixing Universal bend of "Rocell" brand & model "Vario Joint" or approved equivalent. | Nr. | 2,107.00 |
| | <u>Painting</u> | | |
| Z 98 | Removing painting from walls and clearing debris away. | Sqr. | 1,175.00 |
| Z 99 | Removing enamel paint from door or window frame and clearing debris away. | Sqr. | 2,349.00 |
| Z 100 | Removing paint from painted glass panes with paint remover. | Sq.ft. | 83.00 |
| Z 101 | Removing water proof layers and/or hot bitumen from concrete floors or flat roof and clearing debris away. | Sqr | 4,560.00 |
| Z 102 | Painting ceiling beading with two coats of enamel paint. | L.ft | 24.00 |
| Z 103 | Painting existing ceiling fan with one coat of anti-corrosive paint & two coats of enemel paint including removing corroded scale and wire brushing. | Nr. | 1,240.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-----------|----------------|
| | <u>AA - LANDSCAPING</u> | | |
| | <u>Turfing</u> | | |
| | <u>Note:</u> | | |
| | Depending on the ground conditions and requirements, turfing shall be decided. Following shall be a guide. | | |
| | (a) For landscaping work involving covering gravel areas item AB02 recommend in combination with item AB01. | | |
| | (b) When grass areas are meant for human traffic, item AB03 & AB05 recommend.(ex. Jogging tracks ,sides) | | |
| | (c) For specific areas item AB04 & AB06 with item AB01. | | |
| AA 01 | Remove roots and loose gravel particles from the area identified for turfing and level or graded to a uniform surface, spread a 150mm thick layer of top vegetable soil comprising of a mixture of earth and coir dust mixed in proportion of 2:1 and raked to a depth of 150mm while removing gravel pieces. | Sq.ft. | 139.00 |
| AA 02 | Supply and placing(laying) buffalo grass turves of size not less than 200mm x 150mm and laid closed butted to one another while ensuring lateral joints between turves being staggered, where necessary turves shall be pegged to the soil to prevent movement or slippage. Thereafter, turfing shall be compacted, levelled and maintained for a period of three(3) months by watering, weeding and trimming, untill roots are firmly rooted in to the ground. | Sq.ft. | 47.00 |
| AA 03 | Supplying grass sods of malesiyan type grown on any soil and laid on jogging tracks, earth slopes etc; Rate inclusive of levelling the ground and maintaining the same for a period of not less than three months . | Sq.ft. | 57.00 |
| AA 04 | Supplying grass sods of Australian type grown on a prepared surface and maintaining the grass including daily watering, spreading fertilizer, weeding and trimming for a period of three(3) months. | Sq.ft. | 100.00 |
| AA 05 | Supplying grass carpet of malesiyan type grown on any soil and laid on jogging tracks, earth slopes etc; Rate inclusive of levelling the ground and maintaining the same for a period of not less than three months . | Sq.ft. | 66.00 |
| AA 06 | Supplying grass carpet of Australian type grown on a prepared surface and maintaining the grass including daily watering, spreading fertilizer, weeding and trimming for a period of three months. | Sq.ft. | 125.00 |
| | <u>Note:</u> In case of landscaping work involving, Planting of ball-rooted trees, flower pots and turfing with area of grass turfing under item AA 02 exceeds 2000 sq.ft, item AA07 may be incorporated subject to the approval of Divisional Engineer. | | |
| AA 07 | Employing a labourer for maintaing the grass ball-rooted trees and flower pots for a period of 3 months. Rate shall include the cost of water, hiring charges for lawn mover/ grass-cutter machine, trimming with hand- held scissors, weeding, re-planting damaged areas and cost of fertilizer. | Per month | 17,955.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|------|----------------|
| | <u>Root Bowlling Of Plants</u> | | |
| AA 08 | Supply & Planting maximum 5'-0" girth and 7'-0" - 8'-0" high Atteria Plant with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 11,762.00 |
| AA 09 | Supply & Planting maximum 5'-0" girth and 8'-0" - 10'-0" high Ehala with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 12,951.00 |
| AA 10 | Supply & Planting maximum 5'-0" girth and 6'-0" - 8'-0" high Araliya Plant with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 9,384.00 |
| AA 11 | Supply & Planting maximum 5'-0" girth and 6'-0" - 8'-0" high Kiripalu Plant with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 10,573.00 |
| AA 12 | Supply & Planting maximum 5'-0" girth and 7'-0" - 8'-0" high Foxtail Palm with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 10,573.00 |
| AA 13 | Supply & Planting maximum 5'-0" girth and 8'-0" - 10'-0" high Kentiya Palm with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 9,384.00 |
| AA 14 | Supply & Planting maximum 5'-0" girth and 6'-0" - 8'-0" high Red Palm with the fertilizing , watering & plant should be maintain for a one week period. | Nr. | 9,384.00 |
| | <u>Paving Blocks</u> | | |
| | Natural Colour Blocks - Item No. AA 15 - AA 22 | | |
| AA 15 | Supply & paving 80mm thick Rectangular(Approx. size 200mm x 100mm) natural colour precast interlocking paving blocks of 40 N/mm ² compressive strength , on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 27,549.00 |
| AA 16 | Supply & paving 80mm thick Rectangular (Approx. size 200mm x 100mm) natural colour precast interlocking paving blocks of 30 N/mm ² compressive strength , on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 24,840.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| AA 17 | Supply & paving 80mm thick Rectangular (Approx. size 200mm x 100mm) natural colour precast interlocking paving blocks of 25 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 24,011.00 |
| AA 18 | Supply & paving 60mm thick Rectangular (Approx. size 200mm x 100mm) natural colour precast interlocking paving blocks of 15 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the Low volume traffic areas or Pedestrian areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 22,076.00 |
| AA 19 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) natural colour precast interlocking paving blocks of 40 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 26,202.00 |
| AA 20 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) natural colour precast interlocking paving blocks of 30 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 23,455.00 |
| AA 21 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) natural colour precast interlocking paving blocks of 25 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 22,540.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------|----------------|
| AA 22 | Supply & paving 60mm thick Non-Rectangular (Approx. size 220mm x 110mm) natural colour precast interlocking paving blocks of 15 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the Low volume traffic areas or Pedestrian areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 21,396.00 |
| | Coloured Blocks - Item No. AB 23 - AA 30 | | |
| AA 23 | Supply & paving 80mm thick Rectangular (Approx. size 200mm x 100mm) coloured precast interlocking paving blocks of 40 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 31,474.00 |
| AA 24 | Supply & paving 80mm thick Rectangular (Approx. size 200mm x 100mm) coloured precast interlocking paving blocks of 30 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 27,605.00 |
| AA 25 | Supply & paving 80mm thick Rectangular (Approx. size 200mm x 100mm) coloured precast interlocking paving blocks of 25 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 26,499.00 |
| AA 26 | Supply & paving 60mm thick Rectangular (Approx. size 200mm x 100mm) coloured precast interlocking paving blocks of 15 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the Low volume traffic areas or Pedestrian areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 24,564.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| AA 27 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) coloured precast interlocking paving blocks of 40 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 33,962.00 |
| AA 28 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) coloured precast interlocking paving blocks of 30 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 25,973.00 |
| AA 29 | Supply & paving 80mm thick Non-Rectangular (Approx. size 220mm x 110mm) coloured precast interlocking paving blocks of 25 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the high volume traffic areas. Paving blocks and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 24,600.00 |
| AA 30 | Supply & paving 60mm thick Non-Rectangular (Approx. size 220mm x 110mm) coloured precast interlocking paving blocks of 15 N/mm ² compressive strength, on 2" thick compacted Quarry dust laid on top of a levelled and well compacted earth sub base for the Low volume traffic areas or Pedestrian areas. Paving blocks should confirming to S.L.S 1425 : Part I & II and subject to the approval of the quality & colour including transport and laying. Rate shall include hire charges of 1/2 - 1 ton vibrating roller. | Sqr. | 23,455.00 |
| | <u>Concrete Curb</u> | | |
| AA 31 | Supply & paving pre cast concrete Curb size 75mm x 175mm x 540mm of 25 N/mm ² compressive strength laid with 1:3 cement mortar on top of a well compacted earth sub base & tied with Grade 20 cement concrete layer of 0' - 6" thick. | L.ft. | 532.00 |
| AA 32 | Supply & paving pre cast concrete Curb size 125mm x 255mm x 450mm of 25 N/mm ² compressive strength laid with 1:3 cement mortar on top of a well compacted earth sub base & tied with Grade 20 cement concrete layer of 0' - 6" thick. | L.ft. | 715.00 |
| AA 33 | Supply & paving pre cast concrete Curb size 125mm x 255mm x 915mm of 25 N/mm ² compressive strength laid with 1:3 cement mortar on top of a well compacted earth sub base & tied with Grade 20 cement concrete layer of 0' - 6" thick. | L.ft. | 627.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|--------|----------------|
| | <u>Cement Flower Pots</u> | | |
| AA 34 | Supply & placing of 12" dia. Cement pots 4'-0" high (size approximate) | Nr. | 1,080.00 |
| AA 35 | Supply & placing of 15" dia. Cement pots 4'-0" high (size approximate) | Nr. | 2,460.00 |
| AA 36 | Supply & placing of 18" dia. Cement pots 4'-0" high (size approximate) | Nr. | 3,120.00 |
| AA 37 | Supply & placing of 24" dia. Cement pots 4'-0" high (size approximate) | Nr. | 5,040.00 |
| AA 38 | Supply & placing of 28" dia. Cement pots 4'-0" high (size approximate) | Nr. | 6,840.00 |
| | <u>Cement Flower Pots of Tapering Square Cross-Section</u> | | |
| AA 39 | Supply & placing of 8"x8" and 12" x 12" Taper flower pot 12" high (size approximate) | Nr. | 783.00 |
| AA 40 | Supply & placing of 10"x10" and 15" x 15" Taper flower pot 18" high (size approximate) | Nr. | 1,044.00 |
| AA 41 | Supply & placing of 6"x6" and 12"x12" Taper flower pot 33" high (size approximate) | Nr. | 1,827.00 |
| | <u>Cement Flower Pots of Square Cross-Section</u> | | |
| AA 42 | Supply & placing of 8" x 8" Square flower pot 12" high (size approximate) | Nr. | 1,140.00 |
| AA 43 | Supply & placing of 15" x 15" Square flower pot 15" high (size approximate) | Nr. | 2,400.00 |
| AA 44 | Supply & placing of 18" x 18" Square flower pot 18" high (size approximate) | Nr. | 3,000.00 |
| AA 45 | Supply & placing of 24" x 24" Square flower pot 24" high (size approximate) | Nr. | 4,800.00 |
| | <u>P.V.C. Coated Chain Link Fence</u> | | |
| AA 46 | Supplying & fixing PVC coated G.I. chain link fence (2" x 2") of gauge 10 on to existing GI pipe and flat iron frame (GI pipe & flat iron measured separately) complete with tension J bolts and tension cords. | Sq.ft. | 138.00 |
| AA 47 | Supplying and fixing 2" dia.x 2.3mm thick Medium quality GI pipe up to 8'-0" clear height above R/R masonry / Concrete wall and 1'-6" length embedded into 1'-0"x 1'-0"x 2'-0" cement concrete base 1:2:4 (3/4") with 1/2" dia. MS rod welded to bottom of G.I. Pipe and drilling 7 Nos. holes to fixed the chain link (chain link measured separately) and fiberglass coping on top. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint. | L.ft. | 439.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| AA 48 | Supplying and fixing 3" dia.x 2.9 mm thick Medium quality GI pipe up to 8'-0" clear height above R/R masonry / Concrete wall and 1'-6" length embedded into 1'-0"x 1'-0"x 2'-0" cement concrete base 1:2:4 (3/4") with 1/2" dia. MS rod welded to bottom of G.I. Pipe and drilling up to 8 Nos. holes to fixed the chain link (chain link measured separately) and fiberglass coping on top. Rate Shall include for applying one coat of etch primer (50% of etch primer base and 50% etch primer activator), one coat of anti-corrosive primer with two coats of enamel paint | L.ft. | 703.00 |
| AA 49 | Supplying and fixing 20mm x 6mm flat iron to existing GI pipe (GI pipe measured separately) to fix the chain link, Rate inclusive of drilling holes of 6mm dia. at 1' 0" c/c. Rate to include for application of one coat of anticorrosive paint and two coats of enamel paint. | L.ft. | 150.00 |
| AA 50 | Supplying and fixing 38mm x 38mm x 6mm angle iron horizontal bracings welded to existing GI pipes. Rate to include for application of one coat of anticorrosive paint and two coats of enamel paint. | L.ft. | 277.00 |
| AA 51 | Supplying and fixing 1" dia. 2mm thick GI pipe horizontal bracings welded to existing GI vertical pipes. Rate to include for application of one coat of anticorrosive paint and two coats of enamel paint. | L.ft. | 184.00 |
| AA 52 | Supplying & fixing 3" dia. G.I cap on G.I pipe posts as directed. | No | 350.00 |
| | <u>Barbed Wire Fence</u> | | |
| AA 53 | Supplying & fixing 2mm dia.gauge 14 galvanized barbed wire, 3" apart on pre-cast concrete fence posts at 8'-0" interval with J bolts & nuts including straining. Maximum distance between barbs should be 100mm and minimum of 4 nodes between barbs.(Concrete fence Posts to be paid seperately) | L.ft. | 11.00 |
| | <u>Fence Post - 7strands</u> | | |
| AA 54 | Supplying & fixing pre-cast concrete corner or starting Posts of size (6'-3" ht. & (5" x 5") for 7 strands of 12mm dia. holes including necessary excavation, reinforced with 4 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 8" c/c and erecting the post and concreting the base with 1:3:6(1"). All details for fence post as per Drawing No:- CC/237/FENCE POST/03 | Nr. | 2,691.00 |
| AA 55 | Supplying & fixing pre-cast concrete Intermediate Posts of size Intermediate posts - 5'-9" ht. & (5 3/4" x 5 3/4") - (3" x 3") for 7strands of 12mm dia. holes including necessary excavation, reinforced with 4 nos of 6mm dia. mild steel bars and 6mm mild steel stirrups @ 8" c/c and erecting the post and concreting the base with 1:3:6(1"). All details for fence post as per Drawing No:- CC/237/FENCE POST/03 | Nr. | 1,779.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|---------|----------------|
| AA 56 | Supplying & fixing pre-cast concrete struts of size - 6'-5" ht. & (5" x 4") - (3" x 3") for 7strands of 12mm dia. holes including necessary excavation, reinforced with 4 nos of 10mm dia. tor steel bars and 6mm mild steel stirrups @ 8" c/c and erecting the post and concreting the base with 1:3:6(1"). All details for fence post as per Drawing No:- CC/237/FENCE POST/03 | Nr. | 1,920.00 |
| | <u>AB - TIMBER STAGE</u> | | |
| AB 01 | Suplying and Laying 8" x 1 1/4" finished size Kumbuk or Teak timber board fixing tongue & groove joint & 2" brass screws as directed including, levelling with timber strips where necessary in stage area. | Sq.ft. | 2,550.00 |
| AB 02 | Suplying and Fixing 5"x2" Balau, Thulan or Kempas panelled timber (Sawn timber) joist at 2'-0" c/c and Suplying and Laying 8" x 1 1/4" finished size Kumbuk or Teak timber board fixing tongue & groove joint & 2" brass screws as directed including, levelling with timber strips where necessary in stage area. | Sq.ft. | 3,100.00 |
| | <u>AC - CONCRETE STRUCTURAL REPAIRS</u> | | |
| | Basic material prices for rates of AC 01 to AC 22 has obtain from Finex Engineering Pvt Ltd. | | |
| | <u>Foundation Repair</u> | | |
| AC 01 | Repairing with refilling of spalled out or cracked concrete column base area including, Chipping the top of the column base and clearing debris away, column base expand by 0'-6" both sides ,Shuttering for sides of column base with 1" thick rubber planking including dismantling , Applying as epoxy bonding agent used to bond fresh the concrete to hardened concrete , Reconcreting with 1:1 1/2:3 (3/4") including vibrating & excluding Curing with a superplasticising Admixture , Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. (Excavation & reinforcement to be paid seperately). All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 01 | per no. | 21,280.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|-------|----------------|
| | <u>Column Jacketting</u> | | |
| AC 02 | Repairing with refilling of spalled out or cracked concrete column area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements , Shuttering for sides of column including dismantling in 15mm thick plywood, Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond the fresh concrete to hardened concrete, Reconcreting with 1:1 1/2:3 (3/4") including vibrating & excluding Curing with a superplasticising Admixture, Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. (If existing bars in the column totally deteriorated , new reinforcements to be fabricated by lapping to existing bars in good condition. These reinforcements are to be estimated seperately. (i.e. These reinforcements are not taken in to account for this rate.) All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 01 | sq.ft | 829.00 |
| AC 03 | Repairing with refilling of spalled out or cracked concrete column area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements , Shuttering for sides of column including dismantling in 15mm thick plywood, Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond fresh concrete to hardened concrete , Reconcreting with flowable micro concrete (Master flow 810 or approved equivalent) , Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. (If existing bars in the column completely deteriorated , new reinforcements to be fabricated by lapping to existing bars in good condition. These reinforcements are to be estimated seperately. (i.e. These reinforcements are not taken in to account for this rate.) All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 01 | sq.ft | 1,471.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|--|-------|----------------|
| | <u>Slab & Slab beam repair with flowable micro concrete</u> | | |
| AC 04 | Repairing with refilling of spalled out or cracked concrete slab beam area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements , Shuttering for sides and bottom of beams including dismantling in 15mm thick plywood, Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond fresh concrete to hardened concrete , Reconcreting with flowable micro concrete (Master flow 810 or approved equivalent) , Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 02 | sq.ft | 2,782.00 |
| AC 05 | Repairing with refilling of spalled out or cracked concrete slab area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements , Shuttering for slab including dismantling in 15mm thick plywood, Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond the fresh concrete to hardened concrete , Reconcreting with flowable micro concrete (Master flow 810 or approved equivalent), Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 02 | sq.ft | 2,338.00 |
| | <u>Slab & Slab beam repair with repair mortar (Trowellable)</u> | | |
| AC 06 | Repairing with refilling of spalled out or cracked concrete slab beam area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements ,Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond the fresh concrete to hardened concrete , Reconcreting with repair mortar (MasterEmaco S 5400 or approved equivalent), Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 02 | sq.ft | 2,855.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|------------|----------------|
| AC 07 | Repairing with refilling of spalled out or cracked concrete slab area including Chipping at about 10 mm beyond the inner surface of the reinforcement to form a regular shape so as to expose the sound concrete & all corroded reinforcements, Cleaning the reinforcement using two coats of Rust Remover, Applying Protection coat for the reinforcement, Applying as epoxy bonding agent used to bond the fresh concrete to hardened concrete ,Reconcreting with repair mortar (MasterEmaco S 5400 or approved equivalent), Applying one coat of concrete curing agent, Applying two coats of high performance anti carbonation coating. All details given in Drawing No:- TYPE PLAN/ STRUCTURAL REPAIRS/2020/DETAIL 02 | sq.ft | 2,526.00 |
| | AD -TESTING CHARGES | | |
| | THE FOLLOWING LABORATORY TEST RATES ARE APPLICABLE WHEN IT IS NECESSARY TO DIRECT ADDITIONAL TESTING OVER AND ABOVE THE MINIMUM TESTING SPECIFIED IN THE SPECIFICATIONS. | | |
| | PLEASE NOTE THAT NO PAYMENT SHOULD BE MADE FOR TESTING MENTIONED IN SPECIFICATION. | | |
| | TESTING OF CONCRETE | | |
| AD 01 | Slump Test of Concrete | Per Test | 843.00 |
| AD 02 | Casting of Concrete Cubes (3 Cubes) | Per Test | 1,960.00 |
| AD 03 | Compressive Strength of Concrete Cubes. | Per Test | 810.00 |
| AD 04 | Rental for casting Mould (1 Mould) | Per Test | 268.00 |
| | TESTING OF CONCRETE PAVING BLOCK | | |
| AD 05 | Compressive Strength of Concrete Paving Block | Per Test | 772.00 |
| | TESTING OF AGGREGATE | | |
| AD 06 | Particle Size Distribution (Sieve Analysis) | Per Test | 2,268.00 |
| AD 07 | Field Density | Per Test | 2,804.00 |
| AD 08 | Modified Compaction Test | Per Test | 5,880.00 |
| AD 09 | Standard Compaction Test | Per Test | 5,619.00 |
| | TESTING OF SOIL | | |
| AD 10 | Particle Size Distribution (Sieve Analysis) | Per Test | 2,274.00 |
| AD 11 | Consistency Limit Test | Per Test | 3,456.00 |
| AD 12 | Field Density | Per Test | 2,063.00 |
| AD 13 | California Bearing Ratio (CBR) | Per Test | 4,731.00 |
| AD 14 | Modified Compaction Test | Per Test | 4,461.00 |
| AD 15 | Standard Compaction Test | Per Test | 4,229.00 |
| | TESTING OF REINFORCEMENT | | |
| AD 16 | Rate for testing of Tor-steel specimen of 1m length for mechanical properties at an approved laboratory. | Per Sample | 3,800.00 |
| | TESTING OF TIMBER | | |
| AD 17 | Testing of a timber sample for identification from the Timber corporation laboratory. | Per Test | 2,400.00 |
| | TESTING OF WATER PRESSURE | | |
| AD 18 | Water Pressure testing for PVC pipes for 6 bars. | Item | 1,200.00 |

| ITEM NO. | DESCRIPTION | UNIT | RATE 2020/2021 |
|----------|---|---------------------------------|----------------|
| | TESTING OF WATER TANKS AND SLUMPS | | |
| AD 19 | Testing of Water tanks & Sumps as per clause 3.8.6 of SCA/4/11 | Item | 4,800.00 |
| | WHEN TESTS ARE CARRIED OUT IN THE FIELD, TRANSPORT CHARGES SHALL BE ADDED IN ADDITION TO THE TESTING CHARGES. | | |
| AD 20 | Transport charges for testing. | Per km | 45.90 |
| | <u>AE - MISCELLANEOUS</u> | | |
| | The following AE 01 & AE 02 items are exclusively for estimating purposes for which a standard work norm is not immediately available and at the same time it is impossible to arrive at a realistic break-up of labour component involved at the time of preparation of the estimate. The rate is not to be used for engaging labourers on routine work and the mere appearance of this rate on BSR is not a sanction to pay the daily labourers at this rate. Skillness of the Craftman to be verified by a trade test certificate at the time of engagement. | | |
| AE 01 | Engaging special skilled labour services in the trades of fitter, electrician, welder, mason, carpenter, bar bender, painter on 8 hour day basis. (Rate Include 20% over head & profit) | Per 8 Hour day Per Person | 2,880.00 |
| AE 02 | Engaging labour services in un-skilled category of any type of manual work on a 8 hour day basis. (Rate Include 20% over head & profit) | Per 8 Hour day Per Person | 2,280.00 |
| AE 03 | Supplying and fixing 10-0" 'x3'-6" size green board for class rooms | sq.ft | 488.00 |
| AE 04 | Compressed soil stabilized un - plastered wall built using earth blocks of size 220mm x 220mm x130mm (allow +_ 10mm only for the length) solid type (confirming to SLS 1382 and subject to the approval of the quality of the blocks, dry compressive strength grade 3.28 up to 4.0 N/mm ² , Wet compressive strength - grade 3> 1.2 up to 1.6 N/mm ² . Pitting depth (erosion resistance) <10mm) in cement and sand 1:5 mortar to filling the groove and painting the exposed groove to match the bricks. rate shall include for 1/2 thick plaster band to bonding surface of brick & concrete. | Sqr. | 50,055.00 |